

ECMA/TC38-TG3/2015/026 (Rev. 1 – 15 April 2017)

### Annex B2 - Product environmental attributes Desktop/All-in-One Computers

The declaration may be published only when all rows and/or fields marked with \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lenovo	Logo
Company name *	Lenovo	and the second second second second
Contact information *	Lenovo Global Environmental Affairs	Lenovo
e-mail address	Alvin L Carter	LEI IOVO.
	alcarter@lenovo.com	and the second se
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment	.html
Additional information	The latest version of this document can be found at:	
	http://www.lenovo.com/ecodeclaration	

The company declares (based on product specification or test results based obtained from sample testing), that the product						
conforms to the statements given in this declaration.						
Type of product *	All in one computer					
Commercial name *	IdeaCentre AIO 3 24ALC6					
Model number *	F0G1					
Issue date *	2021/4/23					
Intended market *	🛛 Global 🔲 🗆 Europe 📃 Asia, Pacific & Japan 🔛 Americas 💭 Other					
Additional information						

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

#### About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products.

Model n	umber *	F0G1 Logo	Low	-	
lssue da	ate *	2021/4/23	Len	ove	2
Produc	t environ	mental attributes - Legal requirements	Require	ment	t met
Item			Yes	No	n.a.
P1		ous substances and preparations			
P1.1*	Product	s do comply with current European RoHS Directive. (See legal reference and NOTE B1)	$\square$		
P1.2*		s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value.	$\square$		
P1.3*	hydrobro trichloro	s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), pmofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- ethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum ration values.			
P1.4*	terpheny	s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated /I (PCT) in preparations (see legal reference).	$\square$		
P1.5*	chain co	s do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).			
P1.6*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm <sup>2</sup> /week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:2011-5.				
P1.7*	REACH	Article 33 information about substances in articles is available at (add URL or mail contact): www.lenovo.com/us/en/Lenovo-REACH-SVHC-Disclosure	$\boxtimes$		
P2	Batterie				
P2.1*	If the pro symbol.	oduct contains a battery or an accumulator, the battery/accumulator is labeled with the disposal Information on proper disposal is provided in user manual. (See legal reference)	$\square$		
P2.2*	Batterie: referenc	s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See lega e)	al 🖂		
P2.3*	Batterie	s and accumulators are readily removable. (See legal reference)	$\square$		
P3	Conform	nity verification & Eco design (ErP)			
P3.1*	The Dec	duct is CE-marked to show conformance with applicable legal requirements (see legal reference). claration of Conformity can be requested at (add link or e-mail address): www.lenovo.com/us/en/compliance/eu-doc			
P3.2*	The pro	duct complies with the Eco design requirements for energy-related products, al reference).	$\boxtimes$		
		d information is; given in item P15 or added to this document, available at (add URL): www.lenovo.com/us/en/compliance/eco-declaration			
P5		t packaging			
P5.1*	Packagi	ng and packaging components do not contain more than 0,01% lead, mercury, cadmium ar ent chromium by weight of these together.	nd 🔀		
P5.2*	The pac	kaging materials are marked with abbreviations and numbers indicating the nature of the material ( se legal reference).	s) 🔀		
P5.3*	The pro	Juct packaging material is free from ozone depleting substances as specified in the Montreal Protoc al reference). nt: Legal reference has no maximum concentration values.	ol 🔀		
P6		nt information			

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model nu	ımber *	F0G1	Logo	Lon	-	
Issue dat	te *	2021/4/23		Len	ovo	-
Product	environ	mental attributes - Market requirements (See General NOTE GN	below)			
		onmental conscious design		Require		
Item <b>P7</b>		tory to fill in. Additional information regarding each item may be found under P14. <b>Disassembly, recycling</b>		Yes	No	n.a.
P7.1*		at have to be treated separately are easily separable				
P7.2*		naterials in covers/housing have no surface coating.			╶┤╴	$\exists$
P7.3*		arts > 100 g consist of one material or of easily separable materials.			╞	$\exists$
P7.4*	Plastic p		╶┼┤	$\exists$		
P7.5		available tools		╞	$\exists$	
P7.6*		arts are free from metal inlays or have inlays that can be removed with commonly re easily separable. (This requirement does not apply to safety/regulatory labels).			╞	$\exists$
		lifetime				
P7.7*		ng can be done e.g. with processor, memory, cards or drives				
P7.8*	Upgradir	ng can be done using commonly available tools			Ē	Ē
P7.9		arts are available after end of production for: 5 years				T I
P7.10		is available after end of production for: 5 years				T I
		and substance requirements				
P7.11*	Material		ial type:			
P7.12	Insulatio	n materials of external electrical cables are PVC free.			$\square$	
P7.13		n materials of internal electrical cables are PVC free.			$\boxtimes$	
P7.14	weight ( polyvinyl	plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) 1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flam I chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine an 25% post-consumer recycled content.	ne retardants, a	nd 📃		
P7.15		circuit boards, PCBs (without components) are low halogen: all ⊠ PCBs > 25 g [ ed in IEC 61249-2-21. (See 1NOTE B2)	are low halog	en	$\boxtimes$	
P7.16	Flame re Marking:	etarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4				
P7.17	TBBF	hemical specifications of flame retardants in printed circuit boards > 25 g (without of PA (additive), TBBPA (reactive) (See NOTE B3), Other: <i>aromatic brominat</i> 9003-35-4		, 🛛		
		nemical specifications of flame retardants in printed circuit boards (without compor g ISO 1043-4:	nents) > 25 g			
P7.18	concentr 1. Chem 2. Chem	lame retarded plastic parts > 25 g contain the following flame retardant substanc rations above 0,1%: ical name: <b>confidential</b> , CAS #: <b>confidential</b> (See NOTE B4) ical name: , CAS #:	es/preparations	in 🔀		
	<u>Alt. 2: </u> Cl <i>FR(40)</i> <			• 🖂		
P7.19		c parts > 25 g, flame retardant substances/preparations above 0,1% are used whic d the following Risk phrases; and Hazard statements:	h have been			
			See note B5)			
P7.20*	lf YES; a	sumer recycled plastic material content is used in the product (See Note B6): at least one of the two alternatives below shall be answered;				
	or a p	total plastic parts' weight > 25 g, the postconsumer recycled plastic material conte ercentage of total plastic by weight) is <b>11.4%</b> . (black ) <b>11.25%</b> . (White ). e weight of recycled material is <b>137.7</b> g. (black) <b>137.7</b> g. (White )	ni (caiculated as	5		

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model number *	F0G1	Logo	Lenovo
Issue date *	2021/4/23		
Product environm	nental attributes - Market requirements (continued)		Requirement met

. . . . .

Item

Requirement metYesNon.a.

P8         Batteries           P8.1*         Battery chemical composition: Manganese dioxide           P9         Energy consumption (See NOTE B8)           P9.1         For the product the following power levels or energy consumptions.           Energy mode *         Power level at 100 V AC         Power level at 115 V AC           Peak (On-max)         W         W           Category2         Short Idle State - WOL         15.94 W         15.15 W         15           Short Idle State - WOL         6.00 W         5.9 W         6.1           Enabled         0.67 W         0.67 W         0.3           Sleep (S3) - WOL Enabled         0.67 W         0.47 W         0.3           Off (S5) - WOL Enabled         0.22 W         0.24 W         0.3           EPS No-load         W         W         0.144 W         0.1           Wail addet but discontedet from the product)         W         W         0.1           PTEC *         S0.08 kWh/year         47.94 kWh/year         50           Annual Energy Consumption         Power Off Mode(S5) - WOL Enabled; Pathege SK         50           Pather and power supply Efficiency Level (International Efficiency Marking Protoco         50           Display resolution * : 2.07 megapixels         Default time to ente		
a) Of total plastic parts' weight > 25 g, the biobased plastic mater total plastic by weight) is %. or b) The weight of the biobased plastic material is g. P7.22* Light sources are free from mercury, i.e. less than 0,1 mg/lamp. If fmercury is used specify: Number of lamps: and maximum of P8 Batteries P8.1* Battery chemical composition: Manganese dioxide P9 Energy consumption (See NOTE B8) P9.1 For the product the following power levels or energy consumptions. Energy mode * Power level at Power level at Pack (On-max) W W W Category2 Short idle State - WOL 15.94 W 15.15 W 15 Enabled Long idle State - WOL 15.94 W 5.9 W 6.1 Enabled Sleep (S3) - WOL Enabled 0.67 W 0.67 W 0.7 Off (S5) - WOL Enabled 0.67 W 0.24 W 0.3 ETEC * W W Cypical Energy Consumption ETEC * Solve for the metadult of the the solve set of the solve set of the metadult of the solve set of th	ΓE B7):	
P7.22*       Light sources are free from mercury, i.e. less than 0,1 mg/lamp. If mercury is used specify: Number of lamps: and maximum in P8         P8       Batteries         P8.1*       Battery chemical composition: Manganese dioxide         P9       Energy consumption (See NOTE B8)         P9.1       For the product the following power levels or energy consumptions.         Energy mode *       Power level at 100 V AC         Peak (On-max)       W         W       W         Category2       If 5.94 W         Short Idle State - WOL       6.00 W         Enabled       6.00 W         Sleep (S3) - WOL Enabled       0.67 W         Off (S5) - WOL Enabled       0.22 W         Off (S5) - WOL Enabled       0.22 W         Verternal power supply / charger plugged in the wal outlet but disconneed from the product)       W         PTEC *       W         Annual Energy Consumption       50.08 kWh/year         EERE *       W       W         Part: Off Mode(S5) - WOL Enabled; Palseg: Side         External Power Supply Efficiency Level (International Efficiency Marking Protocol)         Part: Off Mode(S5) - WOL Enabled; Palseg: Side         External Power Supply Efficiency class (monitors only): N/A         P10       Emissions <t< td=""><td></td><td>ed as a percentage of</td></t<>		ed as a percentage of
If mercury is used specify: Number of lamps:       and maximum if         P8       Batteries         P8.1*       Battery chemical composition:         Managemese dioxide       Power levels or energy consumptions.         Energy mode*       Power levels or energy consumptions.         Energy mode*       Power levels or energy consumptions.         Energy mode*       Power level at 100 V AC 115 V AC         Peak (On-max)       W         W       W         Category2       Ison 15.5 W         Short Idle State - WOL       15.94 W         Enabled       6.00 W         Long Idle State - WOL       6.00 W         Enabled       0.67 W       0.67 W         Sleep (S3) - WOL Enabled       0.67 W       0.67 W         Off (S5) - WOL Enabled       0.22 W       0.24 W       0.3         EPS No-load       W       W       0.144 W       0.1         (External power supply charger plugged in the wait outel but disconneeted from the product)       W       W       0.24 W         PTEC *       Annual Energy Consumption       50.08 kWh/year       47.94 kWh/year       50         Part: Off Mode(S5) - WOL Enabled; Pattery: Strest       External Power Supply Efficiency Level (International Efficiency Marking Protoce       50		
P8.1*       Battery chemical composition: Manganese dioxide         P9       Energy consumption (See NOTE B8)         P9.1       For the product the following power levels or energy consumptions.         Energy mode *       Power level at 100 V AC       Power level at 115 V AC         Peak (On-max)       W       W         Category2       Is.94 W       15.15 W       15         Short Idle State - WOL Enabled       6.00 W       5.9 W       6.3         Sleep (S3) - WOL Enabled       0.67 W       0.67 W       0.3         Off (S5) - WOL Enabled       0.22 W       0.24 W       0.3         Off (S5) - WOL Enabled       0.67 W       0.67 W       0.3         Etter * Valuational but disconneeded from the product.       W       W       Q         PTEC * Valuational Energy Consumption       So.08 kWh/year       47.94 kWh/year       50         Default time to enter energy save mode:       25 minutes       99.2*       Information about the energy save function is provided with the product Display resolution * : 2.07 megapixels       Declared according to ISO 9296 (See NOTE B9)         P10.1       Mode       Mode description       Si       Si       Si         Mode       Mode description       Si       Si       Si       Si       Si       Si	n mercury content per	lamp: mg
P9       Energy consumption (See NOTE B8)         P9.1       For the product the following power levels or energy consumptions in the following power level at the following powerelevel at the following powerelevel at the following		
P9.1       For the product the following power levels or energy consumptions is Energy mode *       Power level at 115 V AC         Peak (On-max)       W       W         Category2       Short Idle State - WOL       15.94 W         Short Idle State - WOL       6.00 W       5.9 W         Enabled       6.00 W       5.9 W         Sleep (S3) - WOL Enabled       0.67 W       0.67 W         Off (S5) - WOL Enabled       0.22 W       0.24 W       0.3         Off (S5) - WOL Enabled       0.22 W       0.24 W       0.3         EPS No-load       W       W       W       0.144 W         (External power supply / charger plugged in the wal outlet but disconnected from the product)       W       W       W         PTEC *       W       W       W       0.144 W       0.1         External Power Supply Charger plugged in the wal outlet but disconnected from the product)       W       W       W         PTEC *       W       W       W       D       State		
Energy mode *       Power level at 100 V AC       Power level at 115 V AC         Peak (On-max)       W       W         Category2       Short Idle State - WOL       15.94 W       15.15 W       15         Short Idle State - WOL       6.00 W       5.9 W       6.1         Inabled       0.67 W       0.67 W       0.67         Short Idle State - WOL       6.00 W       5.9 W       6.1         Short Idle State - WOL       0.67 W       0.67 W       0.7         Gff (S5) - WOL Enabled       0.67 W       0.67 W       0.3         Off (S5) - WOL Enabled       0.22 W       0.24 W       0.3         EPS No-load       W       0.144 W       0.1         Value Oute Undescontext from the product.)       W       W       0.144 W       0.1         PTEC *       W       W       W       V       15         External Power Supply Efficiency Level (International Efficiency Marking Protocol Display resolution * 1 2.07 megapixels       50       0.8 kWh/year       47.94 kWh/year       50         Default time to enter energy save mode: 25 minutes       Power Oute and sout the energy save function is provided with the protocol Display resolution * 1 2.07 megapixels       Poese function is provided with the protocol Display resolution * 1 2.07 megapixels       Poese function is provide		
100 V AC       115 V AC         Peak (On-max)       W       W         Category2       Short Idle State - WOL       15.94 W       15.15 W       15         Shord Idle State - WOL       6.00 W       5.9 W       6.1         Enabled       0.67 W       0.67 W       0.7         Off (S5) - WOL Enabled       0.67 W       0.67 W       0.7         Off (S5) - WOL Enabled       0.22 W       0.24 W       0.3         EPS No-load       W       0.144 W       0.1         (External power supply / charger plugged in the wall outlet but disconnected from the product.)       W       W       W         PTEC *       W       W       W       0.1       Steep:		
Category2       Image: State - WOL Enabled       15.94 W       15.15 W       15         Long Idle State - WOL Enabled       6.00 W       5.9 W       6.1         Sleep (S3) - WOL Enabled       0.67 W       0.67 W       0.7         Off (S5) - WOL Enabled       0.22 W       0.24 W       0.3         EPS No-load       W       0.144 W       0.3         (External power supply charger plugged in the wall outlet but disconnected from the product).       W       0.144 W       0.3         PTEC *       W       W       0.144 W       0.3         EPS No-load       W       0.144 W       0.3         EPS Carrent power supply charger plugged in the wall outlet but disconnected from the product).       W       W       0.144 W         PTEC *       W       W       W       0.144 W       0.3         External power supply consumption       External Power Supply Efficiency Level (International Efficiency Marking Protocol Display resolution * : 2.07 megapixels       Default time to enter energy save mode: 25 minutes       50         P9.2*       Information about the energy save function is provided with the protocol Display resolution * : 2.07 megapixels       External Power Supply Efficiency class (monitors only): N/A       P10         P10       Emissions       Mode description       S1	Power level at 230 V AC	Reference/Standard for energy modes and test method *
Short Idle State - WOL       15.94 W       15.15 W       15         Enabled       6.00 W       5.9 W       6.1         Sleep (S3) - WOL Enabled       0.67 W       0.67 W       0.7         Off (S5) - WOL Enabled       0.22 W       0.24 W       0.3         EPS No-load       W       0.144 W       0.1         (External power supply / charger plugged in the wall outlet but disconnet defrom the product.)       W       0.144 W       0.1         PTEC *       W       W       0.144 W       0.1         EPS No-load       W       W       0.144 W       0.1         Wall outlet but disconneted from the product.)       W       W       0.1         PTEC *       W       W       W       0.1         Annual Energy Consumption       50.08 kWh/year       47.94 kWh/year       50         External Power Supply Efficiency Level (International Efficiency Marking Protocol Display resolution * : 2.07 megapixels       50       50.08 kWh/year       50         Default time to enter energy save mode: 25 minutes       59.2*       Information about the energy save function is provided with the proot P9.3       Energy efficiency class (monitors only): N/A         P10       Emissions       Noise emission – Declared according to ISO 9296 (See NOTE B9         P10.1	W	Full load
Enabled       6.00 W       5.9 W       6.1         Sleep (S3) - WOL Enabled       0.67 W       0.67 W       0.7         Off (S5) - WOL Enabled       0.67 W       0.67 W       0.7         Off (S5) - WOL Enabled       0.22 W       0.24 W       0.3         EPS No-load       W       0.144 W       0.1         (External power supply / charger plugged in the wall outlet but disconnected from the product.)       W       W       0.144 W       0.1         PTEC *       W       W       W       0.144 W       0.1       1         Variational Energy Consumption       W       W       W       1       1         ETEC *       S0.08 kWh/year       47.94 kWh/year       50         Annual Energy Consumption       Form: Off Mode(S5) - WOL Enabled; Paleop: Steep       50         External Power Supply Efficiency Level (International Efficiency Marking Protoco       Display resolution * : 2.07 megapixels       50         Default time to enter energy save mode: 25 minutes       P9.2*       Information about the energy save function is provided with the proc         P9.3       Energy efficiency class (monitors only): N/A       P10       Emissions         Noise emission – Declared according to ISO 9296 (See NOTE B9       P10.1       Mode       Mode description       S		
Enabled       Sleep (\$3) - WOL Enabled       0.67 W       0.67 W       0.7         Off (\$5) - WOL Enabled       0.22 W       0.24 W       0.5         EPS No-load       W       0.144 W       0.5         (External power supply / charger plugged in the wall outlet but disconnected from the product.)       W       0.144 W       0.1         PTEC *       W       W       W       V       0.144 W       0.1         Typical Energy Consumption       ETEC *       W       W       V       V         ETEC *       50.08 kWh/year       47.94 kWh/year       50         Annual Energy Consumption <i>Post: Off Mode(\$5) - WOL Enabled; Psiloep: Stell</i> 50         External Power Supply Efficiency Level (International Efficiency Marking Protocol)       50         Display resolution * : 2.07 megapixels       50       50         Default time to enter energy save mode: 25 minutes       50         P9.2 *       Information about the energy save function is provided with the prodocol       50         P3.3       Energy efficiency class (monitors only): N/A       50         P10       Emissions       50       50         Noise emission – Declared according to ISO 9296 (See NOTE B9       50         P10.1       Mode       Mode description	15.94 W	Use for ENERGY STAR V8 registration (P <sub>idle</sub> )
Off (S5) - WOL Enabled       0.22 W       0.24 W       0.3         EPS No-load       W       0.144 W       0.1         (External power supply / charger plugged in the wall outlet but disconnected from the product.)       W       0.144 W       0.1         PTEC *       W       W       W       W       0.144 W       0.1         PTEC *       W       W       W       W       0.144 W       0.1         ETEC *       W       W       W       W       0.144 W       0.1         Annual Energy Consumption       50.08 kWh/year       47.94 kWh/year       50         External Power Supply Efficiency Level (International Efficiency Marking Protocol Display resolution * : 2.07 megapixels       Default time to enter energy save mode: 25 minutes       99.2*         Default time to enter energy save mode: 25 minutes       P9.2*       Information about the energy save function is provided with the protocol P9.3       Energy efficiency class (monitors only): N/A         P10       Emissions       Noise emission – Declared according to ISO 9296 (See NOTE B9         P10.1       Mode       Mode description       S         Idle       * HDD idle       *       *         Operation       * HDD Operating       *       *	6. <b>12</b> W	Use for ENERGY STAR V8 registration (P <sub>idle</sub> )
EPS No-load       W       0.144 W       0.1         (External power supply / charger plugged in the wall outlet but disconnected from the product.)       W       W       0.144 W       0.1         PTEC *       W       W       W       W       0.144 W       0.1         PTEC *       W       W       W       W       0.144 W       0.1         PTEC *       W       W       W       W       W       0.1         Annual Energy Consumption       50.08 kWh/year       47.94 kWh/year       50         External Power Supply Efficiency Level (International Efficiency Marking Protocol Display resolution * : 2.07 megapixels       E         Default time to enter energy save mode: 25 minutes       P9.2*       Information about the energy save function is provided with the protocol P9.3       Energy efficiency class (monitors only): N/A         P10       Emissions       Noise emission – Declared according to ISO 9296 (See NOTE B9         P10.1       Mode       Mode description       S         Idle       * HDD idle       *       *         Operation       * HDD Operating       *       *         Other mode       Declared A-weighted sound pressure level (dB) L_pAm       *	0.73 W	Use for ENERGY STAR V8 registration(P <sub>sleep</sub> )
(External power supply / charger plugged in the wall cutlet but disconnected from the product.)       W       W         PTEC *       W       W       W         Typical Energy Consumption       50.08 kWh/year       47.94 kWh/year       50         ETEC *       So.08 kWh/year       47.94 kWh/year       50         Annual Energy Consumption       Point: Off Mode(S5) - WOL Enabled; Psileep: Site       50         External Power Supply Efficiency Level (International Efficiency Marking Protocol       Display resolution * : 2.07 megapixels       50         Default time to enter energy save mode: 25 minutes       P9.2 *       Information about the energy save function is provided with the protocol         P9.3       Energy efficiency class (monitors only): N/A       P10       Emissions         Noise emission – Declared according to ISO 9296 (See NOTE B9)       P10.1       Mode       Mode description       S         Idle       * HDD idle       *       *       Operation       *       S         Other mode       Declared A-weighted sound pressure level (dB) LpAm       *	0.30 W	Use for ENERGY STAR V8 registration(P <sub>off</sub> )
PTEC * Typical Energy Consumption       W       W         ETEC * Annual Energy Consumption       50.08 kWh/year       47.94 kWh/year       50         External Power Supply Efficiency Level (International Efficiency Marking Protocol Display resolution * : 2.07 megapixels       50       90.02 kWh/year       50         Default time to enter energy save mode: 25 minutes       50       99.2 k       Information about the energy save function is provided with the protocol P9.3 Energy efficiency class (monitors only): N/A       70         P10       Emissions       50         Noise emission – Declared according to ISO 9296 (See NOTE B9)       9         P10.1       Mode       Mode description       S         Idle       * HDD idle       *       *         Operation       * HDD Operating       *         Other mode       Declared A-weighted sound pressure level (dB) L_pAm	0. <b>191</b> W	
ETEC * Annual Energy Consumption       50.08 kWh/year       47.94 kWh/year       50         Port: Off Mode(S5) - WOL Enabled; Psileop: Site       Port: Off Mode(S5) - WOL Enabled; Psileop: Site       Site         External Power Supply Efficiency Level (International Efficiency Marking Protocol Display resolution * : 2.07 megapixels       50         Default time to enter energy save mode: 25 minutes       99.2*       Information about the energy save function is provided with the protocol P9.3       Energy efficiency class (monitors only): N/A         P10       Emissions       Noise emission – Declared according to ISO 9296 (See NOTE B9)         P10.1       Mode       Mode description       S         Idle       * HDD Operating       *         Other mode       Declared A-weighted sound pressure level (dB) LpAm	W	$\square$
External Power Supply Efficiency Level (International Efficiency Marking Protocol         Display resolution * : 2.07 megapixels         Default time to enter energy save mode: 25 minutes         P9.2*       Information about the energy save function is provided with the prod         P9.3       Energy efficiency class (monitors only): N/A         P10       Emissions         Noise emission – Declared according to ISO 9296 (See NOTE B9)         P10.1       Mode         Mode       Mode description         Idle       * HDD idle         Operation       * HDD Operating         Other mode       Declared A-weighted sound pressure level (dB) L_pAm	50.52 kWh/year	$E_{TEC} = (8760/1000) \times (P_{off} \times 0.45)$ + $P_{sleep} \times 0.05 + P_{long_ldle} \times 0.15 + P_{short_ldle} \times 0.35)$
Display resolution * : 2.07 megapixels         Default time to enter energy save mode: 25 minutes         P9.2*       Information about the energy save function is provided with the proceed of the energy save function is provided with the proceed of the energy save function is provided with the proceed of the energy save function is provided with the proceed of the energy save function is provided with the proceed of the energy save function is provided with the proceed of the energy save function is provided with the proceed of the energy save function is provided with the proceed of the energy save function is provided with the proceed of the energy save function is provided with the proceed of the energy save function is provided with the proceed of the energy save function is provided with the proceed of the energy save function is provided with the proceed of the energy save function is provided with the proceed of the energy save function is provided with the proceed of the energy save function is provided with the proceed of the energy save function is provided with the proceed of the energy save function is provided with the proceed of the energy save function is provided of the energy save function is prov		Enabled; P <sub>idle</sub> : Idle State - WOL Enabled
Default time to enter energy save mode: 25 minutes         P9.2*       Information about the energy save function is provided with the proceed of the proced of the proceed of the proceed of the proceed of the p	) (ICOI) : VI	
P9.2*       Information about the energy save function is provided with the prod         P9.3       Energy efficiency class (monitors only): N/A         P10       Emissions         Noise emission – Declared according to ISO 9296 (See NOTE B9)         P10.1       Mode       Mode description         Idle       * HDD idle       *         Operation       * HDD Operating       *         Other mode       Declared A-weighted sound pressure level (dB) L_pAm		
P9.3       Energy efficiency class (monitors only): N/A         P10       Emissions         Noise emission – Declared according to ISO 9296 (See NOTE B9)         P10.1       Mode         Mode       Mode description         Idle       * HDD idle         Operation       * HDD Operating         Other mode       Declared A-weighted sound pressure level (dB) L <sub>pAm</sub>		
P10         Emissions           Noise emission – Declared according to ISO 9296 (See NOTE B9)           P10.1         Mode         Mode description         S           Idle         * HDD idle         *           Operation         * HDD Operating         *           Other mode         Declared A-weighted sound pressure level (dB) L <sub>pAm</sub>	oduct.	
Noise emission – Declared according to ISO 9296 (See NOTE B9)           P10.1         Mode         Mode description         S           Idle         * HDD idle         *           Operation         * HDD Operating         *           Other mode         Declared A-weighted sound pressure level (dB) L <sub>pAm</sub>		
P10.1       Mode       Mode description       S         Idle       * HDD idle       *         Operation       * HDD Operating       *         Other mode       Declared A-weighted sound pressure level (dB) L <sub>pAm</sub>	20)	
Idle       * HDD idle       *         Operation       * HDD Operating       *         Other mode       Declared A-weighted sound pressure level (dB) L <sub>pAm</sub>		A-weighted sound power level, $L_{WA,c}$ (B)
Operation         * HDD Operating         *           Other mode         Declared A-weighted sound pressure level (dB) L <sub>pAm</sub>	* 2.8	
Other mode Declared A-weighted sound pressure level (dB) L <sub>pAm</sub>	* 2.9	<u>L</u>
Other mode Declared A-weighted sound pressure level (dB)	19 (operator position	desktop – idle)
	21 (operator position	desktop – operating)
Measured according to: ISO 7779 ECMA-74		<b></b>

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available; see <u>http://www.ecma-international.org/publications/standards/Ecma-370.htm</u>

NOTE B9 A Guidance document on Acoustic Noise is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

Model nu	umber *	F0G1			Logo	Long		
Issue da	te *	2021/4/23				Leno	vo	
Product	t environ	mental attributes	s - Market requirements	(continued)		Require	ment	met
Item						Yes	No	n.a.
	Electro	magnetic emissio	ns					
P10.4		er display meets th n(s): CE,FCC,VCCI	e requirement for low frequer , <b>C-<i>Tick</i></b>	ncy electromagnetic fields	s of the following volunta	ry 🔀		
P12		mics for computir						
P12.1*			nomic requirements of ISO 9				$\square$	
P12.2*	The phy	vsical input device n	neets the requirements of ISC	O 9995 and ISO 9241-41	0.		$\times$	
P13	Packag	ing and document	tation					
P13.1*	Product Product Product	packaging materia packaging materia packaging materia	I type(s): Corrugated Doubl I type(s): Plastic-Solid EPE I type(s): Plastic-HDPE (high I type(s): Corrugated single	(solid Expanded polyet h density polyethylene)	hylene weight (kg): (			
P13.2*			kaging is free from PVC.			$\boxtimes$		
P13.3*		duct primary corru	gated fiberboard packaging, content: <b>80</b> %	specify the contained p	ercentage of minimum	post-		
P13.4*	Specify	media for user and tronic, 🔀 Paper, 📘	product documentation (tick Other	box):				
P13.5	Ùser an		item if paper documentation tation on paper media is chlo					
	Totally of	chlorine-free				$\boxtimes$		
		tal chlorine-free						
	Process	ed chlorine-free						
P14	Volunta	ary programs						
P14.1			uirements of the following vol	untary program(s):				
	Eco-lab Eco-lab Eco-lab		Criteria version: <b>V8</b> Criteria version: Criteria version:	Date: <b>2021/03/30</b> Date: Date:	Product category: <b>1,2</b> Product category: Product category:			
P15	Additio	nal information (S	ee NOTE B10)					
P9	Energy Ryzen	consumption of s 3 5300U, Ryzen 5 {	pecific configuration may 5500U, Ryzen 7 5700U ; GP	vary; description of the U : NA ; RAM : 8+8G ; S	tested product configu torage : 1T HDD+512G	ration: CPU SSD ; OS :W	: AMI IN10	)
	informa knowled provide informa	tion contained in thi lge available at the d here is approxima tion.	representations, guarantees, s document. All information p time of completion, and supp te and provided for informati	provided by supplier in thi blier shall have no obligat onal purposes only. See a	s document is provided i ion to update such inform a Lenovo Account Repre	based on supp nation. The int	olier's format	ion
P9			Notebooks & Tablet Compute index.cfm?fuseaction=find a					_

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

## Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1
Regulation (EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC ( Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1

# Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

### Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	IdeaCentre AIO 3 24ALC6	Logo
Model Number	F0G1	Longua
Issue Date	2021/4/23	Lenovo.
Additional information		

(d)	year of manufacture:				2021
(e)	Etec value (kWh) per ErP Lot 3 Categorian disabled and if the system is tested with				cards (dGfx) are
f)	Etec value (kWh) per ErP Lot 3 Catego enable	ry and capability adjus	tments applied when <b>a</b>	all discrete graphics o	cards (dGfx) are
		Category A (according to ErP Lot 3)	Category B (according to ErP Lot 3)	Category C (according to ErP Lot 3)	Category D (according to ErP Lot 3)
	Memory over base [GB]				16
ing	Additional internal storage	(Yes / No)	(Yes / No)	(Yes / No)	Yes (Yes / No)
capability adjustments applied during testing	Discrete television tuner	(Yes / No)	(Yes / No)	(Yes / No)	No (Yes / No)
ability a lied du	Discrete Audio Card	(Yes / No)	(Yes / No)	(Yes / No)	No (Yes / No)
cap; app	Discrete graphics Card(s) [number / #]	#: (Yes / No)	#: (Yes / No)	#: (Yes / No)	No #: (Yes / No)
	Category of discrete graphics Card(s)				NA
sults	Etec Value (kWh) - dGfx disabled all discrete graphics cards (dGfx) are disabled/ UMA is active for switchable graphics/ product has no graphics cards (dGfx)				23.14
Test results	Etec Value (kWh) - dGfx enabled all discrete graphics cards (dGfx) are enabled				NA
g)	Idle state power demand (Watts);				6.07
h)	Sleep mode power demand (Watts);				6.072
i)	Sleep mode with WOL enabled power d	emand (Watts) (where	enabled);		0.686
i)	Off mode power demand (Watts);				0.313
k)	Off mode with WOL enabled power dem	and (Watts) (where er	nabled);		0.325
l)	Internal power supply efficiency at 10 %	, 20 %, 50 % and 100	% of rated output pow		
	10% 20% 50%	100% Aver	age		
m)	External power supply efficiency (if appl	icable)*:			
	Average active efficiency: 90W Level V	(1 (88.5%)			
	*internal note: show values for all available external p				
o)	Minimum number of loading cycles that	the batteries can withs	tand (applies only to n	otebook computers):	N/A
p-1)	Measurement methodology used to dete	ermine information me	ntioned in points (I) – i	nternal PSU efficiency:	:
(p-2)	Measurement methodology used to dete				cy:

	Measurement methodology	v used to determine information ment N/A	ioned in points (o) – loading cycles batteries:	
(p-4)			ioned in maximum, idle, sleep, off mode n:	
			rs-Measurement of energy consumption	
(q)		eving a stable condition with respect		
(r)		on user manual/Power on->Wait 5 nd/or off mode was selected or progr		
		Based on user manual-Set power	button behaviors	
	Set power butto	n behaviors		
		power button does according to yo urn off the computer or put the com	ur preference. For example, by pressing the puter to sleep or hibernation mode.	
	To change what the pow	ver button does:		
	1. Go to Control Pane	and view by large icons or small ic	ons.	
	2. Click Power Option	ns → Choose what the power butt	ons do.	
	3. Change the settings	s as you prefer.		
(s)	Sequence of events require off mode:	ed to reach the mode where the equi	pment automatically changes to sleep and/or	
	Based on user manual/	Control Panel->Power Options-> C for this plan	hange Settings-> Restore default settings	
(t)		dition before the computer autom	atically reaches sleep mode, or another	25 minutes
(u)	Length of time after a per	riod of user inactivity in which the	requirements for sleep mode (in minutes): computer automatically reaches a power	
(v)		ower demand requirement than sleep display sleep mode is set to activ		10 minutes
(w)		saving potential of power manageme		
		N/A		
	Set the power pla	n		
	been idle for a specified d Table 1. Default power plan	pliant computers, the following power luration: (when plugged into ac power)	plan takes effect when your computers have	
	been idle for a specified d	pliant computers, the following power luration: <i>(when plugged into ac power)</i> r 10 minutes	plan takes effect when your computers have	
	<ul> <li>been idle for a specified d</li> <li>Table 1. Default power plan</li> <li>Turn off the display: Afte</li> <li>Put the computer to sleet</li> </ul>	pliant computers, the following power luration: <i>(when plugged into ac power)</i> r 10 minutes		
	been idle for a specified of <i>Table 1. Default power plan</i> • Turn off the display: Afte • Put the computer to slee To awaken the computer To reset the power plan to 1. Go to <b>Control Panel</b>	pliant computers, the following power luration: <i>(when plugged into ac power)</i> or 10 minutes p: After 25 minutes	ur keyboard. rformance and power saving:	
(z)	been idle for a specified of Table 1. Default power plan • Turn off the display: After • Put the computer to slee To awaken the computer To reset the power plan to 1. Go to Control Panel 2. Click Power Options Test parameters for measu	pliant computers, the following power luration: (when plugged into ac power) or 10 minutes pp: After 25 minutes from Sleep mode, press any key on yo o achieve the best balance between pe and view by large icons or small icons s, and then choose or customize a pow urements: — test voltage in V and fre	ur keyboard. rformance and power saving:	
(z)	been idle for a specified of Table 1. Default power plan • Turn off the display: Afte • Put the computer to slee To awaken the computer To reset the power plan to 1. Go to Control Panel 2. Click Power Options Test parameters for measure the electricity supply system used for electrical testing:	pliant computers, the following power luration: (when plugged into ac power) r 10 minutes p: After 25 minutes from Sleep mode, press any key on yo o achieve the best balance between pe and view by large icons or small icons a, and then choose or customize a pow rements: — test voltage in V and fre m, — information and documentation <b>Test voltage in V and frequency</b>	ur keyboard. promance and power saving: there plan of your preference. quency in Hz, — total harmonic distortion of on the instrumentation, set-up and circuits in Hz: 230V/50Hz	
(z)	been idle for a specified of Table 1. Default power plan • Turn off the display: Afte • Put the computer to slee To awaken the computer To reset the power plan to 1. Go to Control Panel 2. Click Power Options Test parameters for measure the electricity supply system used for electrical testing:	pliant computers, the following power luration: (when plugged into ac power) or 10 minutes (p: After 25 minutes from Sleep mode, press any key on yo o achieve the best balance between pe and view by large icons or small icons (s, and then choose or customize a pow irements: — test voltage in V and fre m, — information and documentation	ur keyboard. prformance and power saving:  rer plan of your preference. quency in Hz, — total harmonic distortion of on the instrumentation, set-up and circuits in Hz: 230V/50Hz ifty supply system: ≤2%	
(z)	been idle for a specified of Table 1. Default power plan • Turn off the display: After • Put the computer to slee To awaken the computer To reset the power plan to 1. Go to Control Panel 2. Click Power Options Test parameters for measur the electricity supply system used for electrical testing: Total	pliant computers, the following power luration: (when plugged into ac power) ir 10 minutes pp: After 25 minutes from Sleep mode, press any key on yo o achieve the best balance between pe and view by large icons or small icons a, and then choose or customize a pow irements: — test voltage in V and fre m, — information and documentation Test voltage in V and frequency harmonic distortion of the electric	ur keyboard. promance and power saving: there plan of your preference. quency in Hz, — total harmonic distortion of on the instrumentation, set-up and circuits in Hz: 230V/50Hz	
(z)	been idle for a specified of Table 1. Default power plan • Turn off the display: After • Put the computer to slee To awaken the computer To reset the power plan to 1. Go to Control Panel 2. Click Power Options Test parameters for measure the electricity supply system used for electrical testing: Total Instrument	pliant computers, the following power luration: (when plugged into ac power) or 10 minutes (p: After 25 minutes from Sleep mode, press any key on you to achieve the best balance between per and view by large icons or small icons (a, and then choose or customize a power) (rements: — test voltage in V and free (m, — information and documentation) (Test voltage in V and frequency) (harmonic distortion of the electric) (Range Used)	ur keyboard. prformance and power saving:  rer plan of your preference. quency in Hz, — total harmonic distortion of on the instrumentation, set-up and circuits in Hz: 230V/50Hz ifty supply system: ≤2%	
(z)	been idle for a specified of Table 1. Default power plan • Turn off the display: After • Put the computer to slee To awaken the computer To reset the power plan to 1. Go to Control Panel 2. Click Power Options Test parameters for measure the electricity supply system used for electrical testing: Total Instrument Type	pliant computers, the following power luration: (when plugged into ac power) r 10 minutes p: After 25 minutes from Sleep mode, press any key on yo o achieve the best balance between pe and view by large icons or small icons s, and then choose or customize a pow urements: — test voltage in V and fre m, — information and documentation Test voltage in V and frequency harmonic distortion of the electrico Range Used Or ***	ur keyboard. rformance and power saving: ter plan of your preference. quency in Hz, — total harmonic distortion of on the instrumentation, set-up and circuits in Hz: 230V/50Hz ity supply system: ≤2% Make and Model **	
(z)	been idle for a specified of Table 1. Default power plan • Turn off the display: After • Put the computer to slee To awaken the computer To reset the power plan to 1. Go to Control Panel 2. Click Power Options Test parameters for measure the electricity supply system used for electrical testing: Total Instrument Type AC Power Source	pliant computers, the following power luration: (when plugged into ac power) r 10 minutes p: After 25 minutes from Sleep mode, press any key on yo o achieve the best balance between pe and view by large icons or small icons s, and then choose or customize a pow arements: — test voltage in V and fre m, — information and documentation Test voltage in V and frequency harmonic distortion of the electric Range Used Or *** 230V;50Hz	ur keyboard. rformance and power saving: ter plan of your preference. quency in Hz, — total harmonic distortion of on the instrumentation, set-up and circuits in Hz: 230V/50Hz ity supply system: ≤2% Make and Model ** EXTECH;6810;SN:1450172	
(z)	been idle for a specified of Table 1. Default power plan • Turn off the display: After • Put the computer to slee To awaken the computer To reset the power plan to 1. Go to Control Panel 2. Click Power Options Test parameters for measure the electricity supply system used for electrical testing: Total Instrument Type AC Power Source Power Meter	pliant computers, the following power luration: (when plugged into ac power) or 10 minutes pp: After 25 minutes from Sleep mode, press any key on yo o achieve the best balance between per and view by large icons or small icons a, and then choose or customize a power arements: — test voltage in V and free m, — information and documentation Test voltage in V and frequency harmonic distortion of the electric Range Used Or *** 230V;50Hz 0~200V;0~20A	ur keyboard. rformance and power saving:  rer plan of your preference. quency in Hz, — total harmonic distortion of on the instrumentation, set-up and circuits in Hz: 230V/50Hz ity supply system: ≤2% Make and Model ** EXTECH;6810;SN:1450172 YOKOGAWA;WT210;SN:91H427511	

	Battery[ies] not user replaceable	Battery[ies] user replaceable	n/a
	The battery[ies] in this product cannot be easily replaced by users themselves. <sup>1)</sup>		
Internal/built-in Battery			$\boxtimes$
External/detachable Battery			
Bios Backup Battery	$\boxtimes$		
Other:			
Additional information			

1) The battery[ies] in this product cannot be easily replaced by users themselves.

Акумулаторната[ите] батерия[и] в този продукт не може да се замени[ят] лесно от самите потребители.

Las baterías de este producto no pueden ser sustituidas fácilmente por los propios usuarios. Výměnu baterie/baterií v tomto výrobku by neměli provádět sami uživatelé. Brugeren kan ikke uden videre udskifte batteriet/batterierne i dette produkt.

Der Akku/die Akkus dieses Produkts kann/können nicht ohne weiteres vom Benutzer selbst ausgetauscht werden. Kasutajad ei saa selle toote akut/akusid ise hõlpsasti asendada.

Η μπαταρία[-ες] στο προϊόν αυτό δεν μπορούν να αντικατασταθούν εύκολα από τους ίδιους τους χρήστες

La/les batterie(s présente(s) dans ce produit ne peuvent être facilement remplacée(s) par les utilisateurs eux-mêmes. Korisnik ne može lako zamijeniti Bateriju sam u ovom proizvodu.

La batteria/le batterie in questo prodotto non può/possono essere facilmente sostituita/e dall'utente. Lietotăji paši nevar nomainît šă ražojuma akumulatoru(-us). Šio gaminio baterijos [bateriju] pats vartotojas negali lengvai pakeisti. A termék akkumulátorát/akkumulátorait a felhasználó nem tudja egyedül egyszerűen kicserélni.

Il-batterija/batteriji f'dan il-prodott ma tistax/jistgħux tiġi/jiġu sostitiwita/i mill-utenti stess. Batteriet [ene] i dette produktet kan ikke lett erstattes av brukerne selv.

De batterij(en) in dit product is (zijn) door de gebruiker niet gemakkelijk vervangbaar.

Użytkownik nie może sam w łatwy sposób wymienić baterii w tym produkcie. A ou as baterias deste produto não podem ser facilmente substituídas pelos próprios utilizadores.

Bateria (bateriile) din acest produs nu poate (pot) fi ușor înlocuită (înlocuite) de utilizatorii înșiși.

Batériu(-ie) v tomto výrobku nemôže výmieňať používateľ. Baterij/baterije v tem izdelku uporabniki sami ne morejo zlahka zamenjati.

Tämän tuotteen akku [akut] ei[vät] ole helposti käyttäjän vaihdettavissa.

Det är inte enkelt för kunden att själv byta ut batteriet/batterierna. Bu üründeki batarya(lar) kullanıcılar tarafından kolaylıkla değiştirilemez.