

ECMA/TC38-TG3/2015/026 (Rev. 1 – 15 April 2015)

Annex B2 - Product environmental attributes Notebooks and Tablets

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

| Brand * | Lenovo | Logo | | |
|------------------------|---|---------|--|--|
| Company name * | Lenovo | | | |
| Contact information * | Lenovo Global Environmental Affairs | Lenovo | | |
| e-mail address | Alvin L Carter | Lehovo. | | |
| | alcarter@lenovo.com | | | |
| Internet site * | http://www.lenovo.com/social_responsibility/us/en/environment | .html | | |
| Additional information | The latest version of this document can be found at: | | | |
| | http://www.lenovo.com/ecodeclaration | | | |

| The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration. | | | | |
|--|--|--|--|--|
| Type of product * | Notebook | | | |
| Commercial name * | Lenovo IdeaPad S145-14/Lenovo V14 | | | |
| Model number * | 81MU, 81MV, 81MX, 81MW, 81N3, 81ST, 81UV, 81VB, 81VC, 81W6, 81W7, 81YA, 82C4 | | | |
| Issue date * | 2019-10-31 | | | |
| Intended market * | 🔀 Global 📃 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other | | | |
| Additional information | | | | |

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template: P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products.

| Model n | umber * | 81W6, 81W7, 82C4 | | Logo | | | |
|----------|---|--|---|------------------------------|-------------|-----|------|
| Issue da | ate * | 2019-10-31 | | | Lend | OVC | |
| | t environ | nental attributes - Legal requiremen | ts | | Require | | |
| Item | | | | | Yes | No | n.a. |
| P1 | | us substances and preparations | | | | | |
| P1.1* | | do comply with current European RoHS Di | | E B1) | \square | | |
| P1.2* | Comme | do not contain Asbestos (see legal referen t: Legal reference has no maximum concer | tration value. | | \square | | |
| P1.3* | hydrobro trichloro | do not contain Ozone Depleting Substance mofluorocarbons (HBFC), hydrochlorofluoro thane, methyl bromide (see legal reference ation values. | carbons (HCFC), Halons, carbontetrach | nloride, 1,1,1- naximum | | | |
| P1.4* | | do not contain more than; 0,005% polychlo (PCT) in preparations (see legal reference | | nlorinated | \square | | |
| P1.5* | | do not contain more than 0,1% short chain taining at least 48% per mass of chlorine in | | bon atoms in | the 🔀 | | |
| P1.6* | Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm ² /week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:2011-5. | | | | | | |
| P1.7* | REACH | Article 33 information about substances in a ww.lenovo.com/us/en/Lenovo-REACH-SVH | rticles is available at (add URL or mail | contact): | | | |
| P2 | Batterie | ; | | | | | |
| P2.1* | symbol. | duct contains a battery or an accumulator, t nformation on proper disposal is provided i | n user manual. (See legal reference) | - | \square | | |
| P2.2* | Batterie: referenc | or accumulators do not contain more than | 0,0005% of mercury or 0,002% of cadr | nium. (See leç | jal 🔀 | | |
| P2.3* | Batterie | and accumulators are readily removable. (| See legal reference) | | \boxtimes | | |
| P3 | | ity verification & Eco design (ErP) | | | | | |
| P3.1* | The pro The Dec | uct is CE-marked to show conformance wit aration of Conformity can be requested at: | h applicable legal requirements (see le https://www.lenovo.com/us/en/complia | gal reference) nce/eu-doc | | | |
| P3.2* | The pro (see leg | uct complies with the Eco design requireme I reference). | ents for energy-related products, | | \boxtimes | | |
| | Require | information is; given in item P15 | or added to this document, | | \boxtimes | | |
| | | available at: <i>https</i> | ://www.lenovo.com/us/en/compliance/e | co-declaratio | n | | |
| P5 | Product | packaging | | | | | |
| P5.1* | Packagi | g and packaging components do not co nt chromium by weight of these together. | ntain more than 0,01% lead, mercur | y, cadmium a | and 🔀 | | |
| P5.2* | The pac | aging materials are marked with abbreviation egal reference). | ons and numbers indicating the nature | of the materia | l(s) 🔀 | | |
| P5.3* | (see leg | uct packaging material is free from ozone de l reference). | | Montreal Proto | ocol 🔀 | | |
| P6 | | t: Legal reference has no maximum concer it information | | | | | |
| P6.1* | | on for recyclers/treatment facilities is availab | | | | | |
| 10.1 | mormat | | | | \square | | |

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

| Model nu | ımber * | 81W6, 81W7, 82C4 | Logo | Lon | | |
|------------|-------------------------------|--|------------------|-------------|-------------|--|
| Issue dat | te * | 2019-10-31 | | Len | ovc | Den |
| Product | | mental attributes - Market requirements (See General NOTE GN | | Doguiro | mont | mat |
| lt a rea | - Envire | onmental conscious design | | Require | | |
| Item P7 | | tory to fill in. Additional information regarding each item may be found under P14. Disassembly, recycling | | Yes | No | n.a. |
| P7.1* | | at have to be treated separately are easily separable | | | | |
| | | | | | | <u> </u> |
| P7.2* | | naterials in covers/housing have no surface coating. | | | | <u> </u> |
| P7.3* | | arts > 100 g consist of one material or of easily separable materials. | | \square | | |
| P7.4* | • | arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. | | \square | | |
| P7.5 | Plastic p | arts are free from metal inlays or have inlays that can be removed with commonly a | available tools. | \square | | |
| P7.6* | Labels a | re easily separable. (This requirement does not apply to safety/regulatory labels). | | | | |
| | Product | lifetime | | | | |
| P7.7* | Upgradir | ng can be done e.g. with processor, memory, cards or drives | | \square | | |
| P7.8* | Upgradir | ng can be done using commonly available tools | | | Ħ | — ——————————————————————————————————— |
| P7.9 | | arts are available after end of production for: 5 years | | | | -#- |
| P7.10 | | | | | | |
| F7.10 | | | | | | |
| P7.11* | | and substance requirements cover/housing material type (e.g. plastics, metal, aluminum): | | | | |
| F7.11 | | type: PC+ABS Material type (e.g. plastics, metal, administration). | | | | |
| P7.12 | | n materials of external electrical cables are PVC free. | | | \boxtimes | |
| P7.13 | | n materials of internal electrical cables are PVC free. | | | | ╞ |
| | | | | | <u> </u> | <u> </u> |
| P7.14 | weight (' polyvinyl | plastic casing/cover parts > 25 g contain no more than $0,1\%$ weight (1000 ppm) b 1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame chloride or $0,3\%$ weight (3000 ppm) bromine and $0,3\%$ weight (3000 ppm) chlorine in an 25% post-consumer recycled content. | e retardants, an | d 🔼 | | |
| P7.15 | Printed c | circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g ed in IEC 61249-2-21. (See 1NOTE B2) | are low haloge | n 🗌 | \boxtimes | |
| P7.16 | Flame re Marking: | etarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: FR(40) | | \boxtimes | | |
| P7.17 | | nemical specifications of flame retardants in printed circuit boards > 25 g (without c | | _ | | |
| | TBBF 26265-0 | PA (additive), TBBPA (reactive) (See NOTE B3), Other: <i>Brominated Epoxy</i> 8-7 | Resins, CAS #: | \square | | |
| | | nemical specifications of flame retardants in printed circuit boards (without compone g ISO 1043-4: | ents) > 25 g | | | |
| P7.18 | concentr Common 1. Chem | etarded plastic parts >25g contain the following flame retardant substances rations above 0.1%: ent: No legal limits exist, this is a market requirement. ical name: <i>BPADP</i> , CAS #: <i>181028-79-5</i> | s/preparations i | n 🔀 | | |
| | Alt. 2 Chomica | al specifications of flame retardants in plastic parts >25g according ISO 1043-4: | | | | |
| P7.19 | | parts > 25 g, flame retardant substances/preparations above 0,1% are used which | have been | | ╞ | |
| F7.19 | assigned | the following Risk phrases; and Hazard statements: rce(s) for these classifications is/are found at (add URL(s)): <i>European Coun</i> | | | | |
| P7.20* | Postcons | sumer recycled plastic material content is used in the product (See Note B6): | | | \boxtimes | |
| | a) Of t a pe or | at least one of the two alternatives below shall be answered; total plastic parts' weight > 25 g, the postconsumer recycled plastic material conten ercentage of total plastic by weight) is <i>0</i> %. weight of recycled material is g. | t (calculated as | | | |

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

| Model number * | 81W6, 81W7, 82C4 | Logo | |
|------------------|---|------|-----------------|
| Issue date * | 2019-10-31 | | Lenovo |
| Product environm | nental attributes - Market requirements (continued) | | Requirement met |

Item

Yes No n.a.

| P7.21* Biobased plastic material content is used in the product (See NOTE B7): Image: Second Se | | Material and su | bstance requirements | s (continued) | | |
|---|-------------------|---------------------------------|-------------------------|----------------------------------|---------------------------------------|---|
| P7.22* Light sources are free from mercury, i.e. less than 0,1 mg/lamp. If mercury is used specify: Number of lamps: and maximum mercury content per lamp: mg Image: mg P8 Battery chemical composition: LH/ON Polymer battery and lithium-metal battery P9.1 For the product the following power levels or energy consumptions are reported: Energy consumption (See NOTE 88) P9.1 For the product the following power levels or energy consumptions are reported: Energy mode* Power level at 115V AC Power level at 230 V AC Peak (On-max) 65 W 65 W Short Idle State - WOL 5.18 W 5.21 W Short Idle State - WOL 5.18 W 5.21 W Steep (S3) - WOL Enabled 0.65 W 0.66 W Sleep (S3) - WOL Disabled 0.65 W 0.66 W Off (S5) - WOL Enabled 0.47 W 0.47 W Off (S5) - WOL Disabled 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration(Pow) Off (S5) - WOL Disabled 0.47 W 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration(Pow) Off (S5) - WOL Disabled 0.47 W 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration(Pow) Off (S5) - WOL Disabled 0.47 W 0.48 W | P7.21* | | | | NOTE B7): | |
| Image: Control of the second secon | | | | | | |
| P8 Batteries P8.1* Battery chemical composition: LI-ION Polymer battery and lithium-metal battery P9 Energy consumption (See NOTE B8) P9.1 For the product the following power levels or energy consumptions are reported: Energy mode * Power level at 100 V AC Peak (On-max) 65 W 65 W 65 W Category 1 | P7.22* | | | | | |
| P8.1* Battery chemical composition: Li-ION Polymer battery and lithium-metal battery P9 Energy consumption (See NOTE B8) P9.1 For the product the following power levels or energy consumptions are reported: Energy mode * Power level at 100 V AC Power level at 115 V AC Power level at 230 V AC Reference/Standard for energy modes and test method * Peak (On-max) 65 W 65 W 65 W Full load Reference/Standard for energy modes and test method * Category 1 5.18 W 5.21 W 5.4 W Use for ENERGY STAR V7.1 registration (Pnim) Long Idle State - WOL Enabled 0.65 W 0.66 W 0.66 W Use for ENERGY STAR V7.1 registration (Pnim) Sleep (S3) - WOL Enabled 0.65 W 0.66 W 0.66 W Use for ENERGY STAR V7.1 registration (Pnim) Sleep (S3) - WOL Disabled 0.65 W 0.66 W 0.66 W Use for ENERGY STAR V7.1 registration(Pnim) Off (S5) - WOL Disabled 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration(Pnim) Off (S5) - WOL Disabled 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration(Pnim) EFS No-load 0.107 W 0.108 W 0.108 W Use for ENERGY STAR V7.1 registration(Pnim) | | | d specify: Number of la | amps: and maxin | num mercury content p | per lamp: mg |
| P9 Energy consumption (See NOTE B8) P9.1 For the product the following power levels or energy consumptions are reported: Energy mode* Power level at 100 V AC Power level at 115 V AC Reference/Standard for energy modes and test method* Peak (On-max) 65 W 65 W 65 W Full load Category 1 Start Idle State - WOL Enabled 5.18 W 5.21 W 5.4 W Use for ENERGY STAR V7.1 registration (Pam) Long idle State - WOL Enabled 3.22 W 3.16 W 3.45 W Use for ENERGY STAR V7.1 registration (Pam) Sleep (S3) - WOL Enabled 0.65 W 0.66 W 0.66 W Use for ENERGY STAR V7.1 registration(Pam) Sleep (S3) - WOL Enabled 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration(Pam) Off (S5) - WOL Enabled 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration(Pam) Off (S5) - WOL Disabled 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration(Pam) Off (S5) - WOL Disabled 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration(Pam) Off (S5) - WOL Disabled 0.47 W 0.48 W Use for Energe (3660/1000) x (Pam x 0.25 Pam) (abade dataded bode docode ton the pom) (abade bode docode docode ton the pom) (aba x 0.30) <tr< td=""><td></td><td></td><td></td><td></td><td></td><td></td></tr<> | | | | | | |
| P9.1 For the product the following power levels or energy consumptions are reported: Energy mode * Power level at 100 V AC Power level at 115 V AC Power level at 230 V AC Reference/Standard for energy modes and test method * Peak (On-max) 65 W 65 W 65 W Full load Category 1 Short Idle State - WOL 5.18 W 5.21 W 5.4 W Use for ENERGY STAR V7.1 registration (Powe) Long Idle State - WOL 3.22 W 3.16 W 3.45 W Use for ENERGY STAR V7.1 registration (Powe) Sleep (S3) - WOL Enabled 0.65 W 0.66 W 0.66 W Use for ENERGY STAR V7.1 registration(Powe) Sleep (S3) - WOL Disabled 0.65 W 0.66 W 0.66 W Use for ENERGY STAR V7.1 registration(Powe) Off (S5) - WOL Disabled 0.47 W 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration(Powe) Off (S5) - WOL Disabled 0.47 W 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration(Powe) Off (S5) - WOL Disabled 0.47 W 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration(Powe) PTEC * Typical Energy Consumption 19.46 kWh/year 19.50 kWh/year 20.28 kWh/year Erec = (8760/1000) x (Pow x 0.25 + Powe), Max 0.30) | - | - | | | thium-metal battery | |
| Energy mode* Power level at 100 V AC Power level at 115 V AC Power level at 230 V AC Reference/Standard for energy modes and test method * Peak (On-max) 65 W 65 W 65 W Full load Category 1 | | | | | · · · · · · · · · · · · · · · · · · · | |
| 100 V AC 115 V AC 230 V AC modes and test method * Peak (On-max) 65 W 65 W 65 W Full load Category 1 Image: State (On-max) 5.8 W 5.21 W 5.4 W Use for ENERGY STAR V7.1 registration (Pudu) Short Idle State - WOL 5.18 W 5.21 W 5.4 W Use for ENERGY STAR V7.1 registration (Pudu) Long Idle State - WOL 3.22 W 3.16 W 3.45 W Use for ENERGY STAR V7.1 registration (Pudu) Sleep (S3) - WOL Enabled 0.65 W 0.66 W 0.66 W Use for ENERGY STAR V7.1 registration (Pudu) Sleep (S3) - WOL Disabled 0.65 W 0.66 W 0.66 W Use for ENERGY STAR V7.1 registration (Pudu) Off (S5) - WOL Disabled 0.47 W 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration (Pudu) Off (S5) - WOL Disabled 0.47 W 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration (Pudu) Off (S5) - WOL Disabled 0.47 W 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration (Pudu) Off (S5) - WOL Disabled 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration (Pudu) Off (S5) - WOL Disabled 0.47 W 0.48 W Use for ENERGY | | | | els or energy consumpt | ions are reported: | Deference/Standard for anormy |
| Category 1 Short Idle State - WOL 5.18 W 5.21 W 5.4 W Use for ENERGY STAR V7.1 registration (Puils) Long Idle State - WOL Enabled 3.22 W 3.16 W 3.45 W Use for ENERGY STAR V7.1 registration (Puils) Sleep (S3) - WOL Enabled 0.65 W 0.66 W 0.66 W Use for ENERGY STAR V7.1 registration (Puils) Sleep (S3) - WOL Disabled 0.65 W 0.66 W 0.66 W Use for ENERGY STAR V7.1 registration(Puils) Sleep (S3) - WOL Disabled 0.65 W 0.66 W 0.66 W Use for ENERGY STAR V7.1 registration(Puils) Off (S5) - WOL Disabled 0.47 W 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration(Poil) Off (S5) - WOL Disabled 0.47 W 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration(Poil) Off (S5) - WOL Disabled 0.107 W 0.108 W 0.108 W Use for ErP PS No-load (Eternal power supply charge plaged in the meterite bod decorrected in the poduct) 19.46 kWh/year 19.50 kWh/year 20.28 kWh/year Erec = (8760/1000) x (Poir x 0.25 + Paloey x 0.35 + Poing_stie x 0.10+ Palor Late x 0.30) Palor Late x 0.30) Palor Late x 0.30) Palor Late x 0.30) Palor X 0.10 + Palor Late x 0.30) Palor X 0.10 + Palor Late x 0.30) Palor Late x 0.30) <td< td=""><td></td><td></td><td>100 V AC</td><td>115 V AC</td><td>230 V AC</td><td>modes and test method *</td></td<> | | | 100 V AC | 115 V AC | 230 V AC | modes and test method * |
| Short Ide State - WOL Enabled 5.18 W 5.21 W 5.4 W Use for ENERGY STAR V7.1 registration (Pusin) Long Idle State - WOL Enabled 3.22 W 3.16 W 3.45 W Use for ENERGY STAR V7.1 registration (Pusin) Sleep (S3) - WOL Enabled 0.65 W 0.66 W 0.66 W Use for ENERGY STAR V7.1 registration (Pusin) Sleep (S3) - WOL Disabled 0.65 W 0.66 W 0.66 W Use for ENERGY STAR V7.1 registration (Pusin) Off (S5) - WOL Enabled 0.65 W 0.66 W 0.66 W Use for ENERGY STAR V7.1 registration (Pusin) Off (S5) - WOL Enabled 0.47 W 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration (Pusin) Off (S5) - WOL Disabled 0.47 W 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration (Pusin) Off (S5) - WOL Disabled 0.107 W 0.108 W 0.108 W 0.108 W (Estemap puser supply chaine puser supply chaine the poduct) W W W PTEC * W W W Erec = (8760/1000) x (Pur x 0.25 + Pusing x 0.01 + Pusin (168 State - WOL Enabled) Patter off Mode(S5) - WOL Enabled; Pusing: Steep Mode(S3) - WOL Enabled; Pusing X 0.01 + Pusing X 0.01 + Pusin (168 State - WOL Enabled) Pusing X 0.01 + Pusin (168 State - WOL Enabled) <tr< td=""><td>Peak (On-I</td><td>max)</td><td>65 W</td><td>65 W</td><td>65 W</td><td>Full load</td></tr<> | Peak (On-I | max) | 65 W | 65 W | 65 W | Full load |
| Enabled registration (Puttle) Long Idle State - WOL Enabled 3.22 W 3.16 W 3.45 W Use for ENERGY STAR V7.1 registration (Puttle) Sleep (S3) - WOL Enabled 0.65 W 0.66 W 0.66 W Use for ENERGY STAR V7.1 registration (Puttle) Sleep (S3) - WOL Disabled 0.65 W 0.66 W 0.66 W Use for ENERGY STAR V7.1 registration(Puttle) Off (S5) - WOL Enabled 0.47 W 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration(Puttle) Off (S5) - WOL Disabled 0.47 W 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration(Puttle) Off (S5) - WOL Disabled 0.47 W 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration(Puttle) Off (S5) - WOL Disabled 0.47 W 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration(Puttle) Off (S5) - WOL Disabled 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration(Puttle) PTEC * N 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration(Puttle) PTEC * Information Budde(S) - WOL Enabled; Puttle) 20.28 kWh/year Erec = (8760/1000) x (Putr x 0.25 + Putre), dite x 0.30 + Putr x 0.35 + Piong, dite x 0.10+ Putre), dite x 0.30 + Putre), dite X | <u>Categor</u> | <u>y 1</u> | | | | |
| Enabled registration (P _{idid}) Sleep (S3) - WOL Enabled 0.65 W 0.66 W 0.66 W Use for ENERGY STAR V7.1 registration(P _{steep}) Sleep (S3) - WOL Disabled 0.65 W 0.66 W 0.66 W Reference Off (S5) - WOL Enabled 0.47 W 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration(P _{off}) Off (S5) - WOL Disabled 0.47 W 0.47 W 0.48 W Use for EnERGY STAR V7.1 registration(P _{off}) Off (S5) - WOL Disabled 0.47 W 0.47 W 0.48 W Use for EnF EPS No-load 0.107 W 0.108 W 0.108 W Use for EnF PTEC * W W W W V Typical Energy Consumption 19.46 kWh/year 19.50 kWh/year 20.28 kWh/year Errcc = (8760/1000) x (P _{off} x 0.25 + P _{biog} x 0.35 + P _{long} , ide x 0.10 + P _{biox} z ide x 0.30) P _{off} : Off Mode(S5) - WOL Enabled; P _{steep} : Steep Mode(S3) - WOL Enabled; P _{biox} z ide x 0.30) Poff External Power Supply Efficiency Level (International Efficiency Marking Protocol)* : VI Display resolution* : 8.294 megapixels V V Default time to enter energy save function is provided with the product. Y P P P9.2* Information about the energy save | | State - WOL | 5.18 W | 5.21 W | 5.4 W | |
| Image: Sign of the second second provided pr | | State - WOL | 3.22 W | 3.16 W | 3.45 W | |
| Off (S5) - WOL Enabled 0.47 W 0.47 W 0.48 W Use for ENERGY STAR V7.1 registration(Port) Off (S5) - WOL Disabled 0.47 W 0.47 W 0.48 W Use for ErP EPS No-load 0.107 W 0.108 W 0.108 W Use for ErP PTEC * W W W W Typical Energy Consumption 19.46 kWh/year 19.50 kWh/year 20.28 kWh/year ErEc = (8760/1000) × (Port × 0.25 + Postop × 0.35 + Plong_ute × 0.10+ Postor_Ute × 0.30) Port: Off Mode(S5) - WOL Enabled; Psteep: Steep Mode(S3) - WOL Enabled; Psteep: Steep Mode(S3) - WOL Enabled; Psteep: Steep Mode(S3) - WOL Enabled; Psteep: A 0.30 + Postor_Ute × 0.30) Port: Off Mode(S5) - WOL Enabled; Psteep: Steep Mode(S3) - WOL Enabled; Psteep: Idle State - WOL Enabled External Power Supply Efficiency Level (International Efficiency Marking Protocol)*: VI Display resolution*: 8.294 megapixels Impact Idle State - WOL Enabled Default time to enter energy save mode: 10 minutes P9.2 * Information about the energy save function is provided with the product. Impact Idle State - WOL Enabled Impact Idle State - WOL Enabled P9.2 * Information about the energy save function is provided with the product. Impact Idle State - WOL Enabled Impact Idle State - WOL Enabled Impact Idle State - WOL Enabled P10 Emissions Vise for Statistical upper limit A-weighted | Sleep (S3) | - WOL Enabled | 0.65 W | 0.66 W | 0.66 W | |
| Off (S5) - WOL Disabled 0.47 W 0.47 W 0.48 W Use for ErP EPS No-load 0.107 W 0.108 W 0.108 W 0.108 W (External power supply / charger plugade in the wall outlet but disconnected from the product) W W W PTEC * 19.46 kWh/year 19.50 kWh/year 20.28 kWh/year Erec = (8760/1000) x (Port x 0.25 + Psteep x 0.35 + Plong_Idle x 0.10+ Pstort_idle x 0.30) Port: Off Mode(S5) - WOL Enabled; Psteep: Sleep Mode(S3) - WOL Enabled; Psteep x 0.35 + Plong_Idle x 0.10+ Pstort_idle x 0.30) Port: Off Mode(S5) - WOL Enabled; Psteep: Sleep Mode(S3) - WOL Enabled; Psteep x 0.35 + Plong_Idle x 0.10+ Pstort_idle x 0.30) Port: Off Mode(S5) - WOL Enabled; Psteep: Sleep Mode(S3) - WOL Enabled; Psteep x 0.35 + Plong_Idle x 0.10+ Pstort_idle x 0.30) Port: Off Mode(S5) - WOL Enabled; Psteep: Sleep Mode(S3) - WOL Enabled; Psteep x 0.35 + Plong_Idle x 0.10+ Pstort_idle x 0.30) Port: Off Mode(S5) - WOL Enabled; Psteep: Sleep Mode(S3) - WOL Enabled; Psteep x 0.35 + Plong_Idle x 0.10+ Pstort_idle x 0.30) Port: Off Mode(S5) - WOL Enabled; Psteep x 0.35 + Plong_Idle x 0.10+ Pstort_idle x 0.30) Port: Off Mode(S5) - WOL Enabled; Psteep: Sleep Mode(S3) - WOL Enabled; Psteep x 0.35 + Plong_Idle x 0.30) Psteep x 0.35 + Plong_Idle x 0.30) Port: Off Mode(S5) - WOL Enabled; Psteep: Sleep Mode(S3) - WOL Enabled; Psteep x 0.35 + Plong_Idle x 0.30) Ence x 0.30 Pstee x 0.35 + Psteep x 0.35 + Psteepsteep x 0.35 + Plong_Idle x 0.10+ Psteep x | Sleep (S3) | - WOL Disabled | 0.65 W | 0.66 W | 0.66 W | Reference |
| EPS No-load (Extemal power supply / drarger plugged in the wall outlet but disconnected from the product.) 0.107 W 0.108 W PTEC * Typical Energy Consumption W W W ETEC * Annual Energy Consumption 19.46 kWh/year 19.50 kWh/year 20.28 kWh/year Erec = (8760/1000) x (Pofr x 0.25 + P sleep x 0.35 + Plong_tdle x 0.10+ Pshort_tdle x 0.30) Port: Off Mode(S5) - WOL Enabled; P sleep: Sleep Mode(S3) - WOL Enabled; P lotle: Idle State - WOL Enabled Postor_tdle x 0.30) Port: Off Mode(S5) - WOL Enabled; P sleep: Sleep Mode(S3) - WOL Enabled; P lotle: Idle State - WOL Enabled External Power Supply Efficiency Level (International Efficiency Marking Protocol) * : VI Display resolution * : 8.294 megapixels Default time to enter energy save mode: 10 minutes P P9.2* Information about the energy save function is provided with the product. Image: Comparison of the comparison o | Off (S5) - V | WOL Enabled | 0.47 W | 0.47 W | 0.48 W | |
| (External power supply / charger plugged in the wall outlet but disconnected from the product.) W W PTEC * W W W Typical Energy Consumption 19.46 kWh/year 19.50 kWh/year 20.28 kWh/year ETEC = (8760/1000) x (Port x 0.25 + Psleep x 0.35 + Plong_Idle x 0.10+ Pshort_Idle x 0.30) Port: Off Mode(S5) - WOL Enabled; Psleep: Sleep Mode(S3) - WOL Enabled; Psleep x 0.35 + Plong_Idle x 0.10+ Pshort_Idle x 0.30) Port: Off Mode(S5) - WOL Enabled; Psleep: Sleep Mode(S3) - WOL Enabled; Psleep x 0.35 + Plong_Idle x 0.30) Port: Off Mode(S5) - WOL Enabled; Psleep: Sleep Mode(S3) - WOL Enabled; Pslee x 0.30) Port: Off Mode(S5) - WOL Enabled; Psleep: Sleep Mode(S3) - WOL Enabled; Pslee x 0.30) Display resolution * : 8.294 megapixels Default time to enter energy save mode: 10 minutes P9.2* Information about the energy save function is provided with the product. P9.3 Energy efficiency class (monitors only): P10 Emissions Noise emission – Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode description | Off (S5) - V | NOL Disabled | 0.47 W | 0.47 W | 0.48 W | Use for ErP |
| PTEC * Typical Energy Consumption W W W ETEC * Annual Energy Consumption 19.46 kWh/year 19.50 kWh/year 20.28 kWh/year ETEC = (8760/1000) x (Poff x 0.25 + Poleg_1de x 0.10+ Poleg_1de x 0.30) Poff: Off Mode(S5) - WOL Enabled; Poleg_: Sleep Mode(S3) - WOL Enabled; Poleg_: Sleep Mode(S3) - WOL Enabled; Poleg_: Idle State - WOL Enabled External Power Supply Efficiency Level (International Efficiency Marking Protoci) * : VI Image: Consumption * : 8.294 megapixels Default time to enter energy save function is provided with the product. Image: Consumption * : 0 P9.2* Information about the energy save function is provided with the product. Image: Consumption * : 0 P9.3 Energy efficiency class (monitors only): Image: Consumption * Consurpoverende * Consumption * Consumption * Consumption | EPS No-loa | ad | 0.107 W | 0.108 W | 0.108 W | |
| PTEC * Typical Energy Consumption W W W ETEC * Annual Energy Consumption 19.46 kWh/year 19.50 kWh/year 20.28 kWh/year ETEC = (8760/1000) x (Poff x 0.25 + Poleg_1de x 0.10+ Poleg_1de x 0.30) Poff: Off Mode(S5) - WOL Enabled; Poleg_: Sleep Mode(S3) - WOL Enabled; Poleg_: Sleep Mode(S3) - WOL Enabled; Poleg_: Idle State - WOL Enabled External Power Supply Efficiency Level (International Efficiency Marking Protoci) * : VI Image: Consumption * : 8.294 megapixels Default time to enter energy save function is provided with the product. Image: Consumption * : 0 P9.2* Information about the energy save function is provided with the product. Image: Consumption * : 0 P9.3 Energy efficiency class (monitors only): Image: Consumption * Consurpoverende * Consumption * Consumption * Consumption | (External power s | supply / charger plugged in the | e | | | |
| ETEC * Annual Energy Consumption 19.46 kWh/year 19.50 kWh/year 20.28 kWh/year ETEC = (8760/1000) x (P _{off} x 0.25 + P _{sleep} x 0.35 + P _{long_Idle} x 0.10+ P _{short_Idle} x 0.30) Porr: Off Mode(S5) - WOL Enabled; P _{sleep} : Sleep Mode(S3) - WOL Enabled; P _{ldle} : Idle State - WOL Enabled External Power Supply Efficiency Level (International Efficiency Marking Protocol) * : VI Image: Constraint of the state - WOL Enabled Display resolution * : 8.294 megapixels Image: Constraint of the energy save mode: 10 minutes Image: Constraint of the energy save function is provided with the product. P9.2* Information about the energy save function is provided with the product. Image: Constraint of the energy save function on the energy save function on the energy save function on the energy save function is provided with the product. P9.3 Energy efficiency class (monitors only): Image: Constraint of the energy save function on the energy save function is provided with the product. P9.3 Energy efficiency class (monitors only): Image: Constraint of the energy save function on the energy save functio | | connected from the product.) | | W | W | |
| Annual Energy Consumption + Psieep x 0.35 + Plong_idle x 0.10+ Psinort_idle x 0.30) Port: Off Mode(S5) - WOL Enabled; Psieep: Sleep Mode(S3) - WOL Enabled; Pidle: Idle State - WOL Enabled External Power Supply Efficiency Level (International Efficiency Marking Protocol) * : VI Display resolution * : 8.294 megapixels Default time to enter energy save mode: 10 minutes P9.2* Information about the energy save function is provided with the product. P9.3 Energy efficiency class (monitors only): P10 Emissions Noise emission – Declared according to ISO 9296 (See NOTE B9) P10.1 Mode | | ergy Consumption | | | | |
| External Power Supply Efficiency Level (International Efficiency Marking Protocol)*: VI Display resolution*: 8.294 megapixels | | ergy Consumption | | | | + $P_{sleep} \times 0.35$ + $P_{long_{ldle}} \times 0.10$ + $P_{short_{ldle}} \times 0.30$) |
| Display resolution * : 8.294 megapixels | | | | | | oled; Pidle: Idle State - WOL Enabled |
| Default time to enter energy save mode: 10 minutes Information about the energy save function is provided with the product. Image: Comparison of the product of the produc | | | | al Efficiency Marking Pi | rotocol) * : VI | |
| P9.2* Information about the energy save function is provided with the product. Image: Constraint of the product of the produc | Display res | olution * : 8.294 m | negapixels | | | |
| P9.3 Energy efficiency class (monitors only): P10 Emissions Noise emission – Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode Mode description | Default tim | e to enter energy s | save mode: 10 minutes | 3 | | |
| P9.3 Energy efficiency class (monitors only): P10 Emissions Noise emission – Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode Mode description Statistical upper limit A-weighted sound power level, L _{WA,C} | P9.2* | Information abou | t the energy save func | tion is provided with the | e product. | |
| P10 Emissions Noise emission – Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, L _{WA,c} | | | | | • | |
| Noise emission – Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, L _{WA,c} | | | | | | |
| | | | - Declared according | to ISO 9296 (See NOT | E B9) | |
| | P10.1 | Mode | Mode description | | Statistical upper lin | nit A-weighted sound power level, $L_{WA,c}$ (B) |
| Idle * HDD:Idle * 2.9 | | Idle | * HDD:Idle | | * 2.9 | |
| Operation * HDD: Operating * 4 | | | | | | |
| Other mode Declared A-weighted sound pressure level (dB) L_{pAm} 18.6 (operator position desktop – idle) | | | | | | sition desktop – idle) |
| Other mode Declared A-weighted sound pressure level (dB) L_{pAm} 32.2 (operator position desktop – operating) | | Other mode | Declared A-weighted sou | and pressure level (dB) L_{pA} | m 32.2 (operator pos | sition desktop – operating) |
| Measured according to: X ISO 7779 ECMA-74 Other (only if not covered by ECMA-74) | | Measured accord | · · = | | y ECMA-74) | |

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

| Model nu | umber * | 81W6, 81W7, 82 | 2C4 | | | Logo | | | |
|----------|--|---|---|--|---|--|---|----------------------|------|
| lssue da | te * | 2019-10-31 | | | | | Len | | Тн |
| Product | t environr | nental attribute | es - Market requirements | (continued) | | | | iremen | |
| ltem | | | | | | | Ye | s No | n.a. |
| | | nagnetic emissi | | | | | | | |
| P10.4 | program | (s): MPR-II(3 pin | he requirement for low frequer AC adapter only) | icy electromagneti | c fields of the foll | owing volun | tary 📐 | | |
| P12 | | nics for comput | | | | | | | |
| P12.1* | | , , | onomic requirements of ISO 9 | | | gies. | \geq | | |
| P12.2* | The phy | sical input device | meets the requirements of ISC |) 9995 and ISO 92 | 241-410. | | \geq | | |
| P13 | | ng and docume | | | | | | | |
| P13.1* | Product Product | packaging materi | al type(s): <i>paper(manual)</i> al type(s): <i>corner paper</i> weigh | nt (kg): 0.303 weight (kg): (nt (kg): 0.038 nt (kg): 0.072 | 0.045 | | | | |
| P13.2* | Product | plastic primary pa | ckaging is free from PVC. | | | | \triangleright | $1 \square$ | |
| P13.3* | | For product primary corrugated fiberboard packaging, specify the contained percentage of minimum post- consumer recovered fiber content: 100 % | | | | | | | |
| P13.4* | | media for user an ic ⊠, Paper ⊠, | d product documentation (tick Other | box): | | | | | |
| P13.5 | Úser and | | s item if paper documentation (ntation on paper media is chlo | | | | | | |
| | Element | hlorine-free al chlorine-free ed chlorine-free | | | | | | | |
| P14 | Volunta | ry programs | | | | | | | |
| P14.1 | The proc | luct meets the red | quirements of the following volu | untary program(s): | : | | | | |
| | | Y STAR® H: EPEAT | Criteria version: 7.1 Criteria version: | Date: Date: | | category: 1 category: | | | |
| | Eco-labe | el: | Criteria version: | Date: | Product | category: | | | |
| P15 | Addition | al information (| | | | <u> </u> | | | |
| P9 | | | specific configuration may v | ary; description | of the tested pro | oduct config | guration: | | |
| | NOTE: S informati knowled provided informati | Supplier makes no on contained in the ge available at the here is approxim on. | representations, guarantees, his document. All information p e time of completion, and supp ate and provided for information | assurances or wa rovided by supplie lier shall have no onal purposes only | rranties whether er in this documer obligation to upda /. See a Lenovo / | express or in nt is provided ate such info | nplied, regar based on s rmation. The | upplier's informa | |
| P9 | | | Notebooks & Tablet Compute /index.cfm?fuseaction=find_a_ | | | code=CO | | | |

Annex B1 of ECMA-370 5th edition (Lenovo) 2015-04-08

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B2

| Reference | Declaration item |
|---|------------------------|
| Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications. | P1.1 |
| Regulation (EC) 1907/2006(REACH, Annex XVII | P1.2, P1.4, P1.6, P1.7 |
| Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances) | P1.3, P5.3 |
| Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002 | P1.5 |
| Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator. | P2.1, P2.2, P2,3, P8.1 |
| Directive 2006/95/EC (Low Voltage Directive) | P3.1 |
| Directive 2004/108/EC (EMC Directive) | P3.1 |
| Directive 1999/5/EC (R&TTE Directive) | P3.1 |
| Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions | P3.1, P3.2 |
| Regulation (EC) No 1272/2008 (CLP Regulation) | P7.19 |
| Directive 2004/12/EC (Packaging Directive) | P5.1 |
| Decision 97/129/EC (Secondary packaging legislation) | P5.2 |
| Directive 2012/19/EU (WEEE directive) | P6.1 |

Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

| Commercial name | Lenovo IdeaPad S145-14IIL/Lenovo V14IIL | Logo | | |
|------------------------|---|------|--------|--|
| Model number * | 81W6, 81W7, 82C4 | | | |
| Issue date * | 2019-10-31 | | Lenovo | |
| Additional information | | | | |

| P7.1.1 | Product environmental attributes | | | | | |
|--|--|--|--|--|--|--|
| (d) | Year of manufacture: | | | | 2019 | |
| (e) | Etec value (kWh) per ErP Lot 3 Catego disabled and if the system is tested with | | | | cards (dGfx) are | |
| (f) | Etec value (kWh) per ErP Lot 3 Categor enable | y and capability adjust | ments applied when a | II discrete graphics o | cards (dGfx) are | |
| | | Category A (according to ErP Lot 3) | Category B (according to ErP Lot 3) | Category C (according to ErP Lot 3) | Category D (according to ErP Lot 3) | |
| | Memory over base [GB] | 12 | | | | |
| lents sting | Additional internal storage | Yes (Yes / No) | (Yes / No) | (Yes / No) | (Yes / No) | |
| capability adjustments applied during testing | Discrete television tuner | No (Yes / No) | (Yes / No) | (Yes / No) | (Yes / No) | |
| ability a | Discrete Audio Card | No (Yes / No) | (Yes / No) | (Yes / No) | (Yes / No) | |
| cap app | Discrete graphics Card(s) [number / #] | No #: (Yes / No) | #: (Yes / No) | #: (Yes / No) | # <i>:</i> (Yes / No) | |
| | Category of discrete graphics Card(s) | | | | | |
| Test results | Etec Value (kWh) - dGfx disabled all discrete graphics cards (dGfx) are disabled/ UMA is active for switchable graphics/ product has no graphics cards (dGfx) | 11.43 | | | | |
| Test r | Etec Value (kWh) - dGfx enabled all discrete graphics cards (dGfx) are enabled | | | | | |
| (g) | Idle state power demand (Watts); | · | • | | A: 3.45 | |
| (h) | Sleep mode power demand (Watts); | | | | A : 0.49 | |
| (i) | Sleep mode with WOL enabled power de | emand (Watts) (where | enabled); | | A : 0.49 | |
| (j) | Off mode power demand (Watts); | | | | A : 0.37 | |
| (k) | Off mode with WOL enabled power dem | and (Watts) (where en | abled); | | A : 0.37 | |
| (I) | Internal power supply efficiency at 10 %, | , 20 %, 50 % and 100 9 | % of rated output pow | er (if applicable): | | |
| | 10% 20% 50% | 100% Avera | ige S | | | |
| (m) | External power supply efficiency (if appli | cable)*: | | | | |
| | Average active efficiency: 88.62% | | | | | |
| | *internal note: show values for all available external po | | | - (-) () | | |
| (o) | Minimum number of loading cycles that t | ine batteries can withs | tand (applies only to n | OTEDOOK COMPUTERS): | 300 CYCLES | |
| (p-1) | Measurement methodology used to dete | rmine information mer NA | tioned in points (I) – ii | nternal PSU efficiency: | | |
| (p-2) | D-2) Measurement methodology used to determine information mentioned in points (m) – external PSU efficiency: EN 50563:2011 measurement methodology | | | | | |

| | EN 50563:2011 measurement me | ed in points (o) – loading cycles batteries: | |
|--------------------------------|--|--|-----|
| | Point P9.1 in the Product IT Eco Declaration: EN 62623:2013 measurement me | ed in maximum, idle, sleep, off mode | |
| q) Sequence of steps | or achieving a stable condition with respect to p EN 62623:2013 measurement me | | |
| r) Description of how | sleep and/or off mode was selected or programm EN 62623:2013 measurement me | | |
| s) Sequence of event off mode: | required to reach the mode where the equipme | ent automatically changes to sleep and/or | |
| | er to power management, 30mins automatic | ally reaches sleep mode | |
| condition which doe | ate condition before the computer automatic s not exceed the applicable power demand requ | uirements for sleep mode (in minutes): | 30 |
| mode that has a lo | er a period of user inactivity in which the con wer power demand requirement than sleep mo | de (in minutes): | NA |
| | ore the display sleep mode is set to activate mergy-saving potential of power management fu refer to user manual | | 10 |
| x) User information or | how to enable the power management function refer to user manual | ality: | |
| | measurements: — test voltage in V and frequent v system, — information and documentation on esting: 230V, 50GHz, Total Harmonic Dist | the instrumentation, set-up and circuits | |
| Additional Notebook Batte | ry Information: | | |
| | Battery[ies] not user replaceable | Battery[ies] user replaceable | n/a |
| | The battery[ies] in this product cannot be e replaced by users themselves. ¹⁾ | asily | |
| nternal/built-in Battery | | | |
| External/detachable Battery | | | |
| Bios Backup Battery | | | |
| Other: | | | |
| Additional information | | | |
| | | | |
| | | | |
| | assily replaced by users tnemserves. продукт не може да се замени[ят] лесно от самите потр ser sustituidas fácilmente por los propios usuarios. r neměli provádět sami uživatelé. tteriet/batterierne i dette produkt. | ебители. uscht werden. | |