

ECMA/TC38-TG3/2015/026 (Rev. 1 – 15 April 2015)

Annex B2 - Product environmental attributes Desktop/All-in-One Computers

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

| Brand * | Lenovo | Logo | | | | | |
|------------------------|---|-------|---------|--|--|--|--|
| Company name * | Lenovo | | | | | | |
| Contact information * | Lenovo Global Environmental Affairs | | Lenovo | | | | |
| e-mail address | Alvin L Carter | | LEIIOVO | | | | |
| | alcarter@lenovo.com | | | | | | |
| Internet site * | http://www.lenovo.com/social_responsibility/us/en/environment | .html | | | | | |
| Additional information | The latest version of this document can be found at: | | | | | | |
| | http://www.lenovo.com/ecodeclaration | | | | | | |

| The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration. | | | | | | |
|--|--|--|--|--|--|--|
| Type of product * | Desktop Computer | | | | | |
| Commercial name * | ThinkCentre M720s | | | | | |
| Model number * | 10ST, 10SU, 10SV, 10SV, 10TR, 10U6, 10U7 | | | | | |
| Issue date * | 2020-11-6 | | | | | |
| Intended market * | 🔀 Global 📃 Europe 📃 Asia, Pacific & Japan 📃 Americas 📃 Other | | | | | |
| Additional information | | | | | | |

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template: P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products.

| Model n | umber * | 10ST, 10SU, 10SV, 10SV, 10TR, 10U6, 10U7 | | Logo | | | | |
|----------|---|--|--|-----------------|-------------|----|------|--|
| lssue da | ite * | 2020-11-6 | | Leng | Den | | | |
| Produc | t environ | nental attributes - Legal requirements | | | Require | | met | |
| Item | | | | | Yes | No | n.a. | |
| P1 | Hazardo | us substances and preparations | | | | | | |
| P1.1* | Products | do comply with current European RoHS Directive | . (See legal reference and NOTE | EB1) | \square | | | |
| P1.2* | Comme | do not contain Asbestos (see legal reference). t: Legal reference has no maximum concentration | | | \boxtimes | | | |
| P1.3* | hydrobro trichloro | do not contain Ozone Depleting Substances: Chlor mofluorocarbons (HBFC), hydrochlorofluorcarbons thane, methyl bromide (see legal reference). Con ation values. | s (HCFC), Halons, carbontetrach | | | | | |
| P1.4* | terpheny | do not contain more than; 0,005% polychlorinated (PCT)in preparations (see legal reference). | , | | \square | | | |
| P1.5* | Products do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference). Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 µg/cm ² /week | | | | | | | |
| P1.6* | (see leg | k 🔀 | | | | | | |
| P1.7* | Comment: Max limit in legal reference when tested according to EN1811:2011-5. REACH Article 33 information about substances in articles is available at (add URL or mail contact): http://www.lenovo.com/social_responsibility/us/en/environment.html | | | | | | | |
| P2 | Batterie | ; | | | | | | |
| P2.1* | If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal symbol. Information on proper disposal is provided in user manual. (See legal reference) | | | | | | | |
| P2.2* | Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal reference) | | | | | | | |
| P2.3* | Batteries and accumulators are readily removable. (See legal reference) | | | | | | | |
| P3 | Conform | ity verification & Eco design (ErP) | | | | | | |
| P3.1* | The proc | uct is CE-marked to show conformance with appli aration of Conformity can be requested at: https:// | | | \boxtimes | | | |
| P3.2* | | uct complies with the Eco design requirements for I reference). | energy-related products, | | \boxtimes | | | |
| | | information is; given in item P15 or adde | ed to this document, . <i>lenovo.com/us/en/compliance/e</i> | an declaration | \boxtimes | | | |
| P5 | Droduct | packaging | enovo.com/us/en/compilance/e | | | | | |
| P5.1* | | g and packaging components do not contain r | nore than 0.01% lead moreur | v cadmium o | nd 🔀 | | | |
| 1 J.1 | | nt chromium by weight of these together. | nore man 0,0170 leau, mercur | y, caumum a | | | | |
| P5.2* | The pac | aging materials are marked with abbreviations and elegal reference). | d numbers indicating the nature | of the material | (s) 🔀 | | | |
| P5.3* | The pro Protocol | luct packaging material is free from ozone dep (see legal reference). t: Legal reference has no maximum concentration | | in the Montre | al 🔀 | | | |
| P6 | | | | | | | | |
| | | atment information prmation for recyclers/treatment facilities is available (see legal reference). | | | | | | |

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

| Model number * | | 10ST, 10SU, 10SV, 10SV, 10TR, 10U6, 10U7 | Logo | | | | |
|----------------|--|---|------------------|-------------|-----------|-------------|--|
| Issue dat | te * | 2020-11-6 | | Len | ovo | тм | |
| Product | | mental attributes - Market requirements (See General NOTE GN | below) | | | | |
| | | onmental conscious design | | Require | | net | |
| Item | | tory to fill in. Additional information regarding each item may be found under P14. | | Yes | No | n.a. | |
| P7 | Design Disasse | mbly, recycling | | | | | |
| P7.1* | | t have to be treated separately are easily separable | | | | | |
| P7.2* | Plastic m | aterials in covers/housing have no surface coating. | | | Ē | Ħ | |
| P7.3* | Plastic p | arts > 100 g consist of one material or of easily separable materials. | | | Ē | | |
| P7.4* | Plastic p | arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. | | | Ē | | |
| P7.5 | Plastic p | arts are free from metal inlays or have inlays that can be removed with commonly a | available tools. | . 🛛 | Π | | |
| P7.6* | Labels a | re easily separable. (This requirement does not apply to safety/regulatory labels). | | | | | |
| | Product | | | | | | |
| P7.7* | Upgrading can be done e.g. with processor, memory, cards or drives | | | | | | |
| P7.8* | Upgrading can be done using commonly available tools Spare parts are available after end of production for: 5 years | | | | | | |
| P7.9 | Spare pa | | | | | | |
| P7.10 | Service is available after end of production for: 5 years | | | | | | |
| | | and substance requirements | | | | | |
| P7.11* | Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: ABS+PC Material type: PC Material type: ABS | | | | | | |
| | Material | | | | | | |
| P7.12 | Insulatio | | | | | | |
| P7.13 | Insulatio | | \square | | | | |
| P7.14 | External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. | | | | | | |
| P7.15 | Printed | circuit boards, PCBs (without components) are low halogen: all PCBs > as defined in IEC 61249-2-21. (See 1NOTEB2) | 25 g 📃 are | ow | \square | | |
| P7.16 | Flame re Marking: | tarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: | | \square | | | |
| P7.17 | | nemical specifications of flame retardants in printed circuit boards > 25 g (without c | | | _ | | |
| | TBBF 26265-0 | PA (additive), XTBBPA(reactive)(See NOTEB3), XOther: <i>Brominated Epoxy R</i> 8-7 | esin, CAS #: | | | | |
| | <u>Alt. 2:</u> Chemical specifications of flame retardants in printed circuit boards (without components)> 25 g according ISO 1043-4: <i>FR(16)</i> | | | | | | |
| P7.18 | <u>Alt. 1: </u> Fl | ame retarded plastic parts > 25 g contain the following flame retardant substance | s/preparations | s in | | | |
| | | ations above 0,1%: | | | | \boxtimes | |
| | | ical name: , CAS #: (See NOTE B4) ical name: , CAS #: " | | | | | |
| | | ical name: , CAS #: " | | | | | |
| | Alt. 2: Cł | nemical specifications of flame retardants in plastic parts > 25 g according ISO 104 | 3-4: | | | | |
| P7.19 | Alt. 2. Chemical specifications of name retardants in plastic parts > 25 g according ISO 1043-4. In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been | | | | | | |
| | | I the following Risk phrases; and Hazard statements: | | | | | |
| | The sour | ce(s) for these classifications is/are found at (add URL(s)): | ee note B5) | | | | |
| P7.20* | | sumer recycled plastic material content is used in the product (See Note B6): | - / | \boxtimes | | | |
| | a) Of t per or | t least one of the two alternatives below shall be answered; otal plastic parts' weight > 25 g, the postconsumer recycled plastic material conten centage of total plastic by weight) is 8.9 %. weight of recycled material is 87.3 g. | t (calculated a | s a | | | |

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

| Item Mate P7.21* Biob P7.22* Light If me Batte P8 Batte P9 Ener P9.1 For t Energy mode * Peak (On-max) Category 12 Short Idle State Short Idle State Enabled Sleep (S3) - WO Off (S5) - WOL E Category D2 Short Idle State Enabled Long Idle State Enabled Long Idle State | erial and subs ased plastic n t sources are f ercury is used eries ery chemical c rgy consump | ttributes - Market r stance requirements naterial content is used | d in the product (See N less than 0,1 mg/lamp mps: and maxim anese dioxide | OTE B7): | er lamp: mg | Requireme Yes No | n.a. |
|--|---|--|---|--|--|-----------------------------|--------------------|
| Item Item Item P7.21* Biob P7.22* Light If me P8 Batte P8 P8 P8 P8 P9 Ener P9 P9 For t Energy mode * Peak (On-max) Category I2 Short Idle State Enabled Sleep (S3) - WO Off (S5) - WOLE Category D2 Short Idle State Enabled Long Idle State Enabled Long Idle State Enabled | erial and subs ased plastic n t sources are f ercury is used eries ery chemical c rgy consump | stance requirements naterial content is used free from mercury, i.e. specify: Number of lar composition: <i>Li-mange</i> tion (See NOTE B8) e following power leve Power level at | (continued) d in the product (See N less than 0,1 mg/lamp mps: and maxim | OTE B7): | ۶r lamp: mg | | n.a. |
| MateP7.21*BiobP7.22*LightIf meP8BattoP8.1*BattoP9For tEnergy mode *Peak (On-max)Category I2Short Idle StateEnabledSleep (S3) - WOOff (S5) - WOL ECategory D2Short Idle StateEnabledLong Idle StateEnabledLong Idle StateEnabledLong Idle StateEnabledLong Idle StateEnabledLong Idle StateEnabledLong Idle StateEnabled | ased plastic n t sources are t ercury is used eries ery chemical o rgy consump | naterial content is used free from mercury, i.e. specify: Number of lan composition: <i>Li-manga</i> tion (See NOTE B8) e following power leve Power level at | d in the product (See N less than 0,1 mg/lamp mps: and maxim anese dioxide | | ər lamp: mg | Yes No | |
| P7.21* Biob P7.22* Light If me Batte P8 Batte P8.1* Batte P9 Energy P9.1 For t Energy mode * Peak (On-max) Category I2 Short Idle State Short Idle State Enabled Sleep (S3) - WO Off (S5) - WOL E Category D2 Short Idle State Enabled Long Idle State Enabled Long Idle State Short Idle State Enabled | ased plastic n t sources are t ercury is used eries ery chemical o rgy consump | naterial content is used free from mercury, i.e. specify: Number of lan composition: <i>Li-manga</i> tion (See NOTE B8) e following power leve Power level at | d in the product (See N less than 0,1 mg/lamp mps: and maxim anese dioxide | | ər lamp: mg | | |
| P7.22* Light If me P8 P8.1* Batte P9.1 For t Energy mode * Peak (On-max) Category I2 Short Idle State Short Idle State Enabled Sleep (S3) - WO Off (S5) - WOL E Category D2 Short Idle State Enabled Long Idle State Long Idle State Enabled Short Idle State Enabled | t sources are f ercury is used eries ery chemical c rgy consump | free from mercury, i.e. specify: Number of lar composition: <i>Li-manga</i> tion (See NOTE B8) e following power leve Power level at | less than 0,1 mg/lamp mps: and maxim anese dioxide | | er lamp: mg | | |
| If me P8 Batt P8.1* Batte P9.1 For t Energy mode * Peak (On-max) Category I2 Short Idle State Short Idle State Enabled Sleep (S3) - WOL E Category D2 Short Idle State Enabled Long Idle State Enabled Sleep (S3) - WOL E Category D2 Short Idle State Enabled Long Idle State Enabled Long Idle State Enabled | ercury is used eries ery chemical c rgy consump | specify: Number of lar composition: <i>Li-manga</i> tion (See NOTE B8) e following power leve Power level at | mps: and maxim | | ər lamp: mg | | N // |
| P8.1* Batter P9 Energy P9.1 For t Energy mode * * Peak (On-max) Category I2 Short Idle State Enabled Long Idle State Enabled Sleep (S3) - WO Off (S5) - WOL E Category D2 Short Idle State Long Idle State Enabled Long Idle State Enabled | ery chemical c rgy consump | tion (See NOTE B8) e following power leve Power level at | | | | | |
| P9EnerP9.1For tEnergy mode *Peak (On-max)Category I2Short Idle StateEnabledLong Idle StateEnabledSleep (S3) - WOOff (S5) - WOL ECategory D2Short Idle StateEnabledLong Idle StateEnabledLong Idle StateEnabledLong Idle StateEnabled | rgy consump | tion (See NOTE B8) e following power leve Power level at | | | | | |
| P9.1 For t Energy mode * Peak (On-max) Category I2 Short Idle State Short Idle State Enabled Long Idle State Shoep (S3) - WOL E Off (S5) - WOL E Short Idle State Short Idle State Enabled Long Idle State Enabled Long Idle State Enabled Long Idle State Enabled | the product the | e following power leve Power level at | ls or energy consumpti | | | | |
| Energy mode * Peak (On-max) Category 12 Short Idle State Enabled Long Idle State Enabled Sleep (S3) - WOLE Off (S5) - WOLE Category D2 Short Idle State Enabled Long Idle State Enabled | | Power level at | | ons are reported: | | | |
| Category 12 Short Idle State Enabled Long Idle State Enabled Sleep (S3) - WO Off (S5) - WOL E Category D2 Short Idle State Enabled Long Idle State Enabled | | IUU V AC | Power level at 115V AC | Power level at 230 V AC | Reference/Standard modes and test me | | ' |
| Short Idle State Enabled Long Idle State Enabled Sleep (S3) - WO Off (S5) - WOL E Category D2 Short Idle State Enabled Long Idle State Enabled | | 138.1 W | 138.1 W | 138.1 W | Full load | | |
| Short Idle State Enabled Long Idle State Enabled Sleep (S3) - WO Off (S5) - WOL E Category D2 Short Idle State Enabled Long Idle State Enabled | | | | | + | | |
| Enabled Long Idle State Enabled Sleep (S3) - WO Off (S5) - WOL E Category D2 Short Idle State Enabled Long Idle State Enabled | 11/01 | | | | | | |
| Enabled Sleep (S3) - WO Off (S5) - WOL E <u>Category D2</u> Short Idle State Enabled Long Idle State Enabled | - WOL | 18.9 W | 18.6 W | 18.4 W | Use for ENERG registration (Pidle | | 1 |
| Off (S5) - WOL E Category D2 Short Idle State Enabled Long Idle State Enabled | - WOL | 18.3 W | 18.3 W | 18.1 W | Use for ENERG registration (Pidle | | l. |
| Category D2 Short Idle State Enabled Long Idle State Enabled | L Enabled | 1.8 W | 1.8 W | 1.8 W | Use for ENERG registration(Pslee | | 1 |
| Short Idle State Enabled Long Idle State Enabled | Enabled | 0.9 W | 0.9 W | 0.9 W | Use for ENERG registration(Poff) | Y STAR V8 | 1 |
| Enabled Long Idle State Enabled | | | | | | | |
| Enabled | - WOL | 24.3 W | 24 W | 23.7 W | Use for ENERG registration (Pidle | | 1 |
| Sloop (\$3) - WO | - WOL | 23.1 W | 23.1 W | 23.6 W | Use for ENERG registration (Pidle | | ł |
| Sieep (33) - WO | L Enabled | 1.2 W | 1.2 W | 1.3 W | Use for ENERG registration(Pslee | | I |
| Off (S5) - WOL E | Enabled | 0.9 W | 0.9 W | 0.9 W | Use for ENERG registration(Poff) | iy star v8 | 1 |
| EPS No-load | | W | W | W | | | \square |
| PTEC * | | W | W | W | | | |
| Typical Energy C | Consumption | | | | | | |
| ETEC * Annual Energy C | Consumption | <i>I2: 73.6</i> kWh/year <i>D2: 89</i> kWh/year | <i>I2: 73.3</i> kWh/year <i>D2: 89.2</i> kWh/year | <i>I2:</i> 72.6kWh/year <i>D2:</i> 89.5kWh/year | $E_{TEC} = (8760/1000) + P_{sleep} \times 0.45 + P_{lo} \\ P_{short_Idle} \times 0.3)$ | | |
| | | | S5) - WOL Enabled; Psleep | | | te - WOL Enable | ed |
| | , | , , | I Efficiency Marking Pro | otocol) *: | | | \square |
| Display resolution | n*: me | egapixels | | | | | \boxtimes |
| Default time to en | nter energy sa | ave mode: 25 minutes | | | | | |
| P9.2* Infor | mation about | the energy save functi | ion is provided with the | product. | | \square | |
| P9.3 Ener | rgy efficiency of | class (monitors only): | | | | | \boxtimes |
| | ssions | | | | | | |
| | | 0 | o ISO 9296 (See NOTE | / | | | (2) |
| P10.1 Mode Idle | e N * | Mode description HDD:Idle | | Statistical upper lim * 3.3 | it A-weighted sound p | ower level, L _{WA} | _{.,с} (В) |
| | ration * | HDD: Operating | | *3.4 | | | - |
| | | | nd pressure level (dB) L_{pAr} | | desktop – idle) | | |
| | | | $\frac{D_p Ar}{D pressure level (dB)} L_p Ar$ | | | | |
| | | | I | | | | |
| Mea | sured accordi | ng to: 🔀 ISO 7779 🗌 Other (on | _IECMA-74 ly if not covered by EC | | | | |

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available; see<u>http://www.ecma-international.org/publications/standards/Ecma-370.htm</u>

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

| Model nu | umber * | 10ST, 10SU, 10 | 0SV, 10SV, 10TR, 10U6, 10U7 | , | | Logo | Long | | | |
|-----------|--|---|--|---|-------------------------------------|----------------------------------|----------------------------------|-------------------|-----------|--|
| Issue dat | te * | 2020-11-6 | | | | | Leno | enovo. | | |
| Product | environm | nental attribut | es - Market requirements | (continued) | | | Require | ment | me | |
| Item | | | | | | | Yes | No | n.a | |
| | | nagnetic emissi | | | | | | | | |
| P10.4 | program(| (s): | the requirement for low freque | ncy electromagnet | ic fields of the fol | lowing volunta | ry | | \square | |
| P12 | | nics for compu | | | | | | | | |
| P12.1* | The displ | lay meets the er | gonomic requirements of ISO 9 | 241-307 for visual | display technolo | ogies. | | | | |
| P12.2* | The phys | ical input device | meets the requirements of IS | O 9995 and ISO 92 | 241-410. | | \square | | | |
| P13 | Packagii | ng and docume | ntation | | | | | | | |
| P13.1* | Product p Product p | backaging mater backaging mater | ial type(s): <i>Fabricated PE</i> ial type(s): <i>HDPE</i> weig | ht (kg): 0.78 weight (kg): (ht (kg): 0.016 | 0.25 | | | | | |
| P13.2* | Product plastic primary packaging is free from PVC. | | | | | | | | | |
| P13.3* | For product primary corrugated fiberboard packaging, specify the contained percentage of minimum post- | | | | | | | | | |
| P13.4* | Specify media for user and product documentation (tick box): | | | | | | | | | |
| P13.5 | User and | | s item if paper documentation entation on paper media is chlo | | | | | | | |
| | Totally chlorine-free | | | | | | | | | |
| | Elemental chlorine-free | | | | | | | | | |
| | Processed chlorine-free | | | | | | | | | |
| P14 | Voluntar | y programs | | | | | | | | |
| P14.1 | The prod | uct meets the re | quirements of the following vol | untary program(s) | | | | | | |
| | ENERGY | ′ STAR® | Criteria version: 8 | Date: | Product | category: 12, D | 02 | | | |
| | Eco-labe | | Criteria version: 8.0 | Date: | Product | category: Des | ktop Comput | er | | |
| P15 | | | See NOTE B10) | | | | | | | |
| P9 | | | specific configuration may | | | | | | | |
| | information knowledge | on contained in t ge available at th here is approxir | o representations, guarantees, his document. All information p e time of completion, and supp nate and provided for informati | provided by supplie plier shall have no | er in this docume obligation to upd | nt is provided I ate such inform | based on supp nation. The inf | olier's format | ion | |
| P9 | | | d Notebooks & Tablet Compute ergystar.gov/index.cfm?fusea | | ct.showProduct | Group&pgw_cc | ode=CO | | | |

Annex B1 of ECMA-370 5th edition (Lenovo)2015-04-08

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B2

| Reference | Declaration item |
|--|------------------------|
| Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications. | P1.1 |
| Regulation (EC) 1907/2006(REACH, Annex XVII | P1.2, P1.4, P1.6, P1.7 |
| Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances) | P1.3, P5.3 |
| Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002 | P1.5 |
| Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator. | P2.1, P2.2, P2,3, P8.1 |
| Directive 2006/95/EC (Low Voltage Directive) | P3.1 |
| Directive 2004/108/EC (EMC Directive) | P3.1 |
| Directive 1999/5/EC (R&TTE Directive) | P3.1 |
| Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions | P3.1, P3.2 |
| Regulation (EC) No 1272/2008 (CLP Regulation) | P7.19 |
| Directive 2004/12/EC (Packaging Directive) | P5.1 |
| Decision 97/129/EC (Secondary packaging legislation) | P5.2 |
| Directive 2012/19/EU (WEEE directive) | P6.1 |

Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

| Commercial name | ThinkCentre M720s SFF | Logo |
|------------------------|--|--------|
| Model Number | 10ST, 10SU, 10SV, 10SV, 10TR, 10U6, 10U7 | |
| Issue Date | 2020-11-6 | Lenovo |
| Additional information | | |

| P7.1.1 | Product environmental attributes | | | | | | | |
|--|---|--|--|--|--|--|--|--|
| (d) | year of manufacture: | | | | 2020 | | | |
| (e) | Etec value (kWh) per ErP Lot 3 Catego disabled and if the system is tested with | | | | cards (dGfx) are | | | |
| (f) | Etec value (kWh) per ErP Lot 3 Categor enable | ry and capability adjus | tments applied when a | II discrete graphics | cards (dGfx) are | | | |
| | | Category A (according to ErP Lot 3) | Category B (according to ErP Lot 3) | Category C (according to ErP Lot 3) | Category D (according to ErP Lot 3) | | | |
| | Memory over base [GB] | n/a | 64 | | 64 | | | |
| ents ting | Additional internal storage | (Yes / No) | Yes (Yes / No) | (Yes / No) | Yes (Yes / No) | | | |
| capability adjustments applied during testing | Discrete television tuner | (Yes / No) | No (Yes / No) | (Yes / No) | No (Yes / No) | | | |
| ability <i>e</i> lied du | Discrete Audio Card | (Yes / No) | No (Yes / No) | (Yes / No) | No (Yes / No) | | | |
| cap | Discrete graphics Card(s) [number / #] | #: (Yes / No) | Yes #: 1 (Yes / No) | #: (Yes / No) | Yes #: 1 (Yes / No) | | | |
| | Category of discrete graphics Card(s) | | G3 | | G3 | | | |
| esults | Etec Value (kWh) - dGfxdisabled all discrete graphics cards (dGfx) are disabled/ UMA is active for switchable graphics/ product has no graphics cards (dGfx) | | | | | | | |
| Test results | Etec Value (kWh) - dGfxenabled all discrete graphics cards (dGfx) are enabled | | 114.54 | | 110.81 | | | |
| (g) | Idle state power demand (Watts); | | | | 31.12 | | | |
| (h) | Sleep mode power demand (Watts); | | | | 1.65 | | | |
| (i) | Sleep mode with WOL enabled power d | emand (Watts) (where | enabled); | | 1.65 | | | |
| (j) | Off mode power demand (Watts); | | | | 0.90 | | | |
| (k) | Off mode with WOL enabled power demand (Watts) (where enabled); 0.99 | | | | | | | |
| (I) | Internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable): PA-1181-7 10% 78.33 20% 84.22 50% 86.95 100% 85.09 Average 85.42 | | | | | | | |
| (m) | external power supply efficiency (if appli | cable)*: | | | | | | |
| | Average active efficiency: n/a | | | | | | | |
| (0) | *internal note: show values for all available external p Minimum number of loading cycles that | | tand (applies only to n | otebook computers): | n/a | | | |
| (p-1) | the measurement methodology used efficiency: | to determine informa | ation mentioned in p | oints (I) – internal F | PSU | | | |
| | 80Plus Program | | | | | | | |

| (0) | | | | (; ; ; ; ; ; ; ;) ; ; ; ; ; ; ; ; ; ; ; | |
|----------|---|------------|---|---|------------|
| (p-2) | the measurement n efficiency: | nethodolo | gy used to determine information | n mentioned in points (m) – external PSU | |
| | eniciency. | | N/A | | |
| (0) | | | | | |
| (p-3) | the measurement m batteries: | nethodolo | gy used to determine information | n mentioned in points (o) - loading cycles | |
| | | | N/A | | |
| (p-4) | the measurement me | athodolog | y used to determine information me | entioned in maximum, idle, sleep, off mode | |
| (p-4) | | | 1 in the Product IT Eco Declaration | | |
| | | IEC 6 | 2623 / IEC EN50564:2011 measur | ement methodology | |
| (q) | sequence of steps fo | r achievir | ng a stable condition with respect to | power demand: | |
| | | | Bower on > Weit E minutes > St | able condition | |
| | | | Power on -> Wait 5 minutes ->St | | |
| (r) | description of how sl | eep and/o | or off mode was selected or program | mmed: | |
| | | E | Segin menu -> Power -> Select sl | eep or off mode | |
| (c) | soquence of events i | roquirod t | a reach the mode where the equipr | ment automatically changes to sleep and/or | |
| (s) | off mode: | equired t | o reach the mode where the equipt | nent automatically changes to sleep and/or | |
| | Control Pan | | v Ontions > Change Settings > P | Restore default settings for this plan | |
| | Control Fail | er->rowe | in Options-> Change Settings-> N | estore default settings for this plan | |
| (t) | | | | matically reaches sleep mode, or another | 25 minutes |
| (u) | | | | equirements for sleep mode (in minutes): e computer automatically reaches a | 25 minutes |
| () | power mode that has a lower power demand requirement than sleep mode (in minutes): | | | | |
| v) w) | the length of time before the display sleep mode is set to activate after user inactivity (in minutes): information on the energy-saving potential of power management functionality: | | | | 10 minutes |
| () | | leigy cut | | | |
| | | | N/A | | |
| (x) | user information on h | now to en | able the power management function | onality: | |
| | | | Refer to User Guid | e | |
| (| toot poromotoro for p | | vente: test voltage in V and frogu | analy in Hz total harmonia distortion of the | |
| (z) | electricity supply sys | tem, — ir | formation and documentation on the | ency in Hz, — total harmonic distortion of the ne instrumentation, set-up and circuits used | |
| | for electrical testing: | | | | |
| | Test voltage in V and Total harmonic distor | | e electricity supply system≤2% | | |
| | Information and docu | umentatio | n on the instrumentation, set-up an | d circuits used for electrical testing | |
| | Instrument | t | Range Used Or *** | Make and Model ** | |
| | Type AC Power Sou | 1500 | 1~280VAC:1~550HZ:1000VA. | NE-EC10008- SN:0152124 | |
| | AC Power Sol | urce | 1~200VAC,1~550HZ;1000VA. | NF;EC1000S; SN:9152124 | |
| | Digital Wate | ch | Full range | CASIO; HS-70W; SN:208Q08R | |
| | | | 0.0001/0.000 | YOKOGAWA:WT210;SN:91M944 | |
| | Power Mete | er | 0~600V;0~20A | 560 | |
| | Hygrothermog | - | 15~35°C/15~90% | testo; 608-H1,SN:1034895602 | |
| | Thermal anemo Light Measur | | 0~20m/s,-20~70℃ 1°;1-300cd/ m ² | Testo;425;SN:02591883 Konica Minolta:LS-110; | |
| Additio | n Notebook Battery | <u> </u> | | | |
| luuntio | | | y[ies] <u>not</u> user replaceable | Battery[ies] user replaceable | n/a |
| | | | tery[ies] in this product cannot be | e easily | |
| | | | d by users themselves. 1) | | |
| Internal | /built-in Battery | | | | |
| Externa | l/detachable Battery | | | | <u> </u> |
| | - | | | | |
| Bios Ba | ckup Battery | | | | |
| Other: | | | | | |
| Additior | al information | I | | | |
| | | | | | |
| | | | | | |
| | | | | | |

1) The battery[ies] in this product cannot be easily replaced by users themselves. Акумулаторната[ите] батерия[и] в този продукт не може да се замени[ят] лесно от самите потребители. Las baterías de este producto no pueden ser sustituidas fácilmente por los propios usuarios. Výměnu baterie/baterií v tomto výrobku by neměli provádět sami uživatelé.

Brugeren kan ikke uden videre udskifte batteriet/batterierne i dette produkt.

Der Akku/die Akkus dieses Produkts kann/können nicht ohne weiteres vom Benutzer selbst ausgetauscht werden.

Kasutajad e saa selle toote akut/akusid ise hõlpsasti asendada. Ημπαταρία[-ες] στοπροϊόναυτόδενμπορούννααντικατασταθούνεύκολααπότουςίδιουςτουςχρήστες La/les batterie(s présente(s) dans ce produit ne peuvent être facilement remplacée(s) par les utilisateurs eux-mêmes.

La batteria/le batterie in questo prodotto non può/possono essere facilmente sostituita/e dall'utente.

Lietotāji paši nevar nomainīt šā ražojuma akumulatoru(-us).

šio gaminio baterijos [baterijų] pats vartotojas negali lengvai pakeisti. A termék akkumulátorát/akkumulátorait a felhasználó nem tudja egyedül egyszerűen kicserélni. II-batterija/batteriji f'dan il-prodott ma tistax/jistgħux tiġi/jiġu sostitwita/i mill-utenti stess.

Batterija batterija i dan ir-prodott ma itstav/jstgnot tigvijgu sostitivitari mil-utentu stess. Batteriet [ene] i dette produktet kan ikke lett erstattes av brukerne selv. De batterij(en) in dit product is (zijn) door de gebruiker niet gemakkelijk vervangbaar. Użytkownik nie może sam w łatwy sposób wymienić baterii w tym produkcie. A ou as baterias deste produto não podem ser facilmente substituídas pelos próprios utilizadores. Bateria (bateriile) din acest produs nu poate (pot) fi uşor înlocuită (înlocuite) de utilizatorii înşişi. Batériu(-ie) v tomto výrobku nemôže vymieňať používateľ.

Baterij/baterije v tem vijozeliku uporabniki sami ne morejo zlahka zamenjati. Tämän tuotteen akku [akut] ei[vät] ole helposti käyttäjän vaihdettavissa. Det är inte enkelt för kunden att själv byta ut batteriet/batterierna.

Bu üründeki batarya(lar) kullanıcılar tarafından kolaylıkla değiştirilemez.