



ECMA/TC38-TG3/2015/026 (Rev. 1 – 15 April 2015)

Annex B2 - Product environmental attributes Desktop/All-in-One Computers

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lenovo	Lenovo Lenovo Lenovo	
Company name *	Lenovo		
Contact information *	Lenovo Global Environmental Affairs		ODOVO
e-mail address	Alvin L Carter		LCIIOVO
	alcarter@lenovo.com		
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment	.html	
Additional information	The latest version of this document can be found at:		
	http://www.lenovo.com/ecodeclaration		

The company declares (based on product specification or test results based obtained from sample testing), that the product
conforms to the statemen	nts given in this declaration.
Type of product *	Desktop
Commercial name *	Lenovo Legion Y720T
Model number *	90H5, 90H6, 90H9
Issue date *	2017/5/26
Intended market *	☑ Global Europe Asia, Pacific & Japan Americas Other
Additional information	ENERGY STAR® Qualified; GREENGUARD Certified

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products

Model nu	ımber *	90H5, 90H6, 90H9	19								Logo		one	21/	
Issue dat	te *	2017/5/26										<u> </u>	_enc		J _{TM}
Product	environ	mental attributes	es - L	_egal re	equiremo	ents						F	Require	men	met
Item													Yes	No	n.a.
P1	Hazardo	ous substances and	nd pre	eparatio	ons										
P1.1*	Products	s do comply with cur	urrent	t Europe	an RoHS	Directiv	/e. (See	legal ref	ference	and NOT	E B1)		\boxtimes		
P1.2*		s do not contain Asb nt: Legal reference h					on value.								
P1.3*	hydrobro trichloroe	s do not contain Ozo omofluorocarbons (F ethane, methyl brom ration values.	(HBFC	C), hydro	ochloroflu	orcarbo	ns (HCF	C), Halo	ons, carl	ontetrac		1,1-			
P1.4*		s do not contain mor					ed biphe	enyl (PC	B), 0,00	5% polycl	nlorinated		\boxtimes		
P1.5*	Products	s do not contain mor ntaining at least 48%	ore tha	an 0,1%	short cha	ain chlo					rbon atoms	in the	\boxtimes		
P1.6*	Parts wit	th direct and prolong al reference). nt: Max limit in legal	nged s	skin con	tact do no	ot releas	se nickel	in conc	entration		0,5 μg/cm ²	/week			
P1.7*	REACH	Article 33 information w.lenovo.com/social	tion ab	bout sub	stances ir	n article	s is avai	lable at		RL or mail	contact):		\boxtimes		
P2	Batterie	s													
P2.1*		oduct contains a batt Information on prop									the dispos	al			
P2.2*	Batteries referenc	s or accumulators do e)	do not	t contain	n more tha	an 0,000	05% of m	nercury	or 0,002	% of cadr	mium. (See	e legal			
P2.3*	Batteries	and accumulators	s are r	readily re	emovable	. (See I	egal refe	erence)					\boxtimes		
P3	Conforn	nity verification & I	Eco (design	(ErP)										
P3.1*	The prod	duct is CE-marked to laration of Conformi www.lenovo.com	to sho	ow confo	ormance v equested a	at (add I	ink or e-	mail add	dress):	`	gal referer	nce).			
P3.2*	The prod	duct complies with thal reference).								•					
	Required	d information is;		_ ~	in item P1 able at (ad			his docu	ument,						

Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium and

The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s) used (see legal reference).

The product packaging material is free from ozone depleting substances as specified in the Montreal

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

P5

P5.1*

P5.2*

P6 P6.1*

Product packaging

Treatment information

hexavalent chromium by weight of these together.

Protocol (see legal reference).

Comment: Legal reference has no maximum concentration values.

Information for recyclers/treatment facilities is available (see legal reference).

Model number *	90H5, 90H6, 90H9	Logo	Lanova
Issue date *	2017/5/26		Lei Iovo

Product	environmental attributes - Market requirements (See General NOTE GN below)			
		equire	ment	met
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.
P7	Design			
P7.1*	Disassembly, recycling Parts that have to be treated separately are easily separable			
P7.2*	Plastic materials in covers/housing have no surface coating.		+	-
			-	-
P7.3*	Plastic parts > 100 g consist of one material or of easily separable materials.		Щ.	<u> </u>
P7.4*	Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.			\perp
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.	\boxtimes		
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).		Ш	
	Product lifetime			
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives			
P7.8*	Upgrading can be done using commonly available tools			
P7.9	Spare parts are available after end of production for: 5 years			
P7.10	Service is available after end of production for: 5 years			
	Material and substance requirements			
P7.11*	Product cover/housing material type (e.g. plastics, metal, aluminum):			
D7 10	Material type: plastic Material type: metal Material type: Insulation materials of external electrical cables are PVC free.			
P7.12		井		井
P7.13	Insulation materials of internal electrical cables are PVC free.			<u> </u>
P7.14	External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and	\boxtimes		Ш
	polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts			
	containing more than 25% post-consumer recycled content.			
P7.15	Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2)			
P7.16	Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:			\boxtimes
	Marking:			
P7.17	Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components):			
	TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: Brominated Epoxy Resin , CAS #: 26265-08-7	Ш	Ш	ш
	Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4:			Ш
P7.18	Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in			
1 7.10	concentrations above 0,1%:			\boxtimes
	1. Chemical name: , CAS #: (See NOTE B4)			
	2. Chemical name: , CAS #: "			
	3. Chemical name: , CAS #: "			
	Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:			
P7.19	In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been			\boxtimes
	assigned the following Risk phrases; and Hazard statements:			
	The source(s) for these classifications is/are found at (add URL(s)): , (See note B5)			
P7.20*	Postconsumer recycled plastic material content is used in the product (See Note B6):	\boxtimes		
	If YES; at least one of the two alternatives below shall be answered;			
	a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as			
	a percentage of total plastic by weight) is %.			
	or b) The weight of recycled material is 101.575 g.			

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model number *	90H5, 90H6, 90H9	Logo	Lanova
Issue date *	2017/5/26		Lei Iovo

Product 6	environmental at	tributes - Market re	equirements (conti	nued)	F	Require	men	t met
Item			,	,		-	No	n.a.
	Material and subs	stance requirements	(continued)					
P7.21*	Biobased plastic m	aterial content is used	I in the product (See N	OTE B7):			\boxtimes	
	If YES; at least one	e of the two alternative	s below shall be answ	ered;				
				material content (calcu	ulated as a percentage			
	of total plastic	by weight) is %).					
		the biobased plastic r	naterial is g.					
P7.22*	Light sources are f	ree from mercury, i.e.	less than 0,1 mg/lamp					\square
		specify: Number of lan	nps: and maxim	um mercury content pe	er lamp: mg			
P8 P8.1*	Batteries	omposition: Lithium N	Janganoso Diovido					
P9	· ·	tion (See NOTE B8)	ianganese bioxide					
P9.1			s or energy consumpti	ons are reported:				
Energy mo		Power level at	Power level at	Power level at	Reference/Standard	for ene	ergy	П
		100 V AC	115 V AC	230 V AC	modes and test metho	od *		
Peak (On-I	max)	W	W	W	Full load			
Category	<u>y 13</u>							
Short Idle	State - WOL	29.23 W	28.53 W	28.85 W	Use for ENERGY STA	AR V6		
Enabled					registration (P _{idle})			
Long Idle	State - WOL	28.24 W	26.05 W	27.67 W	Use for ENERGY STA	AR V6		
Enabled					registration (P _{idle})			
Sleen (S3)	- WOL Enabled	1.38 W	1.40 W	1.56 W	Use for ENERGY ST	4R V6		
Cicop (CC)	7702 27700700	7.00 1.		7,00	registration(P _{sleep})			
Sloop (S3)	- WOL Disabled	W	W	W	Reference			
			• •					
Off (S5) - V	VOL Enabled	0.38 W	0.40 W	0.53 W	Use for ENERGY STA registration(P _{off})	AR V6		
Off (S5) - V	VOL Disabled	W	W	W	Use for ErP			
		W	W	W	Reference			
Cotomor	. D2							
Category								
	State - WOL	36.01 W	35.07 W	37.14 W	Reference			
Enabled								
	State - WOL	30.46 W	29.81 W	33.23 W	Reference			
Enabled								
Sleep (S3)	- WOL Enabled	1.39 W	1.40 W	1.56 W	Reference			
Sleep (S3)	- WOL Disabled	W	W	W	Reference			
Off (S5) - V	VOL Enabled	0.39 W	0.40 W	0.53 W	Reference			
Off (S5) - V	VOL Disabled	W	W	W	Reference			
- ()		10/	10/	10/				
		W	W	W	Reference			
EPS No-loa	ad upply / charger plugged in the	W	W	W				
wall outlet but disc	connected from the product.)	10/	10/	10/				
PTEC *	ergy Consumption	W	W	W				\boxtimes
ETEC *	ngy consumption	Cat. I3 128.85	Cat. I3 123.88	Cat. I3 127.62	$E_{TEC} = (8760/1000) \times ($	(P _{off} x 0.4	45	
Annual Ene	ergy Consumption	Cat. D2 152.57	Cat. D2 148.87	Cat. D2 160.32	$+P_{sleep} \times 0.05 + P_{long}$			

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

		kWh/year	kWh/year	kWh/year	P _{short_Idle} x 0.35)
		P _{off} : Off Mode(S	S5) - WOL Enabled; P _{sleep} :	Sleep Mode(S3) - WOL I	Enabled; P _{idle} : Idle State - WOL Enabled
External P	ower Supply Efficie	ency Level (International	Efficiency Marking Prof	tocol) * :	
Display res	solution * : n	negapixels			
Default tim	e to enter energy s	ave mode: 25 minutes			
P9.2*	Information about	t the energy save function	on is provided with the p	product.	
P9.3	Energy efficiency	class (monitors only):			
P10	Emissions				
	Noise emission	 Declared according to 	ISO 9296 (See NOTE	B9)	
P10.1	Mode	Mode description		Statistical upper limit	A-weighted sound power level, L _{WA,c} (B)
	Idle	* HDD:Idle		* 3.9	
	Operation	* HDD: Operating		* 3.9	
			d pressure level (dB) $L_{p m Am}$		n desktop – idle)
	Other mode	Declared A-weighted soun	d pressure level (dB) $L_{p{\rm Am}}$	28 (operator position	n desktop – operating)
	Measured accord	ling to: 🔀 ISO 7779 🗌	ECMA-74		
		Other	(only if not covered by	ECMA-74)	

Model nu	mber *	90H5, 90H6, 90H9				Logo	_enc	MO	
Issue date	e *	2017/5/26					-6110	, V U	TM
Product	environr	nental attributes	- Market requirements (continued)			Require	ment	met
Item			•	•			Yes	No	n.a.
		nagnetic emission							
P10.4	Compute program		requirement for low frequence	y electromagnetic field:	s of the follo	owing voluntary			
P12		mics for computing							
P12.1*			nomic requirements of ISO 92	•	•	jies.			\boxtimes
P12.2*	The phys	sical input device m	eets the requirements of ISO	9995 and ISO 9241-41	0.				\boxtimes
P13		ng and documenta							
P13.1*	Product	packaging material packaging material packaging material		weight (kg): 1.92 : (kg): 0.48 : (kg):					
P13.2*	Product	plastic primary pack	aging is free from PVC.				\boxtimes		
P13.3*	For product primary corrugated fiberboard packaging, specify the contained percentage of minimum post- consumer recovered fiber content: 70 %								
P13.4*		media for user and _l ronic, ⊠Paper, □	oroduct documentation (tick b Other	ox):					
P13.5	Ùser and		em if paper documentation us ation on paper media is chlori						
	Element	hlorine-free al chlorine-free ed chlorine-free							
P14									
P14.1		ry programs	rements of the following volui	ntary program(s):					
	ENERG' Eco-labe Eco-labe	Y STAR® el: Greenguard el:	Criteria version: V6.1 Criteria version: Criteria version:	Date: Oct-2014 Date: Date:	Product o Product o Product o	0 ,	er		
P15		nal information (Se							
P9			ecific configuration may va					. 0	
	informati knowled provided informati	ion contained in this ge available at the t I here is approximat ion.	epresentations, guarantees, a document. All information pro- ime of completion, and suppli e and provided for information	ovided by supplier in thi er shall have no obligat nal purposes only. See	is documen tion to upda a Lenovo A	t is provided base te such informatio	d on supp on. The in	olier's format	ion
P9			lotebooks & Tablet Computer idex.cfm?fuseaction=find_a_r			code=CO			

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1
Regulation (EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1

Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	Lenovo Legion Y720T	Logo	
Model Number	90H5, 90H6, 90H9		opovo
Issue Date	2017/5/26	L	enovo.
Additional information	ENERGY STAR® Qualified; GREENGUARD Certified		

	Product environmental attributes				
(d)	year of manufacture:			A	vailable on produc label
(e)	Etec value (kWh) per ErP Lot 3 Categorial disabled and if the system is tested with				cards (dGfx) are
f)	Etec value (kWh) per ErP Lot 3 Categorian enable	ry and capability adjust	tments applied when a	all discrete graphics	cards (dGfx) are
		Category A (according to ErP Lot 3)	Category B (according to ErP Lot 3)	Category C (according to ErP Lot 3)	Category D (according to ErP Lot 3)
	Memory over base [GB]				64
ents ting	Additional internal storage	(Yes / No)	(Yes / No)	(Yes / No)	Yes (Yes / No)
djustm ring tes	Discrete television tuner	(Yes / No)	(Yes / No)	(Yes / No)	No (Yes / No)
capability adjustments applied during testing	Discrete Audio Card	(Yes / No)	(Yes / No)	(Yes / No)	No (Yes / No)
cap	Discrete graphics Card(s) [number / #]	#: (Yes / No)	#: (Yes / No)	#: (Yes / No)	Yes #: 1 (Yes / No)
	Category of discrete graphics Card(s)				G7
esults	Etec Value (kWh) - dGfx disabled all discrete graphics cards (dGfx) are disabled/ UMA is active for switchable graphics/ product has no graphics cards (dGfx)				102.36
Test results	Etec Value (kWh) - dGfx enabled all discrete graphics cards (dGfx) are enabled				133.39
g)	Idle state power demand (Watts);	1	1	1	Max 37.14
h)	Sleep mode power demand (Watts);				Max 1.59
i)	Sleep mode with WOL enabled power d	emand (Watts) (where	enabled);		Max 1.59
j)	Off mode power demand (Watts);				Max 0.54
k)	Off mode with WOL enabled power dem	and (Watts) (where en	abled);		Max 0.53
(I)	Internal power supply efficiency at 10 %	, 20 %, 50 % and 100 °	% of rated output pow	er (if applicable):	
	PC7033: 10% 79.94% 20% 84.48%	50% 86.15% 100% 8	33.33% Average 84	.65%	
(m)	External power supply efficiency (if appli	icable)*:			
	Average active efficiency:				
	*internal note: show values for all available external p				
(o)	Minimum number of loading cycles that	the batteries can withs	tand (applies only to r	notebook computers):	N/A
(p-1)	Measurement methodology used to dete	ermine information mer 80 PLUS® Progra	,	nternal PSU efficiency	:
(p-2)	Measurement methodology used to dete	ermine information mer	ntioned in points (m) -	external PSU efficiend	су:

(p-3)	Measurement metho	dology us	sed to determine information mention <i>N/A</i>	oned in p	points (o) – loading cycles batter	ries:	
(p-4)			sed to determine information mention in the Product IT Eco Declaration		naximum, idle, sleep, off mode		
		IEC 62	2623 / IEC EN50564:2011 measur	rement n	nethodology		
q)	Sequence of steps for	or achievii	ng a stable condition with respect t	o power	demand::		
			Power on -> Wait 5 minutes ->St	table coi	ndition		
r)	Description of how sl	leep and/o	or off mode was selected or progra	mmed:			
		В	Begin menu -> Power -> Select sl	eep or o	ff mode		
s)	Sequence of events off mode:	required t	to reach the mode where the equip	ment aut	tomatically changes to sleep and	d/or	
	Control Pane	el->Powe	r Options-> Change Settings-> F	Restore (default settings for this plan		
)			ion before the computer automa ed the applicable power demand re				25
ı)	Length of time after	r a period	of user inactivity in which the c	ompute	r automatically reaches a pow		
/)			r demand requirement than sleep to splay sleep mode is set to activa				10
v)			ing potential of power managemen				-10
			N/A				
)	User information on I	how to en	able the power management funct	ionality:			
			Refer to User Guid	e			
)		system, -	nents: — test voltage in V and freq — information and documentation o				
·)	the electricity supply used for electrical tes Test voltage in V and Total harmonic distor	system, - sting: d frequenc rtion of the	— information and documentation of the control of	on the ins	strumentation, set-up and circuit		
)	the electricity supply used for electrical tes Test voltage in V and Total harmonic distor	system, - sting: d frequence rtion of the umentatio	— information and documentation of the cy in Hz 230V/50Hz e electricity supply system ≤2% n on the instrumentation, set-up an Range Used	on the ins	strumentation, set-up and circuit s used for electrical testing		
:)	the electricity supply used for electrical tes Test voltage in V and Total harmonic distormation and document of the Type	system, - sting: d frequenc rtion of the umentation	— information and documentation of cy in Hz 230V/50Hz e electricity supply system ≤2% n on the instrumentation, set-up an Range Used Or ***	on the ins	strumentation, set-up and circuit s used for electrical testing Make and Model **		
z)	the electricity supply used for electrical tes Test voltage in V and Total harmonic distor Information and document Type AC Power Sou	system, - sting: d frequence rtion of the umentation t	— information and documentation of the cy in Hz 230V/50Hz e electricity supply system ≤2% n on the instrumentation, set-up an Range Used Or *** 1~280VAC;1~550HZ;1000VA.	nd circuits	s used for electrical testing Make and Model ** 5;EC1000S; SN:9152124		
:)	the electricity supply used for electrical tes Test voltage in V and Total harmonic distormation and document of the Type	system, - sting: d frequence rtion of the umentation t	— information and documentation of cy in Hz 230V/50Hz e electricity supply system ≤2% n on the instrumentation, set-up an Range Used Or ***	on the instant of circuits NF CAS	s used for electrical testing Make and Model ** F;EC1000S; SN:9152124 IO; HS-70W; SN:208Q08R		
:)	the electricity supply used for electrical tes Test voltage in V and Total harmonic distor Information and document Type AC Power Sound Digital Water Power Meter Power Meters	system, - sting: d frequence rtion of the umentation t urce ch	— information and documentation of a cy in Hz 230V/50Hz e electricity supply system ≤2% n on the instrumentation, set-up an Range Used Or *** 1~280VAC;1~550HZ;1000VA. Full range 0~600V;0~20A	on the instance of the instanc	s used for electrical testing Make and Model ** E;EC1000S; SN:9152124 IO; HS-70W; SN:208Q08R OGAWA;WT210;SN:91M944 560		
:)	the electricity supply used for electrical tes Test voltage in V and Total harmonic distor Information and docu Instrument Type AC Power Sou Digital Water Power Meter Hygrothermogic	system, - sting: d frequence rition of the umentation t urce ch er	— information and documentation of any in Hz 230V/50Hz e electricity supply system ≤2% n on the instrumentation, set-up and Range Used Or *** 1~280VAC;1~550HZ;1000VA. Full range 0~600V;0~20A 15~35°C/15~90%	nd circuits NF CAS YOKO	sused for electrical testing Make and Model ** E;EC1000S; SN:9152124 IO; HS-70W; SN:208Q08R OGAWA;WT210;SN:91M944 560 o; 608-H1,SN:1034895602		
:)	the electricity supply used for electrical tes Test voltage in V and Total harmonic distor Information and document Type AC Power Sound Digital Water Power Meter Power Meters	system, - sting: d frequence rition of the umentation t urce ch er raph meter	— information and documentation of a cy in Hz 230V/50Hz e electricity supply system ≤2% n on the instrumentation, set-up an Range Used Or *** 1~280VAC;1~550HZ;1000VA. Full range 0~600V;0~20A	nd circuits NF CAS YOKO	s used for electrical testing Make and Model ** E;EC1000S; SN:9152124 IO; HS-70W; SN:208Q08R OGAWA;WT210;SN:91M944 560		
)	the electricity supply used for electrical tes Test voltage in V and Total harmonic distor Information and document Type AC Power Sound Digital Water Power Meter Hygrothermoging Thermal anemo	system, - sting: d frequence rition of the umentation t urce ch er raph meter	— information and documentation of control of the property of	nd circuits NF CAS YOKO	sused for electrical testing Make and Model ** E;EC1000S; SN:9152124 IO; HS-70W; SN:208Q08R OGAWA;WT210;SN:91M944 560 o; 608-H1,SN:1034895602 resto;425;SN:02591883		
z) Additio	the electricity supply used for electrical tes Test voltage in V and Total harmonic distor Information and document Type AC Power Sound Digital Water Power Meter Hygrothermoging Thermal anemo	system, - sting: d frequence rition of the umentatio t urce ch er raph meter ing	— information and documentation of control of the property of	nd circuits NF CAS YOKO	s used for electrical testing Make and Model ** E;EC1000S; SN:9152124 IO; HS-70W; SN:208Q08R DGAWA;WT210;SN:91M944 560 D; 608-H1,SN:1034895602 esto;425;SN:02591883 Konica Minolta;LS-110;	is	
	the electricity supply used for electrical tes Test voltage in V and Total harmonic distor Information and document of the Instrument of	system, - sting: d frequence rition of the umentatio t urce ch er raph meter ing	— information and documentation of control of the property of	nd circuits NF CAS YOKO	sused for electrical testing Make and Model ** E;EC1000S; SN:9152124 IO; HS-70W; SN:208Q08R OGAWA;WT210;SN:91M944 560 o; 608-H1,SN:1034895602 resto;425;SN:02591883	is	n/a
	the electricity supply used for electrical tes Test voltage in V and Total harmonic distor Information and document of the Instrument of	system, -sting: d frequency rition of the umentation t urce ch er raph meter ing Informa Battery The bat	— information and documentation of control of the property of	nd circuits NF CAS YOKC testo	s used for electrical testing Make and Model ** E;EC1000S; SN:9152124 IO; HS-70W; SN:208Q08R DGAWA;WT210;SN:91M944 560 D; 608-H1,SN:1034895602 esto;425;SN:02591883 Konica Minolta;LS-110;	is	n/a
dditio	the electricity supply used for electrical tes Test voltage in V and Total harmonic distor Information and document of the Instrument of	system, -sting: d frequency rition of the umentation t urce ch er raph meter ing Informa Battery The bat	— information and documentation of the property of the proper	nd circuits NF CAS YOKC testo	s used for electrical testing Make and Model ** E;EC1000S; SN:9152124 IO; HS-70W; SN:208Q08R DGAWA;WT210;SN:91M944 560 D; 608-H1,SN:1034895602 esto;425;SN:02591883 Konica Minolta;LS-110;	is	n/a
. <mark>dditio</mark>	the electricity supply used for electrical tes Test voltage in V and Total harmonic distor Information and document of the Instrument of	system, -sting: d frequency rition of the umentation t urce ch er raph meter ing Informa Battery The bat	— information and documentation of the property of the proper	nd circuits NF CAS YOKC testo	s used for electrical testing Make and Model ** E;EC1000S; SN:9152124 IO; HS-70W; SN:208Q08R DGAWA;WT210;SN:91M944 560 D; 608-H1,SN:1034895602 esto;425;SN:02591883 Konica Minolta;LS-110;	is	n/a
.dditio nternal xterna	the electricity supply used for electrical tes Test voltage in V and Total harmonic distor Information and document Type AC Power Sout Digital Water Power Meter Hygrothermoger Thermal anemore Light Measur //built-in Battery	system, -sting: d frequency rition of the umentation t urce ch er raph meter ing Informa Battery The bat	— information and documentation of the property of the proper	nd circuits NF CAS YOKC testo	s used for electrical testing Make and Model ** E;EC1000S; SN:9152124 IO; HS-70W; SN:208Q08R DGAWA;WT210;SN:91M944 560 D; 608-H1,SN:1034895602 esto;425;SN:02591883 Konica Minolta;LS-110;	is	n/a
dditio uternal xterna	the electricity supply used for electrical tes Test voltage in V and Total harmonic distormation and document of the Information and document of the Instrument of the Instru	system, -sting: d frequency rition of the umentation t urce ch er raph meter ing Informa Battery The bat	— information and documentation of the property of the proper	nd circuits NF CAS YOKC testo	s used for electrical testing Make and Model ** E;EC1000S; SN:9152124 IO; HS-70W; SN:208Q08R DGAWA;WT210;SN:91M944 560 D; 608-H1,SN:1034895602 esto;425;SN:02591883 Konica Minolta;LS-110;	is	n/a
dditio xternal xterna ios Ba ther:	the electricity supply used for electrical tes Test voltage in V and Total harmonic distormation and document of the Information and document of the Instrument of the Instru	system, -sting: d frequency rition of the umentation t urce ch er raph meter ing Informa Battery The bat	— information and documentation of the property of the proper	nd circuits NF CAS YOKC testo	s used for electrical testing Make and Model ** E;EC1000S; SN:9152124 IO; HS-70W; SN:208Q08R DGAWA;WT210;SN:91M944 560 D; 608-H1,SN:1034895602 esto;425;SN:02591883 Konica Minolta;LS-110;	is	n/a

¹⁾The battery[ies] in this product cannot be easily replaced by users themselves.
Aкумулаторната[ите] батерия[и] в този продукт не може да се замени[ят] лесно от самите потребители.
Las baterías de este producto no pueden ser sustituidas fácilmente por los propios usuarios.
Výměnu baterie/baterií v tomto výrobku by neměli provádět sami uživatelé.
Brugeren kan ikke uden videre udskifte batteriet/batterierne i dette produkt.

Der Akku/die Akkus dieses Produkts kann/können nicht ohne weiteres vom Benutzer selbst ausgetauscht werden.

H μπαταρία[-ες] στο προϊόν αυτό δεν μπορούν να αντικατασταθούν εύκολα από τους ίδιους τους χρήστες La/les batterie(s présente(s) dans ce produit ne peuvent être facilement remplacée(s) par les utilisateurs eux-mêmes.

Korisnik ne može lako zamijeniti Bateriju sam u ovom proizvodu.

La batteria/le batterie in questo prodotto non può/possono essere facilmente sostituita/e dall'utente. Lietotăji paši nevar nomainît šă ražojuma akumulatoru(-us). Šio gaminio baterijos [bateriju] pats vartotojas negali lengvai pakeisti. A termék akkumulátorát/akkumulátorait a felhasználó nem tudja egyedül egyszerűen kicserélni. Il-batterija/batteriji fdan il-prodott ma tistax/jistghux tigi/jigu sostitwita/i mill-utenti stess.

Batteriet [ene] i dette produktet kan ikke lett erstattes av brukerne selv.

De batterij(en) in dit product is (zijn) door de gebruiker niet gemakkelijk vervangbaar. Użytkownik nie może sam w łatwy sposób wymienić baterii w tym produkcie. A ou as baterias deste produto não podem ser facilmente substituídas pelos próprios utilizadores.

Bateria (bateriile) din acest produs nu poate (pot) fi uşor înlocuită (înlocuite) de utilizatorii înşişi. Batériu(-ie) v tomto výrobku nemôže vymieňať používateľ. Baterij/baterije v tem izdelku uporabniki sami ne morejo zlahka zamenjati.

Tämän tuotteen akku [akut] el[vät] ole helposti käyttäjän vaihdettavissa. Det är inte enkelt för kunden att själv byta ut batteriet/batterierna. Bu üründeki batarya(lar) kullanıcılar tarafından kolaylıkla değiştirilemez.