

Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lenovo	Logo				
Company name *	Lenovo					
Contact information *	Lenovo Global Environmental Affairs Alvin L Carter 1009 Think Place Building 2 / 5F1 Morrisville, North Carolina 27560 alcarter@lenovo.com					
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment.html					
Additional information	The latest version of this document can be found at http://www.lenovo.com/social_responsibility/us/en/datasheets_notebooks.html					

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.							
Type of product *	Notebook						
Commercial name *	Lenovo E42-80, ZhaoyangE42-80,						
	Lenovo V510-14ISK, Lenovo V510-14IKB						
Model number *	80T8, 80T9, 80WT, 80WR						
Issue date *	2016-06-30						
Intended market *	🔀 Global 📃 Europe 📃 Asia, Pacific & Japan 📃 Americas 📃 Other						
Additional information							

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Control	Requireme	nt met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).	I 🛛	

Model n	umber *	80T8, 80T9, 80WT, 80WR			
Issue da	te *	2016-06-302016-06-30 Logo	Len	ovc	
Product	t environ	mental attributes - Legal requirements	Require	ement	tmet
Item			Yes	No	n.a.
P1	Hazardo	ous substances and preparations		-	-
P1.1*	Product 0.1% po	s do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromiu lybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal e and Note B1)	m, 🔀		
P1.2*	Product	s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value.	\boxtimes		
P1.3*	Products hydrobro trichloro	s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), omofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- ethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum ration values.			
P1.4*	Product	s do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated /l (PCT) in preparations (see legal reference).	\square		
P1.5*	Product	s do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in t ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).	he 🔀		
P1.6*	Textile a Tris-(azi	nd leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS) ridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). nt: Legal reference has no maximum concentration values.),		
P1.7*	Textile a	nd leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split c amines. (See legal reference and Note B1)			\boxtimes
P1.8*	Wooder pentach	parts do not contain arsenic and chromium as a wood preservation treatment as well as lorophenol and derivatives (see legal reference). nt: Legal reference has no maximum concentration values.			
P1.9*	Parts wi microgra	th direct and prolonged skin contact do not release nickel in concentrations above 0.5 am/cm ² /week (see legal reference). ht: Max limit in legal reference when tested according to EN1811:1998.			
P1.10*	REACH	Article 33 information about substances in articles is available at (add URL or mail contact): ww.lenovo.com/social_responsibility/us/en/materials.html	\boxtimes		
P2	Batterie	S			
P2.1*	more that marked	oduct contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is I in user manual. (See legal reference)			
P2.2*	Button c	ells used in the product do not contain more than 2% by weight of mercury. Other batteries or ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference			
P2.3*	design o	s and accumulators are easily removable by either users or service providers (as dependent on th of the product). Exception: Batteries that are permanently installed for safety, performance, medic ntegrity reasons do not have to be "easily removable". (See legal reference)			
P3		EMC connection to the telephone network and labeling			
P3.1*	The pro	duct complies with legally required safety standards as specified (see legal reference).	\boxtimes		
P3.2*	The pro	duct complies with legally required standards for electromagnetic compatibility (see legal referenc	e). 🔀		
P3.3*	If produc	ct is intended for connection to a public telecom network or contains a radio transmitter, it complie ally required standards for radio and telecommunication devices (see legal reference).			
P3.4*		duct is labeled to show conformance with applicable legal requirements (see legal reference).	\boxtimes		
P4	Consun	nable materials			
P4.1*	If a phot	o conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see erence and Note B1).			
P4.2*	-	er is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).			\boxtimes
P4.3*	product/	/toner formulation/preparation is classified as hazardous according to applicable regulations, the packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these tents is available (see legal reference).			
P5		t packaging			
P5.1*	Packagi	ng and packaging components do not contain more than 0.01% lead, mercury, cadmium a ent chromium by weight of these together.	nd 🔀		
P5.2*		ackaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\square		
P5.3*	The pro Protoco	duct packaging material is free from ozone depleting substances as specified in the Montr (see legal reference). nt: Legal reference has no maximum concentration values.	eal 🔀		

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *		80T8, 80T9, 80WT, 80WR			
Issue date *		2016-06-302016-06-30 Logo	Lend	OVO	L
		mental attributes - Market requirements - Environmental conscious design	Require		
Item P6		tory to fill in. Additional information regarding each item may be found under P14. nt information	Yes	No	n.a.
P6.1*		on for recyclers/treatment facilities is available (see legal reference).			
P7	Design				
	Disasse	mbly, recycling			
P7.1*		t have to be treated separately are easily separable	\square		
P7.2*		aterials in covers/housing have no surface coating.		\square	
P7.3*	Plastic pa	arts >100g consist of one material or of easily separable materials.	\square		
P7.4*		arts >25g have material codes according to ISO 11469 referring ISO 1043.	\boxtimes		
P7.5	Plastic pa	arts are free from metal inlays or have inlays that can be removed with commonly available tools.	\square		
P7.6*	Labels a	re easily separable. (This requirement does not apply to safety/regulatory labels).	\boxtimes		
	Product				
P7.7*		g can be done e.g. with processor, memory, cards or drives	\square		
P7.8*	Upgradin	g can be done using commonly available tools			
P7.9.	Spare pa	rts are available after end of production for: 5 years			
P7.10		s available after end of production for: 5 years			
D7.44		and substance requirements			
P7.11*		cover/housing material type: type: >PC+ABS-TD15 Material type: Material type:			
	FR(40)<				
P7.12		cable insulation materials of power cables are PVC free.		\boxtimes	
P7.13	Electrica	cable insulation materials of signal cables are PVC free			
P7.14	All cover	/housing plastic parts >25g are free from chlorine and bromine.		Ē	
P7.15	All printe Note B2)	d circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (Se			
P7.16	Flame re	tarded plastic parts >25g in covers / housings are marked according ISO 1043-4: >PC+ABS-TD15 FR(40)<	\boxtimes		
P7.17	Alt. 1			_	
		I specifications of flame retardants in printed circuit boards >25g (without components):			
	TBBPA (additive) 🔲, TBBPA (reactive) 🔀, Other; chemical name: , CAS #:			
	Alt. 2				
		I specifications of flame retardants in printed circuit boards (without components) >25g according 3-4: Brominated Epoxy Resin See P14			
P7.18	Alt. 1]
		etarded plastic parts >25g contain the following flame retardant substances/preparations ations above 0.1%:	in 🔄		
		ent: No legal limits exist, this is a market requirement.			
		cal name: , CAS #:			
	2. Chemi	cal name: , CAS #:			
		cal name: , CAS #:			
	Alt. 2 Chemica	I specifications of flame retardants in plastic parts >25g according ISO 1043-4:			
	FR(40)	specifications of fiame relations in plastic parts >259 according 150 To45-4.	\boxtimes		
P7.19	Plastic pa	arts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, 6, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)			
P7.20		lastic parts' weight >25g, recycled material content is 6.7 %.			
P7.21		lastic parts' weight >25g, biobased material content is 0% .			
P7.22		rces are free from mercury	\boxtimes		
P8	Batterie:	y is used specify: Number of lamps: and max. mercury content per lamp: mg			
P8.1*		hemical composition: <i>Lithium Ion/Lithium Manganese Dioxide</i>			
P8.2		meet the requirements of the following voluntary program/s: US PBRC			H

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	80T	8, 80 7 9, 8	OWT, 80W	R			
Issue date *	2016-06-30	2016-06-30			Logo	Lenovo	
Product environm	nental attri	butes - Market	t requirements (continued)		Requirement	met
Item						Yes No	n.a.
	consumptio		vels or energy cons	umptions are re	norted: See P14		
Energy mode *			t Power level at 115 V AC			gy modes and test	
Peak (On-max)		W W	W W	230 VAC W	Full load		
Category I1							
Short Idle State - W	/OL Enabled	8.208 W	8.496 W	8.268 W	Use for ENERGY STAR V6 r	egistration (P _{idle})	
Long Idle State - W	OL Enabled	5.436 W	5.508 W	5.496 W	Use for ENERGY STAR V6 r	egistration (P _{idle})	
Sleep (S3) - WOL E	nabled	0.804 W	0.804 W	0.852 W	Use for ENERGY STAR V6 r	egistration(P _{sleep})	
Sleep (S3) - WOL D	isabled	W	W	W	Reference		
Off (S5) - WOL Ena	bled	0.504 W	0.504 W	0.552 W	Use for ENERGY STAR V6 r	egistration(P _{off})	
Off (S5) - WOL Disa	abled	W	W	W	Use for EuP		
Category I2							
Short Idle State - W	/OL Enabled	8.112 W	8.232 W	8.208 W	Use for ENERGY STAR V6 r	egistration(P _{idle})	
Long Idle State - W	OL Enabled	5.256 W	5.472 W	5.364 W	Use for ENERGY STAR V6 r	egistration(P _{idle})	
Sleep (S3) - WOL E	nabled	0.732 W	0.732 W	0.780 W	Use for ENERGY STAR V6 r	egistration (P _{sleep})	
Sleep (S3) - WOL D	isabled	W	W	W	Reference	-	
Off (S5) - WOL Ena	bled	0.468 W	0.468 W	0.504 W	Use for ENERGY STAR V6 r	egistration(P _{off})	
Off (S5) - WOL Disa		W	W	W	Use for EuP	• • • • •	
EPS No-load		0.057 W	0.060 W	0.108 W			
(External power sup plugged in the wall of disconnected from the	outlet but						
PTEC * Typical Energy Cons	sumption	W	W	W			
TEC * Typical Energy Cons	sumption	kWh/week	kWh/week	kWh/week			
ETEC * Annual Energy Cons	sumption	11: 29.90 12: 29.19 kWh/year	11:30.72 / 12:29.70 kWh/year	11: 30.36/ 12: 29.76 kWh/year	$E_{TEC} = (8760/1000) \times (P_{off} \times 0.)$ + $P_{long_ldle} \times 0.10 + P_{short_ldle} \times 0.0$	0.30)	
Display resolution*	· 1 040 Meg		S5) - WOL Enabled;	P _{sleep} : Sleep Mode	(S3) - WOL Enabled; P _{idle} : Idle Sta	ate - WOL Enabled	
		•					
Print Speed *		ges per minute					\square
Default time to enter P9.2* Informat	0,		es ction is provided wi	th the product			H
P9.3* The proc	duct meets th	e energy require	ments of the followi	ng voluntary pro	gram/s: Product category:		
Others s			- autou ouno 2, 20		Saudi dalogory.		Н
P10 Emissio	-						
P10.1 Mode		eclared according de description	g to ISO 9296	Declared	Declared A-we	aighted	
		25 200011011		A-weighted	sound pressure leve	•	
				sound powe		Bystander positions	
				level L_{WAd}	Desktop X		
						nly if product is not operator attended)	
Idle	*	HDD:Idle		* 2.5	24 (operator position) bystander pos);19.0 (1-meter	
Operatio	on *	HDD: Operating		* 2.8	30 (operator position) bystander po	; 25.0 (1-meter	
Other m	ode						
Measure	ed according	to: 🔀 ISO7779	ECMA-74				
		Other			with L _{pAm} measurement distand	ce m)	Ļ
P10.2 The proc	duct meets th	e acoustic noise	requirements of the	e tollowing volunt	ary program/s:		\bowtie

Model nur	mber *	80T8, 80T9, 80WT, 80WR								
Issue date *		2016-06-302016-06-30	Logo		Leno	VO.				
-	•									
	environn	nental attributes - Market requirements (continued)			Require					
Item					Yes	No	n.a.			
		al emissions from printing products								
P10.3*		formed according to ECMA-328 (ISO/IEC 28360) standard, other specify:					\square			
P10.4	Typical e	emission rate (print phase) is (mg/h):					\boxtimes			
	Dust Ozone Styrene Benzene TVOC									
P10.5	Chemica	I emission requirements of the following voluntary program/s are met for :	_	_			\boxtimes			
		Dust Ozone Styrene Benzene	TVOC							
		nagnetic emissions								
P10.6	•	er display meets the requirement for low frequency electromagnetic fields of the fol	lowing vo	luntary	\bowtie					
D44	program									
P11 P11.1*		able materials for printing products Data Sheet (SDS) is available for the ink/toner preparation, even if not legally requ	uired (acc	D4 2)						
	•		•	,		<u> </u>				
P11.2*	EN1228	ontaining post-consumer recycled fibers can be used, provided that it meets to 1.	he require	ements c			\boxtimes			
P11.3*	2-sided (duplex) printing/copying is an integrated product function.					\boxtimes			
P12	Ergonor	nics for computing products								
P12.1*	-	lay meets the ergonomic requirements of ISO 9241-307 for visual display technolo	gies.				\mathbb{X}			
P12.2*		sical input device meets the requirements of ISO 9995 and ISO 9241-410.					\mathbb{X}			
P13		ng and documentation								
P13.1*		packaging material type(s): Corrugated carton								
		(g): 0.310								
		packaging material type(s): <i>paper(manuel)</i> .g): <i>0.135</i>								
	• •	packaging material type(s): EPE cushion								
		(g): 0.060								
		packaging material type(s): partition board								
	weight (k									
		packaging material type(s): <i>PE bag</i>								
P13.2*		g): 0.016 plastic packaging is free from PVC.			\square					
P13.3*		nedia for user and product documentation (tick box):								
1 10.0		$c \ \square, Paper \ \square, Other \ \square$								
P13.4*	For pape	r user and product documentation, please specify contained percentage of post-co	onsumer i	ecycled						
	fiber: 0									
P14		al information (See Note B4)								
		supplier makes no representations, guarantees, assurances or warranties whether on contained in this document. All information provided by supplier in this docume								
		ge available at the time of completion, and supplier shall have no obligation to upda					on			
		here is approximate and provided for informational purposes only. See a Lenovo <i>i</i>								
	informati	on.								
P9		rgy Star Qualified Notebooks & Tablet Computers for the latest information:								
	http://ww	ww.energystar.gov/index.cfm?fuseaction=find_a_product.showProductGroup	p&pgw_c	ode=CO						
1										

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19

Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	Lenovo E42-80, ZhaoyangE42-80, Lenovo V510-14ISK, Lenovo V510-14IKB	Logo
Model Number Issue Date	80T8, 80T9, 80WT, 80WR 2016-06-30	Lenovo
Additional information		

P7.1.1	Product environmental attributes	
(d)	year of manufacture:	Availible on product labe
(e)	E TEC value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete g disabled and if the system is tested with switchable graphics mode with UMA driving the display:	graphics cards (dGfx) are
	Category (according to ErP Lot 3): A Etec: 18.62	
(f)	E TEC value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete g enabled:	raphics cards (dGfx) are
	Category (according to ErP Lot 3): <i>B</i> Etec: 18.69	
(g)	idle state power demand (Watts);	5.9 for Category A and B
(h)	sleep mode power demand (Watts);	0.73 for Category A; 0.74 for Category B
(i)	sleep mode with WOL enabled power demand (Watts) (where enabled);	0.74 for Category A; 0.75 for Category B
(j)	off mode power demand (Watts);	0.46 for Category A; 0.47 for Category B
(k)	off mode with WOL enabled power demand (Watts) (where enabled);	0.47 for Category A; 0.48 for Category B
(I)	internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable):
	10% 20% 50% 100% Average	
(m)	external power supply efficiency (if applicable):	
	Average*: 45W:87.58% 65W:88.65%	
	*internal note: show values for all available external power supplies	
(0)	the minimum number of loading cycles that the batteries can withstand (applies only to notebook co	mputers): 800cycle
(p-1)	the measurement methodology used to determine information mentioned in points (I) - interefficiency:	ernal PSU
	N/A	
(p-2)	the measurement methodology used to determine information mentioned in points (m) – ext efficiency: EPA"Test Method for Calculating the Energy Efficiency of Single-Voltage External AC-DC ar	

,	batteries:								
IEC61960 measurement methodology									
	the measurement methodology used to determine information mentioned in maximum, idle, sleep, off mode power as defined in Point P9.1 in the Product IT Eco Declaration:								
	IEC 62623/ IEC EN50564:2011 measurement methodology								
(q) se	sequence of steps for achieving a stable condition with respect to power demand::								
		IEC 62	623 / IE	C EN50564:2011 measurement methodology					
(r) d	escription	of how sleep and/or	r off moo	le was selected or programmed:					
		B	egin me	nu -> Power -> Select sleep or off mode					
	equence of ff mode:	of events required to	reach tl	ne mode where the equipment automatically changes to sleep and/or					
		s	Settings	-> Restore default settings for this plan					
(t) th co	ne duratic ondition w	on of idle state con hich does not excee	dition b ed the ap	efore the computer automatically reaches sleep mode, or another oplicable power demand requirements for sleep mode (in minutes):	30min				
				ser inactivity in which the computer automatically reaches a demand requirement than sleep mode (in minutes):					
(v) th	ne length	of time before the	display	sleep mode is set to activate after user inactivity (in minutes):	10min				
(w) in	formation	on the energy-savi	ng poten	tial of power management functionality:					
				N/A					
(x) u:	ser inform	ation on how to ena	ble the p	power management functionality:					
				Refer to User Guide					
el fc te	lectricity s or electrica est voltage	supply system, — inf al testing: e in V and frequency	ormatior in Hz	test voltage in V and frequency in Hz, — total harmonic distortion of the n and documentation on the instrumentation, set-up and circuits used					
		nic distortion of the and documentation		y supply system instrumentation, set-up and circuits used for electrical testing					
				230V/50Hz,≤2%					
Addition Not	tebook Ba	attery Information:							
Yes		No	n/a	This notebook computer is operated by battery/ies that cannot be accessed	and replaced				
(Battery no	ot user	(Battery user		by a non-professional user.					
replaceable)		replaceable)		The battery[ies] in this product cannot be easily replaced themselves	d by users				
		\boxtimes							
Additional in	formatio	n							

Г