

#### Product environmental attributes - THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an \* are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

Brand *	Lenovo	Logo
Company name *	Lenovo	
Contact information *	Lenovo Global Environmental Affairs Alvin L Carter 1009 Think Place Building 2 / 5J3 Morrisville, North Carolina 27560 alcarter@lenovo.com	lenovo.
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment	t.html
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	PAD			
Commercial name *	Lenovo Miix 2 10 tablet			
Model number *	20337;80DE			
Issue date *	2013-11-28			
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other			
Additional information				

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality (	Control	Requireme	nt met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	$\boxtimes$	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality controsuch as organized by IT-Företagen (see www.itecodeclaration.org).		

Model number *	Lenovo Miix 2 10 tablet		
Issue date *	2013-11-28	Logo	lenovo.

Product	environmental attributes - Legal requirements	Require	men	t met
Item	<u> </u>	Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)			
P1.2*	Products do not contain Asbestos (see legal reference).  Comment: Legal reference has no maximum concentration value.			
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),			
	hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).			
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).			
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)			
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference).  Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm²/week (see legal reference).  Comment: Max limit in legal reference when tested according to EN1811:1998.			
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact): http://www.lenovo.com/social_responsibility/us/en/ThinkGreen_products.html#environment	$\boxtimes$		
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)			
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)			
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medical or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).	$\boxtimes$		
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).	$\boxtimes$		
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).	; <u>X</u>		
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	$\boxtimes$		
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).			
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).			$\boxtimes$
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium an hexavalent chromium by weight of these together.	d 🔀		
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	$\boxtimes$		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montrea Protocol (see legal reference).  Comment: Legal reference has no maximum concentration values.	al 🔀		

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *	Lenovo Miix 2 10 tablet		
Issue date *	2013-11-28	Logo	lenovo.

Product	t environmental attributes - Market requirements - Environmental conscious design Re	quire	ment	met
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.
P6	Treatment information			
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).	$\boxtimes$		
P7	Design			
D= 44	Disassembly, recycling			
P7.1*	Parts that have to be treated separately are easily separable	$\boxtimes$		Щ.
P7.2*	Plastic materials in covers/housing have no surface coating.	$\boxtimes$		
P7.3*	Plastic parts >100g consist of one material or of easily separable materials.	$\boxtimes$		
P7.4*	Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.	$\boxtimes$		
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.	$\boxtimes$		
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	$\overline{X}$		
	Product lifetime			
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	$\square$		П
P7.8*	Upgrading can be done using commonly available tools		Ħ	Ħ
P7.9.	Spare parts are available after end of production for: 5 years			Ħ
P7.10	Service is available after end of production for: 5 years			-
1 7.10	Material and substance requirements			
P7.11*	Product cover/housing material type:			
' ' ' ' ' '	Material type: <i>PC+ABS-FR(40)</i> Material type: Material type:			
P7.12	Electrical cable insulation materials of power cables are PVC free.	$\Box$	X	
P7.13	Electrical cable insulation materials of signal cables are PVC free	Ħ		Ħ
P7.14	All cover/housing plastic parts >25g are free from chlorine and bromine.			-
P7.15	All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See	$\stackrel{\square}{\vdash}$		$^{+}$
1 7.13	Note B2)	Ш		Ш
P7.16	Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:	$\boxtimes$		
D7 17	Marking: FR(40)			
P7.17	Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components):			
	TBBPA (additive) , TBBPA (reactive) , Other; chemical name: , CAS #:	ш	ш	ш
	TEEL TY (COUNTY) , TEEL TY (COUNTY) , CANOT, CHICAMON THAT C. , CT. C. II.			
	Alt. 2			
	Chemical specifications of flame retardants in printed circuit boards (without components) >25g according			
	ISO 1043-4: Brominated Epoxy Resin See P14			
P7.18	Alt. 1			
	Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%:	Ш		Ш
	Comment: No legal limits exist, this is a market requirement.			
	Provide a list of all used flame retardants including MSDS for each flame retardant. The list must contain			
	complete chemical name, CAS number and supplier.			
	1. Chemical name: , CAS #: , Supplier:			
	2. Chemical name: , CAS #: , Supplier:			
	3. Chemical name: , CAS #: , Supplier:	$\boxtimes$		
	Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:		ш	ш
	FR(40)			
P7.19	Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45,	$\square$		
	R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)	<u>~</u>		
P7.20	Of total plastic parts' weight >25g, recycled material content is 0.0%.			
P7.21	Of total plastic parts' weight >25g, biobased material content is 0%.			
P7.22	Light sources are free from mercury		Ш	
P8	Batteries			
P8.1*	Battery chemical composition: Lithium Ion			Щ.
DQ 2	Patteries most the requirements of the following voluntary program/s: US PRPC			

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number * Lenovo Miix 2 10 tablet								
Issue date *	2013-11	013-11-28 Logo <b>lenovo</b> .						
	Product environmental attributes - Market requirements (continued)  Requirement m							
Item						Yes No	n.a.	
•	37 1							
		e following power lev pped w/ WOL Enable		mptions are reporte	ed: <b>See P14</b>			
Energy mode *		Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference / Standa and test method *	ard for energy modes		
Peak (On-max)		N/AW	N/A W	N/A W	Full load			
Category B		1						
Idle State - WOL Er	nabled	N/AW	N/AW	N/A W	Use for Energy Star	r V5 registration(P <sub>idle</sub> )		
Sleep (S3) - WOL E	nabled	N/A W	N/A W	N/AW	Use for Energy Star	r V5 registration(P <sub>sleep</sub> )		
Sleep (S3) - WOL D	Disabled	N/A W	N/A W	N/A W	Reference			
Off (S5) - WOL Ena	bled	N/A W	N/A W	N/A W	Use for Energy Star	r V5 registration(P <sub>off</sub> )		
Off (S5) - WOL Disa	abled	N/AW	N/A W	N/A W	Use for EuP			
EPS No-load		N/A W	N/A W	N/A W				
(External power sup								
charger plugged in the								
outlet but disconnec	ted from							
the product.)		1-14/1- / 1-	1.34/1- /1-	1.34/1- / 1-				
TEC Typical Energy Cons	sumption	kWh/week	kWh/week	kWh/week			$\boxtimes$	
Typical Ellergy Colls	sumption							
ETEC *		N/A kWh/year	N/A kWh/year	N/A kWh/year	$E_{TEC} = (8760/1000)$	$x (P_{off} \times 0.6 + P_{sleep} \times 1.6 + P_{sleep}$		
Annual Energy Consumption			-	•	$0.1 + P_{idle} \times 0.3$ )	•	_	
		P <sub>off</sub> : Off Mode(S5) - 1	WOL Enabled; P <sub>sleep</sub> : S	Sleep Mode(S3) - WOI	L Enabled; P <sub>idle</sub> : Idle Stat	te - WOL Enabled		
Display resolution	: <b>1280*80</b>	Megapixels						
Print Speed	:	Images per minu	te					
Default time to enter	energy sa	ave mode: 25 minute	s					
P9.2* Informat	ion about	the energy save fund	tion is provided with	the product.				
		s the energy requiren					_	
		version: Version 5.0 nergy Star for Extern					$\sqcup$	
P10 Emission	<u> </u>	lergy Star for Exteri	nai Power Supplies	S Engionity Criteria	i version z		Ш	
		- Declared according	to ISO 0206					
P10.1 Mode		Mode description	10 100 3230	Declared	Declared A	A-weighted		
				A-weighted		level $L_{p{\sf Am}}$ (dB)		
				sound power		*	4	
				level $L_{WAd}$ (B)	Operator position	Bystander positions		
					Desktop 🔀	(only if product is not		
					or Desk side	operator attended)		
Idle	,	* HDD: Idle		* 2.7	11	6.3	1 🖂	

\* *NA* 

Other (only if not covered by ECMA-74 with L<sub>pAm</sub> measurement distance The product meets the acoustic noise requirements of the following voluntary program/s:

\* HDD: Operating

Measured according to: ☐ ISO7779 ☐ ECMA-74

Operation

P10.2

Other mode

NA

Model number *	Lenovo Miix 2 10 tablet		
Issue date *	2013-11-28	Logo	lenovo.

Product	environmental attributes - Market requirements (continued)	Require	ment	met		
Item		Yes	No	n.a.		
	Chemical emissions from printing products					
P10.3*	Test performed according to ECMA-328 (ISO/IEC 28360) standard , other specify:			$\boxtimes$		
P10.4	Typical emission rate (print phase) is (mg/h):			$\boxtimes$		
	Dust Ozone Styrene Benzene TVOC					
P10.5	Chemical emission requirements of the following voluntary program/s are met for :			$\boxtimes$		
	Dust Ozone Styrene Benzene TVOC			_		
	Electromagnetic emissions					
P10.6	Computer display meets the requirement for low frequency electromagnetic fields of the following voluntary program/s: MPR-II					
P11	Consumable materials for printing products					
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).			$\boxtimes$		
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN12281.					
P11.3*	2-sided (duplex) printing/copying is an integrated product function.			$\boxtimes$		
P12	Ergonomics for computing products					
P12.1*	The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.	$\boxtimes$				
P12.2*	The physical input device meets the requirements of ISO 9995 and ISO 9241-410.					
P13	Packaging and documentation					
P13.1*	Product packaging material type(s): <i>Corrugated Carton</i> weight (kg): <i>0.3</i> Product packaging material type(s): <i>Polyethylene Cushions</i> weight (kg): <i>0</i> Product packaging material type(s): <i>Others</i> weight (kg): <i>0.25</i>					
P13.2*	Product plastic packaging is free from PVC.	X				
P13.3*	Specify media for user and product documentation (tick box):					
	Electronic , Paper , Other			_		
P13.4*	For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber: 0% (Japan only 70%)					
P14	Additional information (See Note B4)					
	NOTE: Supplier makes no representations, guarantees, assurances or warranties whether express or implier information contained in this document. All information provided by supplier in this document is provided base knowledge available at the time of completion, and supplier shall have no obligation to update such information provided here is approximate and provided for informational purposes only. See a Lenovo Account Represent information.	d on sup n. The in	plier's format			
P7.17	Product does not contain free TBBPA in printed circuit boards(without components)>25g.					
P9	See Energy Star Qualified (insert appropriate Product type; i.e. Desktop, Notebook, etc.) for the latest http://downloads.energystar.gov/bi/qplist/laptops_prod_list.xls (insert appropriate web url)	informat	ion:			

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

# Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19

### **Lenovo ErP Lot3 Information Sheet**

## - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

#### Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	Lenovo Miix 2 10 tablet	Logo
Model Number	20337 , 80DE	_
Issue Date	2014/6/20	lenovo.
Additional information		

(e)       E TEC value (kWh) and capability adjustments applied when all discrete graphics cards (dGfx) are disabled and if the system is tested with switchable graphics mode with UMA driving the display:       19.29         (f)       E TEC value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete graphics cards (dGfx) are enabled:       6.5         (g)       idle state power demand (Watts);       6.5         (h)       sleep mode power demand (Watts);       1.77         (i)       sleep mode with WOL enabled power demand (Watts) (where enabled);       1.77         (j)       off mode power demand (Watts);       0.13         (k)       off mode with WOL enabled power demand (Watts) (where enabled);       0.13         (li)       internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable): N/A 10% 20% 50% 100% Average       Average         (m)       external power supply efficiency (if applicable): 10% 20% 50% 100% Average ; or level: V       Average ; or level: V         (o)       the minimum number of loading cycles that the batteries can withstand (applies only to notebook computers): 500 cycles         (f)       test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: Information and documentation on the instrumentation, set-up and circuits used for electrical testing. Instr. Instrument Instrument Ra	(d)	year of r	nanufacture:					Ava	ailible on product label			
enabled:  (g) idle state power demand (Watts);  (h) sleep mode power demand (Watts);  (i) sleep mode with WOL enabled power demand (Watts) (where enabled);  (j) off mode power demand (Watts);  (j) off mode power demand (Watts);  (k) off mode with WOL enabled power demand (Watts) (where enabled);  (l) internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable): N/A  10% 20% 50% 100% Average  (m) external power supply efficiency (if applicable):  10% 20% 50% 100% Average;  or level: V  (d) the minimum number of loading cycles that the batteries can withstand (applies only to notebook computers):  test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:  test voltage in V and frequency in Hz 230V/50Hz total harmonic distortion of the electricity supply system≤2% Information and documentation on the instrumentation, set-up and circuits used for electrical testing    Instr.   Instrument   Instrument   Range Used   Make and Model **   Code   I.D.   Type   Or ***   Make and Model **   Or ***   Or ***	(e)	are disa	19.29									
(h) sleep mode power demand (Watts);  1.77  (i) sleep mode with WOL enabled power demand (Watts) (where enabled);  1.77  (j) off mode power demand (Watts);  0.13  (k) off mode with WOL enabled power demand (Watts) (where enabled);  0.13  (l) internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable): N/A 10% 20% 50% 100% Average  (m) external power supply efficiency (if applicable): 10% 20% 50% 100% Average;  or level: V  (o) the minimum number of loading cycles that the batteries can withstand (applies only to notebook computers): 500 cycles  (f) test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:  test voltage in V and frequency in Hz 230V/50Hz total harmonic distortion of the electricity supply system≤2% Information and documentation on the instrumentation, set-up and circuits used for electrical testing  Instr. Instrument Instrument Range Used Make and Model **  Code I.D. Type Or ***	(f)											
(i) sleep mode with WOL enabled power demand (Watts) (where enabled);  (j) off mode power demand (Watts);  (k) off mode with WOL enabled power demand (Watts) (where enabled);  (l) internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable): N/A 10% 20% 50% 100% Average  (m) external power supply efficiency (if applicable): 10% 20% 50% 100% Average;  or level: V  (o) the minimum number of loading cycles that the batteries can withstand (applies only to notebook computers): 500 cycles  (f) test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:    test voltage in V and frequency in Hz 230V/50Hz total harmonic distortion of the electricity supply system ≤2% Information and documentation on the instrumentation, set-up and circuits used for electrical testing    Instr.   Instrument   Instrument   Range Used   Make and Model **   Code   I.D.   Type   Or ****	(g)	idle state	e power demand	(Watts);					6.5			
(i) off mode power demand (Watts);  (ii) off mode with WOL enabled power demand (Watts) (where enabled);  (i) internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable): N/A  10% 20% 50% 100% Average  (m) external power supply efficiency (if applicable):  10% 20% 50% 100% Average ;  or level: V  (o) the minimum number of loading cycles that the batteries can withstand (applies only to notebook computers):  (f) test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:    test voltage in V and frequency in Hz 230V/50Hz total harmonic distortion of the electricity supply system≤2% Information and documentation on the instrumentation, set-up and circuits used for electrical testing    Instr.   Instrument   Instrument   Range Used   Make and Model **	(h)	sleep me	1.77									
(k) off mode with WOL enabled power demand (Watts) (where enabled);  (l) internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable): N/A  10% 20% 50% 100% Average  (m) external power supply efficiency (if applicable):  10% 20% 50% 100% Average ;  or level: V  (o) the minimum number of loading cycles that the batteries can withstand (applies only to notebook computers):  (f) test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:    test voltage in V and frequency in Hz 230V/50Hz total harmonic distortion of the electricity supply system≤2% Information and documentation on the instrumentation, set-up and circuits used for electrical testing    Instr.   Instrument   Instrument   Range Used   Make and Model **	(i)	sleep m	1.77									
(i) internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable): N/A  10% 20% 50% 100% Average  (m) external power supply efficiency (if applicable): 10% 20% 50% 100% Average ; or level: V  (o) the minimum number of loading cycles that the batteries can withstand (applies only to notebook computers):  (f) test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:  test voltage in V and frequency in Hz 230V/50Hz total harmonic distortion of the electricity supply system≤2% Information and documentation on the instrumentation, set-up and circuits used for electrical testing  Instr. Instrument Instrument Range Used  Make and Model **  Code I.D. Type Or ****	(j)	off mode	0.13									
(m) external power supply efficiency (if applicable):  10% 20% 50% 100% Average ;  or level: V  (o) the minimum number of loading cycles that the batteries can withstand (applies only to notebook computers): 500 cycles  (f) test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:  test voltage in V and frequency in Hz 230V/50Hz total harmonic distortion of the electricity supply system≤2% Information and documentation on the instrumentation, set-up and circuits used for electrical testing  Instr. Instrument Instrument Range Used Make and Model **  Code I.D. Type Or ***	(k)	off mode with WOL enabled power demand (Watts) (where enabled);  0.13										
(m) external power supply efficiency (if applicable):  10% 20% 50% 100% Average ;  or level: V  (o) the minimum number of loading cycles that the batteries can withstand (applies only to notebook computers): 500 cycles  (f) test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:  test voltage in V and frequency in Hz 230V/50Hz total harmonic distortion of the electricity supply system≤2% Information and documentation on the instrumentation, set-up and circuits used for electrical testing  Instr. Instrument Instrument Range Used Make and Model **  Code I.D. Type Or ***	(l)	internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable): N/A										
10% 20% 50% 100% Average ; or level: V  (o) the minimum number of loading cycles that the batteries can withstand (applies only to notebook computers): 500 cycles  (f) test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:  test voltage in V and frequency in Hz 230V/50Hz total harmonic distortion of the electricity supply system≤2% Information and documentation on the instrumentation, set-up and circuits used for electrical testing  Instr. Instrument Instrument Range Used Make and Model ** Code I.D. Type Or ****		10%	20%	50%	100%	Average						
or level: V  the minimum number of loading cycles that the batteries can withstand (applies only to notebook computers):  500 cycles  (f) test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:  test voltage in V and frequency in Hz 230V/50Hz total harmonic distortion of the electricity supply system≤2% Information and documentation on the instrumentation, set-up and circuits used for electrical testing  Instr. Instrument Instrument Range Used Make and Model **  Code I.D. Type Or ***	(m)	external	external power supply efficiency (if applicable):									
(o) the minimum number of loading cycles that the batteries can withstand (applies only to notebook computers):  500 cycles  (f) test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:  test voltage in V and frequency in Hz 230V/50Hz total harmonic distortion of the electricity supply system≤2% Information and documentation on the instrumentation, set-up and circuits used for electrical testing  Instr. Instrument Instrument Range Used  Code I.D. Type Or ***  Make and Model **		10%	20%	50%	100%	Average ;						
(f) test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:  test voltage in V and frequency in Hz 230V/50Hz total harmonic distortion of the electricity supply system≤2% Information and documentation on the instrumentation, set-up and circuits used for electrical testing    Instr.   Instrument   Instrument   Range Used   Make and Model **   Code   I.D.   Type   Or ***												
the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:  test voltage in V and frequency in Hz 230V/50Hz total harmonic distortion of the electricity supply system≤2% Information and documentation on the instrumentation, set-up and circuits used for electrical testing  Instr. Instrument Instrument Range Used  Code I.D. Type Or ***  Make and Model **	(o)	the mini	mum number of l	loading cycles tha	t the batter	ies can withstand (appl	lies only	to notebook compute	ers): 500 cycles			
total harmonic distortion of the electricity supply system≤2% Information and documentation on the instrumentation, set-up and circuits used for electrical testing  Instr. Instrument Instrument Range Used  Code I.D. Type Or ***  Make and Model **	(f)	the elect	tricity supply syst	tem, — informatio								
Instr. Instrument Instrument Range Used  Code I.D. Type Or ***  Make and Model **		total har										
Code I.D. Type Or ***												
1 980800014 CHROMA 100-300VAC 50-60Hz 400Hz, 5A, 500 , 61502		Code	I.D.	Туре		Or ***						
		1	980800014	CHROMA	100-300V	AC 50-60Hz 400Hz, 5/	A, 500 ,	61502				

	2	990800	321 YOKOGAWA	600V, 10A, 5KW	WT 210							
	3	990105	548 ISUZU	20-28 degree C 30-80%	TH-27R							
	4	710Q0	3R CASIO	Full Range	HS-3V							
	5	990105	5627 TECPEL	0~20( m/sec)	AVM-714							
(p-1)	the mefficie		methodology used to	determine information mentioned	in points (I) - internal PSI	J						
( 0)												
(p-2)	efficie		methodology used to	determine information mentioned in	n points (m) – external PSt	J						
(p-3)	the measurement methodology used to determine information mentioned in points (o) – loadingcycles batteries:  Charge battery with standard charge method and discharge battery with 0.5Cmin discharging current until battery voltage reaches 3.0V											
(p-4)			methodology used to de n Point P9.1 in the Prod	etermine information mentioned in ma luct IT Eco Declaration:	ximum, idle, sleep, off mode							
				EN62623								
(q)	seque	ence of steps	for achieving a stable c	condition with respect to power deman	nd::							
			Power on -	> Wait 5 minutes ->Stable condition	1							
(r)	descri	ption of how	sleep and/or off mode v	vas selected or programmed:								
			Begin menu	-> Power -> Select sleep or off mod	de							
(s)	seque off mo		s required to reach the I	mode where the equipment automatic	cally changes to sleep and/or							
			Settings-> I	Restore default settings for this pla	n							
(t)				re the computer automatically reac cable power demand requirements for		20 minutes						
(u)		•	•	inactivity in which the computer at mand requirement than sleep mode (i	-	N/A						
(v)	the le	ngth of time	before the display sle	eep mode is set to activate after use	r inactivity (in minutes):	10 minutes						
(w)	inform	ation on the	energy-saving potential	of power management functionality:								
				N/A								
(x)	user ii	nformation or	n how to enable the pow	ver management functionality:								
				Refer to User Guide								
(z)	the ele		oly system, — informatio	t voltage in V and frequency in Hz, — on and documentation on the instrume								
				230V/50Hz								
Addition	n Notebo	ok Battery Ir	nformation:									
Addition Yes	n Noteboo			s operated by battery/ies that cannot	be accessed and replaced b	y a non-professional						
		n/a Th	is notebook computer is er.	s operated by battery/ies that cannot his product cannot be easily								