

Product environmental attributes - THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

Brand *	Lenovo	Logo
Company name *	Lenovo	
Contact information *	Lenovo Global Environmental Affairs Alvin L Carter 1009 Think Place Building 2 / 5J3 Morrisville, North Carolina 27560 alcarter@lenovo.com	lenovo.
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment	t.html
Additional information		

	The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.						
Type of product *	Personal Computer						
Commercial name *	ThinkCentre M83 SFF						
Model number *	SFF: 10AH, 10AJ, 10AM, 10AN						
Issue date *	2014-05-13						
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other						
Additional information	Only 10AH, 10AJ is Energy Star 6.0 Qualified and EPEAT Silver; GREENGUARD Certification						

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Control	Requireme	nt met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).		

Model number *	ThinkCentre M83 SFF	MTs: 10AH, 10AJ, 10	AM, 10AN
Issue date *	2014-05-13	Logo	lenovo

Product	environmental attributes - Legal requirements	Require	men	met
Item	<u> </u>	Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)			
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.	\boxtimes		
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),			
	hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).	\boxtimes		
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).			
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)			\boxtimes
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as			\boxtimes
	pentachlorophenol and derivatives (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm²/week (see legal reference).			
P1.10*	Comment: Max limit in legal reference when tested according to EN1811:1998. REACH Article 33 information about substances in articles is available at (add URL or mail contact):			
F 1.10	http://www.lenovo.com/social_responsibility/us/en/ThinkGreen_products.html#environment		Ш	Ш
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)			
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or			
P2.3*	accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference) Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medical			
D2	or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3.1*	Safety, EMC connection to the telephone network and labeling The product complies with legally required safety standards as specified (see legal reference).		$\overline{}$	
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal	\boxtimes		
P3.3*	reference). If product is intended for connection to a public telecom network or contains a radio transmitter, it complies		$\overline{\Box}$	
P3.4*	with legally required standards for radio and telecommunication devices (see legal reference). The product is labeled to show conformance with applicable legal requirements (see legal reference).		$\overline{}$	
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see			
P4.2*	legal reference and Note B1). If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).			\square
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these			
P5	requirements is available (see legal reference). Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and hexavalent chromium by weight of these together.	d 🔀		
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).			
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montrea Protocol (see legal reference).	ıl 🔀		
	Comment: Legal reference has no maximum concentration values.			

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *	ThinkCentre M83 SFF	MTs: 10AH, 10AJ, 10A	AM, 10AN
Issue date *	2014-05-13	Logo	lenovo.

Product	t environmental attributes - Market requirements - Environmental conscious design Re	quire	men	t met
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.
P6	Treatment information			
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).	\boxtimes		
P7	Design Disassembly, recycling			
P7.1*	Parts that have to be treated separately are easily separable	\square	$\overline{}$	\Box
P7.2*	Plastic materials in covers/housing have no surface coating.			
P7.3*	Plastic parts >100g consist of one material or of easily separable materials.			-
P7.4*	, , ,		-	-
	Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.			<u> </u>
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.			
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).			
D= =+	Product lifetime			
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives			
P7.8*	Upgrading can be done using commonly available tools	\boxtimes		
P7.9.	Spare parts are available after end of production for: 5 years			
P7.10	Service is available after end of production for: 5 years			
	Material and substance requirements			
P7.11*	Product cover/housing material type:			
	Material type: PC/ABS Material type: Steel			
P7.12	Electrical cable insulation materials of power cables are PVC free.		\boxtimes	
P7.13	Electrical cable insulation materials of signal cables are PVC free		\boxtimes	
P7.14	All cover/housing plastic parts >25g are free from chlorine and bromine.	\boxtimes		
P7.15	All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2)			
P7.16	Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking:			
P7.17	Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) , TBBPA (reactive) , Other; chemical name: , CAS #:			
	Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: <i>Brominated Epoxy Resin See P14</i>			
P7.18	Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%:			
	Comment: No legal limits exist, this is a market requirement. Provide a list of all used flame retardants including MSDS for each flame retardant. The list must contain complete chemical name, CAS number and supplier. 1. Chemical name: , CAS #: , Supplier: 2. Chemical name: , CAS #: , Supplier:			
	3. Chemical name: , CAS #: , Supplier: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:			
P7.19	Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)			
P7.20	Of total plastic parts' weight >25g, recycled material content is SFF: 41.75%			
P7.21	Of total plastic parts' weight >25g, biobased material content is 0 %.			
P7.22	Light sources are free from mercury			X
P8	Batteries			
P8.1*	Battery chemical composition:			
P8.2	Batteries meet the requirements of the following voluntary program/s:			Ħ

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	ThinkCentre M83 SFF	MTs: 10AH, 10AJ, 10	AM, 10AN
Issue date *	2014-05-13	Logo	lenovo

Product environmental attrib	outes - Market r	equirements ((continued)	Requirement Yes No	
P9 Energy consumption				1 es INO	n.a.
9.1 For the product the fol	lowing power level		sumptions are rep	ported: See P14	
The product is shipped			.12		
	ower level at 1 100 V AC	Power level a 115 V AC	Power level 230 V AC	at Reference / Standard for energy modes and test method *	Ш
Category 0					
Short Idle State - WOL Enabled	W	W	W	Use for ENERGY STAR V6 registration (P _{idle})	
Long Idle State - WOL Enabled	W	W	W	Use for ENERGY STAR V6 registration (Pidle)	
Sleep (S3) - WOL Enabled	W	W	W	Use for ENERGY STAR V6 registration(P _{sleep})	
Sleep (S3) - WOL Disabled	W	W	W	Reference	
Off (S5) - WOL Enabled	W	W	W	Use for ENERGY STAR V6 registration(Poff)	
Off (S5) - WOL Disabled	W	W	W	Use for EuP	
Category I1					
Short Idle State - WOL Enabled	23.54 W	23.60 W	23.56 W	Use for Energy Star V6.0 registration(P _{ShortIdle})	
Long Idle State - WOL Enabled	21.95 W	22.31 W	22.07 W	Use for Energy Star V6.0 registration(P _{Longldle})	
Sleep (S3) - WOL Enabled	0.82 W	0.84 W	1.05 W	Use for Energy Star V6.0 registration (P _{sleep})	
Sleep (S3) - WOL Disabled	0.82 W	<i>0.84</i> W	1.05 W	Reference	
Off (S5) - WOL Enabled	<i>0.55</i> W	<i>0.56</i> W	0.76 W	Use for Energy Star V6.0 registration (Poff)	
Off (S5) - WOL Disabled	<i>0.38</i> W	<i>0.38</i> W	<i>0.38</i> W	Use for EuP	
Category I2					
Short Idle State - WOL Enabled	23.91 W	23.52 W	23.64 W	Use for Energy Star V6.0 registration(P _{ShortIdle})	
Long Idle State - WOL Enabled	22.59 W	22.21 W	22.46 W	Use for Energy Star V6.0 registration(P _{Longldle})	
Sleep (S3) - WOL Enabled	0.82 W	<i>0.84</i> W	1.05 W	Use for Energy Star V6.0 registration (P _{sleep})	
Sleep (S3) - WOL Disabled	0.82 W	0.84 W	1.05 W	Reference	
Off (S5) - WOL Enabled	0.55 W	<i>0.56</i> W	0.76 W	Use for Energy Star V6.0 registration (Poff)	
Off (S5) - WOL Disabled	0.38 W	<i>0.38</i> W	0.38 W	Use for EuP	
Category I3					
Short Idle State - WOL Enabled	23.90 W	<i>23.63</i> W	23.53 W	Use for Energy Star V6.0 registration(P _{ShortIdle})	
Long Idle State - WOL Enabled	22.38 W	22.32 W	22.31 W	Use for Energy Star V6.0 registration(P _{Longldle})	
Sleep (S3) - WOL Enabled	0.82 W	0.84 W	1.05 W	Use for Energy Star V6.0 registration (P _{sleep})	
Sleep (S3) - WOL Disabled	0.82 W	0.84 W	1.05 W	Reference	
Off (S5) - WOL Enabled	0.55 W	<i>0.56</i> W	0.76 W	Use for Energy Star V6.0 registration (Poff)	
Off (S5) - WOL Disabled	0.38 W	<i>0.38</i> W	0.38 W	Use for EuP	
Category D1					
Short Idle State - WOL Enabled	31.54 W	31.10 W	31.28 W	Use for Energy Star V6.0 registration(P _{ShortIdle})	
Long Idle State - WOL Enabled	30.41 W	30.22 W	29.88 W	Use for Energy Star V6.0 registration(P _{Longldle})	
Sleep (S3) - WOL Enabled	0.82 W	0.84 W	1.05 W	Use for Energy Star V6.0 registration (P _{sleep})	
Sleep (S3) - WOL Disabled	0.82 W	0.84 W	1.05 W	Reference	
Off (S5) - WOL Enabled	0.55 W	<i>0.56</i> W	0.76 W	Use for Energy Star V6.0 registration (Poff)	
Off (S5) - WOL Disabled	<i>0.38</i> W	<i>0.38</i> W	0.38 W	Use for EuP	
Category D2					
Short Idle State - WOL Enabled	31.59 W	31.58 W	31.83 W	Use for Energy Star V6.0 registration(P _{ShortIdle})	
Long Idle State - WOL Enabled	30.48 W	<i>30.38</i> W	30.20 W	Use for Energy Star V6.0 registration(P _{Longldle})	
Sleep (S3) - WOL Enabled	0.82 W	0.84 W	1.05 W	Use for Energy Star V6.0 registration (P _{sleep})	
Sleep (S3) - WOL Disabled	0.82 W	0.84 W	1.05 W	Reference	
Off (S5) - WOL Enabled	0.55 W	<i>0.56</i> W	0.76 W	Use for Energy Star V6.0 registration (Poff)	
Off (S5) - WOL Disabled	0.38 W	0.38 W	<i>0.38</i> W	Use for EuP	

TEC Typical Energy Consumption ETEC * Typical Energy Consumption ETEC * Cat II: 103.54; Cat II: 104.25; Cat II: 104.69; Cat II: 104.69; Cat II: 104.69; Cat II: 103.54; Cat II: 104.69; Cat II: 104.69; Cat II: 103.64; Cat II: 104.69; Cat	plugged i	load I power supply / cha in the wall outlet but ected from the produ		W	W	
Annual Energy Consumption Cat 12: 105.21; Cat 13: 105.21; Cat 13: 105.31; Cat 13: 105.41; Cat 13: 105.31; Cat 13: 105.41; Cat 13: 105.43; Cat 13: 105.44; Cat 13: 105.44; Cat 12: 105.45; Cat 13: 105.43; Cat 13: 105.44; Cat 12: 105.45; Cat 13: 105.43; Cat 13: 105.44; Cat 12: 105.45; Cat 13: 105.45; Cat	_	Energy Consumption		kWh/week	kWh/week	
Display resolution: Megapixels Print Speed: Images per minute Default time to enter energy save mode: 30 minutes P9.2* Information about the energy save function is provided with the product. P9.3* The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version: Version 6.0 dated September 10, 2013 Product category: I1,I2,I3,D1,D2 Others specify: P10 Emissions Noise emission – Declared according to ISO 9296 P10.1 Mode Mode description Declared A-weighted sound power level L _{WAd} (B) Operator position Operator position Operator position Operator attended) Idle HDD: Idle 3.3.3 Operation HDD: Operating 3.5 26 Other mode Measured according to: SO7779 ECMA-74 Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m)			Cat I2: 105.52; Cat I3: 105.21; CatD1:139.19; CatD2:139.43;	Cat I2: 103.87; Cat I3: 104.35; CatD1:137.64; CatD2:139.31;	Cat I2:105.45; Cat I3:104.91; CatD1:138.62; CatD2:140.72;	E _{TEC} = (8760/1000) x (P _{off} x 0.45 + P _{sleep} x 0.05 + P _{shortIdle} x 0.35 + P _{LongIdle} x 0.15)
Print Speed : Images per minute Default time to enter energy save mode: 30 minutes P9.2* Information about the energy save function is provided with the product. P9.3* The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version: Version 6.0 dated September 10, 2013 Product category: I1,I2,I3,D1,D2 Others specify: P10 Emissions Noise emission — Declared according to ISO 9296 P10.1 Mode Mode description P10.1 Mode Mode description Noise emission — Declared according to ISO 9296 P10.1 Idle * HDD: Idle * 3.3 Desktop Or Desk side Operator attended) Operator operator attended) Operation * HDD: Operating * 3.5 26 Other mode Measured according to: Siso7779 ECMA-74 Other (only if not covered by ECMA-74 with Lpam measurement distance m)			P _{off} : Off Mode(S5)	- WOL Enabled;	P _{sleep} : Sleep Mode(S	3) - WOL Enabled; P _{idle} : Idle State - WOL Enabled
Default time to enter energy save mode: 30 minutes P9.2* Information about the energy save function is provided with the product. P9.3* The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version: Version 6.0 dated September 10, 2013 Product category: I1,I2,I3,D1,D2 Others specify: P10 Emissions Noise emission – Declared according to ISO 9296 P10.1 Mode Mode description Declared A-weighted sound power level L _{WAd} (B) Operator position Bystander positions Desktop Or Desk side Operator attended) Operator position Operator attended) Operator operator attended Operator operator attended Operator operator attended Other mode Measured according to: ISO7779 ECMA-74 Other (only if not covered by ECMA-74 with L _{pam} measurement distance m)	Display r	resolution : I	Megapixels			
P9.2* Information about the energy save function is provided with the product. P9.3* The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version: Version 6.0 dated September 10, 2013 Product category: 11,12,13,D1,D2 Others specify: P10 Emissions Noise emission – Declared according to ISO 9296 P10.1 Mode Mode description Declared A-weighted sound power level L _{WAd} (B) Operator position Desktop Operator attended) Idle *HDD: Idle *3.3 24 Operation *HDD: Operating 3.5 26 Other mode Measured according to: SISO7779 ECMA-74 Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m)	Print Spe	eed :	Images per minute)		
P9.3* The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version: Version 6.0 dated September 10, 2013 Product category: I1,I2,I3,D1,D2 Others specify: P10.1 Mode Mode description Declared A-weighted sound power level L _{WAd} (B) Idle *HDD: Idle *3.3 Operation *HDD: Operating Other mode Measured according to: SO7779 ECMA-74 Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m)	Default ti	ime to enter energy	save mode: 30 minutes			
ENERGY STAR® version: Version 6.0 dated September 10, 2013 Product category: I1,I2,I3,D1,D2 Others specify: P10 Emissions Noise emission – Declared according to ISO 9296 P10.1 Mode Mode description Declared A-weighted sound prower level L _{WAd} (B) Operator position Sustander positions Operator position Operator attended) Idle *HDD: Idle *3.3 24 Operation *HDD: Operating 3.5 26 Other mode Measured according to: SO7779 ECMA-74 Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m)	P9.2*	Information about the energy save function is provided with the product.				
Noise emission – Declared according to ISO 9296 P10.1 Mode Mode description Declared A-weighted sound pressure level L _{pAm} (dB) Operator position Desktop ○ or Desk side ○ or Desk side ○ or Desk side ○ Operator attended) Operation HDD: Operating Other mode Measured according to: ○ ISO7779 ○ ECMA-74 Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m)	P9.3*	ENERGY STAR				
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	P10	Emissions				
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$		Noise emission		ISO 9296		
Idle * HDD: Idle * 3.3 24 Operation * HDD: Operating *3.5 Other mode Measured according to: Sorry Sorry ECMA-74 Other (only if not covered by ECMA-74 with LpAm measurement distance m) Compared to the covered by ECMA-74 with LpAm measurement distance m)	P10.1	Mode	Mode description		A-weighted sound power	sound pressure level $L_{p \text{Am}}$ (dB) Operator position \square Desktop \square or Posk side \square (only if product is not
Other mode Measured according to: SO7779 ECMA-74 Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m)		Idle	* HDD: Idle		* 3.3	
Measured according to: SO7779 ECMA-74 Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m)		Operation	* HDD: Operating		*3.5	26
Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m)		Other mode				+
P10.2 The product meets the acoustic noise requirements of the following voluntary program/s:	P10.2		Other	(only if not cov		,

Model number *	ThinkCentre M83 SFF	MTs: 10AH, 10AJ, 10	AM, 10AN
Issue date *	2014-05-13	Logo	lenovo.

Product	environmental attributes - Market requirements (continued)	Require	ment	met
Item	•	Yes	No	n.a.
	Chemical emissions from printing products			
P10.3*	Test performed according to ECMA-328 (ISO/IEC 28360) standard, other specify:			\boxtimes
P10.4	Typical emission rate (print phase) is (mg/h):			\boxtimes
	Dust Ozone Styrene Benzene TVOC			
P10.5	Chemical emission requirements of the following voluntary program/s are met for :			\boxtimes
	Dust Ozone Styrene Benzene TVOC			
	Electromagnetic emissions			
P10.6	Computer display meets the requirement for low frequency electromagnetic fields of the following voluntary program/s:			
P11	Consumable materials for printing products			
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).			\boxtimes
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN12281.			
P11.3*	2-sided (duplex) printing/copying is an integrated product function.			\boxtimes
P12	Ergonomics for computing products			
P12.1*	The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.	\boxtimes		
P12.2*	The physical input device meets the requirements of ISO 9995 and ISO 9241-410.	\boxtimes		
P13	Packaging and documentation			
P13.1*	Product packaging material type(s): Corrugated paper weight (kg): 1.125			
	Product packaging material type(s): Fabricated PE weight (kg): 0.165 Product packaging material type(s): HDPE weight (kg):0.016			
P13.2*	Product plastic packaging is free from PVC.	\square		
P13.3*	Specify media for user and product documentation (tick box):			H
1 10.0	Electronic , Paper , Other			ш
P13.4*	For paper user and product documentation, please specify contained percentage of post-consumer recycled			
	fiber: 0% (Japan only 70%)			ш
P14	Additional information (See Note B4)			
	NOTE: Supplier makes no representations, guarantees, assurances or warranties whether express or implie			
	information contained in this document. All information provided by supplier in this document is provided base			
	knowledge available at the time of completion, and supplier shall have no obligation to update such informatic provided here is approximate and provided for informational purposes only. See a Lenovo Account Represent			tion
	information.	alive for i	11016	
P7.17	Product does not contain free TBBPA in printed circuit boards(without components)>25g.			
P9	See Energy Star Qualified (insert appropriate Product type; i.e. Desktop, Notebook, etc.) for the latest	informat	ion:	
	http://downloads.energystar.gov/bi/qplist/laptops_prod_list.xls (insert appropriate web url)			

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19

Lenovo ErP Lot3 Information Sheet

- PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	ThinkCentre M83 SFF	Logo	
Model Number	10AH, 10AJ, 10AM, 10AN	_	
Issue Date	2014-05-13	lenovo.	
Additional information	Only 10AH, 10AJ is Erp Lot3 Qualified, which is equipped with ES PSU.		

(d)	Year of manufacture:	Availible on product label				
(e)	E TEC value (kWh) and capability adjustments applied when all discrete graphics cards (are disabled and if the system is tested with switchable graphics mode with UMA driving th display:					
	Cat. B 110.90 Cat. C 90.48 Cat. D 113.35					
(f)	E TEC value (kWh) and capability adjustments applied when all discrete graphics cards (are enabled: Cat. B 119.21 Cat. C 115.92	(dGfx)				
	Cat. D 119.38					
(g)	idle state power demand (Watts);	32.59				
(h)	sleep mode power demand (Watts);	1.82				
(i)	sleep mode with WOL enabled power demand (Watts) (where enabled);	1.83				
(j)	off mode power demand (Watts);	0.91				
(k)	off mode with WOL enabled power demand (Watts) (where enabled);	0.92				
(I)	Internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable): 10% 79.37% 20% 84.71% 50% 86.83% 100% 83.69%					
(m)	External power supply efficiency (if applicable):	N/A				
	10% 20% 50% 100% Average ;					
(o)	The minimum number of loading cycles that the batteries can withstand (applies only to notebook computers): N/A					
(f)	Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmon the electricity supply system, — information and documentation on the instrumentation, set-used for electrical testing: Test voltage in V and frequency in Hz 230V/50Hz Total harmonic distortion of the electricity supply system 2%					
	Information and documentation on the instrumentation, set-up and circuits used for electrical					
	Type Or *** Make and Model *					
	AC Power Source 1~280VAC;1~550HZ;1000V NF;EC1000S; SN:915	2124				

				lical ili tilla bioduct o		
			user. The battery	lies) in this product c	annot be easily replaced by users ther	nselves
Yes	No Noteb	n/a		computer is operated by bat	tery/ies that cannot be accessed and replaced by	a non-professional
- ئد:لملم ۸	n Natal	ook Dette	y Information	Refer to User (Guide	
(x)	Usei	r informatio	n on how to ena	ble the power management to		
				N/A		
(w)	Infor	mation on	the energy-savir	ng potential of power manage	ement functionality:	
(v)	The	iength of t	ume before the	display sleep mode is set t	to activate after user inactivity (in minutes):	15 minutes
(u)	The length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes): 45 minutes					
(t)	The duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes): 30 minutes					30 minutes
	OII II		l Panel->Power	Options-> Change Settings	s-> Restore default settings for this plan	
(s)		uence of ev	vents required to	reach the mode where the e	equipment automatically changes to sleep and/or	
(')	D03	o. 1011 01 1	·	egin menu -> Power -> Sele	G	
(r)	Dee	cription of h		Power on -> Wait 5 minutes r off mode was selected or pi		
(q)	Seq	uence of st	•	g a stable condition with resp	•	
				IEC 62301	1	
(p-4)	The pow	measurem er as define	ent methodology ed in Point P9.1	y used to determine informati in the Product IT Eco Declar	ion mentioned in maximum, idle, sleep, off mode ation:	
	batteries: N/A					
(p-3)	The	measurem	nent methodolog	N/A gy used to determine inform	mation mentioned in points (o) - loadingcycles	
(p-2)		ne measurement methodology used to determine information mentioned in points (m) – external PSU ficiency:				
	enic	iency:		80 PLUS® Pro	gram	
(p-1)		measuren	•		rmation mentioned in points (I) – internal PSU	
			nemometer easuring	0~20m/s,-20~70°C 1°:1-300cd/ m²	Testo;425;SN:02591883 Konica Minolta:LS-110;	
		Hygrothe	rmograph	15~35℃/15~90%	testo; 608-H1,SN:1034895602	
		Power	Meter	0~600V;0~20A	YOKOGAWA;WT210;SN:91M94456 0	
		Digital	Watch	Full range	CASIO; HS-70W; SN:208Q08R	
			144	A.	0.1010 110	