



ECMA/TC38-TG3/2015/026 (Rev. 1 – 15 April 2017)

Annex B2 - Product environmental attributes Desktop/All-in-One Computers

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lenovo	Logo	
Company name *	Lenovo		
Contact information *	Lenovo Global Environmental Affairs		Lenovo
e-mail address	Alvin L Carter		
	alcarter@lenovo.com		
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment	.html	
Additional information	The latest version of this document can be found at:		
	http://www.lenovo.com/ecodeclaration		

The company declares (based on product specification or test results based obtained from sample testing), that the product
conforms to the statemen	nts given in this declaration.
Type of product *	All-in-One
Commercial name *	ThinkCentre M920z AIO
Model number *	10\$6, 10\$7, 10\$75, 10\$76
Issue date *	2018.05.30
Intended market *	Global Europe Asia, Pacific & Japan Americas Other
Additional information	TCO;Energy Star 7;Greenguard;Eye Comfort;EPEAT Gold;Low blue Light

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products

Model nu	ımber *	10\$6, 10\$7, 10\$75, 10\$76	Logo	Land		
Issue da	te *	2018.05.30		Lend	JVC	тм
Product	t environ	mental attributes - Legal requirements		Require	ment	met
Item				Yes	No	n.a.
P1	Hazardo	ous substances and preparations				
P1.1*	Products	s do comply with current European RoHS Directive. (See legal reference and NOTE	B1)			
P1.2*		s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value.				
P1.3*	hydrobro trichloroe	do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), profiluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachethane, methyl bromide (see legal reference). Comment: Legal reference has no mation values.				
P1.4*		do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychol (PCT) in preparations (see legal reference).	lorinated			
P1.5*		do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carl ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).	oon atoms in t	the 🔀		
P1.6*	Parts wit	th direct and prolonged skin contact do not release nickel in concentrations above 0 al reference). nt: Max limit in legal reference when tested according to EN1811:2011-5.	,5 μg/cm²/we	ek 🔀		
P1.7*	REACH	Article 33 information about substances in articles is available at (add URL or mail www3.lenovo.com/us/en/Lenovo-REACH-SVHC-Disclosure	contact):			
P2	Batterie	s				
P2.1*		educt contains a battery or an accumulator, the battery/accumulator is labeled with t Information on proper disposal is provided in user manual. (See legal reference)	he disposal			
P2.2*	Batteries reference	s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadme)	nium. (See leg	jal 🔀		
P2.3*	Batteries	and accumulators are readily removable. (See legal reference)		\boxtimes		
P3	Conforn	nity verification & Eco design (ErP)				
P3.1*	The prod	duct is CE-marked to show conformance with applicable legal requirements (see legal requirements).	gal reference)			

https://www3.lenovo.com/us/en/social_responsibility/EU_DoC_desktops

Comment: Legal reference has no maximum concentration values.

Information for recyclers/treatment facilities is available (see legal reference).

hexavalent chromium by weight of these together.

The product complies with the Eco design requirements for energy-related products,

available at (add URL):

given in item P15 or added to this document,

Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium and

The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s)

The product packaging material is free from ozone depleting substances as specified in the Montreal

P3.2*

P5

P5.1*

P5.2*

P5.3*

P6 P6.1*

(see legal reference). Required information is;

Product packaging

used (see legal reference).

Treatment information

Protocol (see legal reference).

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number *	10\$6, 10\$7, 10\$75, 10\$76	Logo	Lanava
Issue date *	2018.05.30		LEI IOVO"

Product	environmental attributes - Market requirements (See General NOTE GN below)			
		Require	ment	met
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.
P7	Design, Disassembly, recycling			
P7.1*	Parts that have to be treated separately are easily separable	\boxtimes		
P7.2*	Plastic materials in covers/housing have no surface coating.		\boxtimes	
P7.3*	Plastic parts > 100 g consist of one material or of easily separable materials.	\boxtimes		
P7.4*	Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.	\boxtimes		
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.	\boxtimes		
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	\boxtimes		
	Product lifetime			
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	\boxtimes		
P7.8*	Upgrading can be done using commonly available tools	\boxtimes		
P7.9	Spare parts are available after end of production for: 5 years			
P7.10	Service is available after end of production for: 5 years			
	Material and substance requirements			
P7.11*	Product cover/housing material type (e.g. plastics, metal, aluminum):			
	Material type: ABS Material type: PC Material type: SGCC			
P7.12	Insulation materials of external electrical cables are PVC free.			
P7.13	Insulation materials of internal electrical cables are PVC free.			
P7.14	External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content.	1		
P7.15	Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2)	′		
P7.16	Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking:			
P7.17	Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: Brominated Epoxy Resin, CAS #: 79-94-7; 26265-08-7			
	<u>Alt. 2:</u> Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4:			
P7.18	Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: "			
	Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:			
P7.19	In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been		Ħ	
	assigned the following Risk phrases; and Hazard statements:			
	The source(s) for these classifications is/are found at (add URL(s)): , (See note B5)			
P7.20*	Postconsumer recycled plastic material content is used in the product (See Note B6):			
	If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 24%. or b) The weight of recycled material is 509 g.			

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model number *	10\$6, 10\$7, 10\$5, 10\$6	Logo	Lanava
Issue date *	2018.05.30		LEI IOVO.

Product e	environmental at	tributes - Market re	equirements (conti	nued)	Requireme	ent met
Item			,	,	Yes No	
	Material and subs	tance requirements	(continued)			
P7.21*	Biobased plastic m	aterial content is used	in the product (See No	OTE B7):		
	If YES; at least one	e of the two alternative	s below shall be answe	ered;		
			, the biobased plastic	material content (calcu	lated as a percentage	
	of total plastic	by weight) is 0%.				
		the biobased plastic n	naterial is <i>0</i> g.			
P7.22*			less than 0,1 mg/lamp.		. 🛛 🗀	
P8	Batteries	specify: Number of lan	nps: and maximi	um mercury content pe	r lamp: mg	
P8.1*		omposition: Lithium N	langanese Dioxide			
P9		tion (See NOTE B8)				
P9.1			s or energy consumption	ons are reported:		
Energy mod	de *	Power level at	Power level at	Power level at	Reference/Standard for energy	/
Peak (On-n	navl	100 V AC W	115 V AC W	230 V AC W	modes and test method * Full load	
,		VV	VV	VV	Tunioad	
Category	<u>/l2</u>					
	State - WOL	23.21 W	23.05 W	23.02 W	Use for ENERGY STAR V6	
Enabled					registration (P _{idle})	
Long Idle S	State - WOL	10.62 W	10.48 W	10.55 W	Use for ENERGY STAR V6	
Enabled					registration (P _{idle})	
Sleen (S3)	- WOL Enabled	0.92 W	0.98 W	1.02 W	Use for ENERGY STAR V6	
Greep (GS)	- WOL Lilabied	0.52 **	0.50 **	7.02 **	registration(P_{sleep})	
Off (S5) 1/	VOL Enabled	0.6 W	0.64 W	0.64 W	Use for ENERGY STAR V6	
OII (33) - V	VOL Ellabled	0.0 VV	0.04 VV	0.04 VV	registration(P _{off})	
Category	/I3					
	State - WOL	23.68 W	23.32 W	23.21 W	Use for ENERGY STAR V6	
Enabled					registration (P _{idle})	
	State - WOL	10.95 W	10.96 W	10.62 W	Use for ENERGY STAR V6	
Enabled					registration (P _{idle})	
Sleep (S3)	- WOL Enabled	0.94 W	0.94 W	0.98 W	Use for ENERGY STAR V6	
					registration(P _{sleep})	
Off (S5) - V	VOL Enabled	0.61 W	0.61 W	0.64 W	Use for ENERGY STAR V6	
					registration(P _{off})	
Category	<u>/D1</u>					
Short Idle	State - WOL	23.65 W	23.94 W	23.18 W	Use for ENERGY STAR V6	
Enabled	-				registration (P _{idle})	
Long Idle S	State - WOL	9.4 W	9.83 W	9.75 W	Use for ENERGY STAR V6	
Enabled					registration (Pidle)	
Sleep (S3)	- WOL Enabled	1.04 W	1.04 W	1.11 W	Use for ENERGY STAR V6	
,					registration(P _{sleep})	
Off (S5) - V	VOL Enabled	0.67 W	0.67 W	0.68' W	Use for ENERGY STAR V6	
1-37					registration(P _{off})	
Category	/I3					
		24.57.\\\	24 57 \\\	24.00 \\	Deference	
Short Idle S Enabled	State - WOL	31.57 W	31.57 W	31.09 W	Reference	
	N. 1 146:	40.0014	40.00.00	40.50.04		
Long Idle S Enabled	State - WOL	16.68 W	16.89 W	16.59 W	Reference	

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

Sleep (S3	3) - WOL Enabled	1.05 W	1.1 W	1.1 W	Reference
Off (S5) -	WOL Enabled	0.72 W	0.72 W	0.75 W	Reference
EPS No-lo	oad	W	W	W	
	er supply / charger plugged in the disconnected from the product.)				
PTEC *		W	W	W	
Typical Er	nergy Consumption				
ETEC *		12:87.88 kWh/year	12:87.39 kWh/year	12:87.41 kWh/year	$E_{TEC} = (8760/1000) \times (P_{off} \times 0.45)$
Annual Er	nergy Consumption	13:89.81 kWh/year	13:88.72 kWh/year	13:88.07 kWh/year	+ P _{sleep} x 0.05 + P _{long_Idle} x 0.15+
		D1:87.96 kWh/year	D1:89.41 kWh/year	D1:87.05 kWh/year	Pshort_Idle x 0.35)
		D2:122.01	D2:122.31 kWh/year	D2:120.56 kWh/year	
		kWh/year			
		P _{off} : Off Mode(S	S5) - WOL Enabled; Psleep	: Sleep Mode(S3) - WOL	Enabled; Pidle: Idle State - WOL Enabled
External F	Power Supply Efficie	ncy Level (International	Efficiency Marking Pro	otocol) * :	
Display re	esolution * : 2.07 me	gapixels			
Default tin	ne to enter energy s	ave mode: 25 minutes			
P9.2*	Information about	the energy save function	on is provided with the	product.	
P9.3	Energy efficiency	class (monitors only):			
P10	Emissions	<u> </u>			
	Noise emission -	- Declared according to	ISO 9296 (See NOTE	B9)	
P10.1		Mode description	·		A-weighted sound power level, L _{WA,c} (B)
	Idle	* HDD:Idle		* 2.7	
	Operation	* HDD: Operating		* 2.8	
Ī	Other mode	Declared A-weighted soun	d pressure level (dB) $L_{p{\sf Am}}$	19.3 (operator posit	ion desktop – idle)
	Other mode	Declared A-weighted soun	d pressure level (dB) $L_{p{\sf Am}}$	19.5 (operator posit	ion desktop – operating)
	Measured accordi	ing to: ISO 7779 Other	ECMA-74 (only if not covered by	ECMA-74)	

Model nu	umber *	10S6, 10S7, 10Y	5, 10Y6				Logo	Lenc	W/0	
Issue dat	te *	2018.05.30						Lenc		TM
Product	t environr	mental attributes	s - Market requirer	ments (con	tinued)			Require	ment	me
Item			-	-	•			Yes	No	n.a
		magnetic emissior								
P10.4	Compute program		e requirement for low	frequency el	ectromagnetic field	s of the foll	lowing voluntary	y 🔀		
P12		mics for computin								
P12.1*	The disp	lay meets the ergo	nomic requirements o	of ISO 9241-3	307 for visual displa	ay technolo	gies.	\boxtimes		
P12.2*	The phys	sical input device m	eets the requirement	ts of ISO 999	5 and ISO 9241-41	0.		\boxtimes		
P13	Packagi	ng and document	ation							
P13.1*	Product	packaging material packaging material packaging material	type(s): Idpe	weight (kg weight (kg weight (kg): 0.028					
P13.2*	Product	plastic primary pac	kaging is free from P\	VC.						\boxtimes
P13.3*	consume	er recovered fiber c	gated fiberboard pack ontent: 70 %		ify the contained	percentage	of minimum p	ost-		
P13.4*			product documentation Other	on (tick box):						
P13.5	Ùser and		item if paper documer tation on paper media							
	,	hlorine-free								
		al chlorine-free								
		ed chlorine-free								
P14		ry programs								
P14.1	The prod	duct meets the requ	irements of the follow	ving voluntary	/ program(s):					
	Eco-labe Eco-labe Eco-labe Eco-labe	el: Eye Comfort el: Low blue light	Criteria version: 7. Criteria version: Criteria version: Criteria version: 3. Criteria version: Criteria version:		Date: 2018.5.30 Date: Date: Date: Date: Date: Date: Date:	Product of Product of Product of	category: <i>I2&I3</i> category: <i>AIO</i> category: <i>Comp</i> category: <i>AIO</i> category: <i>AIO</i> category: <i>AIO</i> category: <i>AIO</i>			
P15		nal information (Se								
P9			pecific configuration							
	informati knowled provided informati	on contained in this ge available at the here is approxima ion.	representations, guara is document. All inform time of completion, ar te and provided for in	nation providend supplier sl formational p	ed by supplier in the nall have no obligate ourposes only. See	is documer tion to upda a Lenovo A	nt is provided ba ate such informa	ased on suppation. The in	plier's format	ion
P9			Notebooks & Tablet C				code=CO			

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1
Regulation (EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1

Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	ThinkCentre M920z AIO	Logo
Model Number	10S6, 10S7, 10Y5, 10Y6	Lanava
Issue Date	2018.05.30	Lenovo
Additional information	TCO;Energy Star 7;Greenguard;Low Blue light;EPEAT Gold;Eye com	ifort

d)	year of manufacture:				2018
e)	Etec value (kWh) per ErP Lot 3 Categor disabled and if the system is tested with				cards (dGfx) are
f)	Etec value (kWh) per ErP Lot 3 Categor enable	ry and capability adjust	ments applied when a	III discrete graphics o	cards (dGfx) are
		Category A (according to ErP Lot 3)	Category B (according to ErP Lot 3)	Category C (according to ErP Lot 3)	Category D (according to ErP Lot 3)
	Memory over base [GB]	-	30		28
ents	Additional internal storage	(Yes / No)	Yes (Yes / No)	(Yes / No)	Yes (Yes / No)
capability adjustments applied during testing	Discrete television tuner	(Yes / No)	No (Yes / No)	(Yes / No)	No (Yes / No)
ability a lied du	Discrete Audio Card	(Yes / No)	No (Yes / No)	(Yes / No)	No (Yes / No)
cap	Discrete graphics Card(s) [number / #]	#: (Yes / No)	Yes #: 1 (Yes / No)	#: (Yes / No)	Yes #: 1 (Yes / No)
	Category of discrete graphics Card(s)		G2		G2
saults	Etec Value (kWh) - dGfx disabled all discrete graphics cards (dGfx) are disabled/ UMA is active for switchable graphics/ product has no graphics cards (dGfx)		38.76		40.30
Test results	Etec Value (kWh) - dGfx enabled all discrete graphics cards (dGfx) are enabled		39.92		41.88
(g)	Idle state power demand (Watts);				B:10.102
h)	Sleep mode power demand (Watts);				D:10.79 B:1.025 D:1.032
(i)	Sleep mode with WOL enabled power do	emand (Watts) (where	enabled);		B:1.081 D:1.092
j)	Off mode power demand (Watts);				B:0.652 D:0.614
(k)	Off mode with WOL enabled power dem	and (Watts) (where en	abled);		B:0.71
(I)	Internal power supply efficiency at 10 %,	, 20 %, 50 % and 100 °	% of rated output pow	er (if applicable):	D:0.746
	150w:10% 83.6% 20% 90.2% 50%	93.8% 100% 93.4%	Average 90.25%		
	180w:10% 85.9% 20% 91.4% 50%	94.0% 100% 92.8%	Average 90.77%		
m)	External power supply efficiency (if appli	cable)*:			
	Average active efficiency: N/A				
(o)	*internal note: show values for all available external p Minimum number of loading cycles that t		and (applies only to n	otebook computers):	N/A
(p-1)	Measurement methodology used to dete	ermine information men	. ,	nternal PSU efficiency:	

(p-2)	Measurement method	N/A	mentionea in p	points (m) – external PSU efficiency:	
p-3)	Measurement method	ology used to determine information N/A	mentioned in p	points (o) – loading cycles batteries:	
p-4)		ology used to determine information oint P9.1 in the Product IT Eco Decla		naximum, idle, sleep, off mode	
	Refer to IEC 6262	3:2013-Desktop and notebook com	puters-Meası	rement of energy conmumption	
)	Sequence of steps for	achieving a stable condition with res	pect to power	demand:	
	Ва	sed on user manual/Power on->Wa	nit 5 minutes-	>Stable condition	
	Description of how sle	ep and/or off mode was selected or p	orogrammed:		
	Base	d on user manual/Begin menu -> F	Power -> Seled	ct sleep or off mode	
)	Sequence of events re off mode:	equired to reach the mode where the	equipment au	tomatically changes to sleep and/or	
	Based on user mai	nual/Control Panel->Power Options for this pl		ettings-> Restore default settings	
)		e condition before the computer au not exceed the applicable power dem			25
1)	Length of time after	a period of user inactivity in which	the compute	r automatically reaches a power	
)		er power demand requirement than set to ethe display sleep mode is set to			10
v)	Information on the end	ergy-saving potential of power manag	ement functio	nality:	
		Based on user	manual		
		Duodu dii uddi			
()	User information on h	ow to enable the power management	functionality:		
()	User information on h				
,	Test parameters for m	Based on user easurements: — test voltage in V an ystem, — information and document.	manual d frequency in		
•	Test parameters for methe electricity supply sused for electrical test	Based on user easurements: — test voltage in V an ystem, — information and document ing: 230V, 50Hz, Total Harmon	manual d frequency in	strumentation, set-up and circuits	
,	Test parameters for methe electricity supply sused for electrical test	Based on user easurements: — test voltage in V an ystem, — information and documenting: 230V, 50Hz, Total Harmon Range Used	manual d frequency in	strumentation, set-up and circuits	
,	Test parameters for methe electricity supply sused for electrical test sustained in the sused for electrical test sustained in the sustained i	Based on user easurements: — test voltage in V an ystem, — information and document ing: 230V, 50Hz, Total Harmon Range Used Or	manual d frequency in ation on the in mic Distortion Make and M	<2 %	
•	Test parameters for methe electricity supply sused for electrical test lnstrument Type AC Power Source	Based on user leasurements: — test voltage in V an ystem, — information and document ing: 230V, 50Hz, Total Harmon Range Used Or 1~280VAC; 1~550Hz; 1000VA	manual d frequency in ation on the in nic Distortion Make and M Chroma;615	<2 % dodel do4; SN:615040001117	
•	Test parameters for methe electricity supply sused for electrical test lnstrument Type AC Power Source Digital Watch	Dow to enable the power management Based on user Reasurements: — test voltage in V an ystem, — information and document ing: 230V, 50Hz, Total Harmon Range Used Or 1~280VAC; 1~550Hz; 1000VA Full range	manual d frequency in ation on the in mic Distortion Make and M Chroma;615 CASIO; HS-	strumentation, set-up and circuits <2 % lodel 104; SN:615040001117 70W; SN:208Q08R	
,	Test parameters for methe electricity supply sused for electrical test used for electrical test Instrument Type AC Power Source Digital Watch Power Meter	Dow to enable the power management Based on user Reasurements: — test voltage in V an ystem, — information and document ing: 230V, 50Hz, Total Harmon Range Used Or 1~280VAC; 1~550Hz; 1000VA Full range 0~600V; 0~20A	manual d frequency in ation on the in mic Distortion Make and M Chroma;615 CASIO; HS-	<2 % dode	
,	Test parameters for methe electricity supply sused for electrical test lnstrument Type AC Power Source Digital Watch	Based on user Based	manual d frequency in ation on the in nic Distortion Make and M Chroma;615 CASIO; HS- YOKOGAW. TESTO; 608	strumentation, set-up and circuits <2 % lodel 104; SN:615040001117 70W; SN:208Q08R	
•	Test parameters for methe electricity supply sused for electrical test linstrument Type AC Power Source Digital Watch Power Meter Hygrothermograph	Based on user Based on user Based on user Beasurements: — test voltage in V an ystem, — information and document ing: 230V, 50Hz, Total Harmon Range Used Or 1~280VAC; 1~550Hz; 1000VA Full range 0~600V; 0~20A 15~35°C/ 15~90%	manual d frequency in ation on the in mic Distortion Make and M Chroma;615 CASIO; HS- YOKOGAW. TESTO; 608 TESTO; 425	<2 % lodel lo4; SN:615040001117 row; SN:208Q08R A; WT310E; SN:C3SJ16035E 8-H1; SN:1034895602	
,	Test parameters for methe electricity supply sused for electrical test linstrument Type AC Power Source Digital Watch Power Meter Hygrothermograph Thermal anemometer	Dow to enable the power management Based on user easurements: — test voltage in V an ystem, — information and document ing: 230V, 50Hz, Total Harmon Range Used Or 1~280VAC; 1~550Hz; 1000VA Full range 0~600V; 0~20A 15~35°C/ 15~90% ar 0~20m/s, -20~70°C	manual d frequency in ation on the in mic Distortion Make and M Chroma;615 CASIO; HS- YOKOGAW. TESTO; 608 TESTO; 425	strumentation, set-up and circuits <2 % lodel 104; SN:615040001117 70W; SN:208Q08R A; WT310E; SN:C3SJ16035E 3-H1; SN:1034895602 5; SN:02591883	
z)	Test parameters for methe electricity supply sused for electrical test used for electrical test Instrument Type AC Power Source Digital Watch Power Meter Hygrothermograph Thermal anemometer Light Measuring	Dow to enable the power management Based on user Reasurements: — test voltage in V an ystem, — information and document ing: 230V, 50Hz, Total Harmon Range Used Or 1~280VAC; 1~550Hz; 1000VA Full range 0~600V; 0~20A 15~35°C/ 15~90% or 0~20m/s, -20~70°C 1; 1~300cd/m²	manual d frequency in ation on the in nic Distortion Make and M Chroma;615 CASIO; HS- YOKOGAW, TESTO; 608 TESTO; 425 KONICA MII	strumentation, set-up and circuits <2 % dodel 604; SN:615040001117 70W; SN:208Q08R A; WT310E; SN:C3SJ16035E 8-H1; SN:1034895602 6; SN:02591883 NOLTQ:LS-110	
z)	Test parameters for methe electricity supply sused for electrical test used for electrical test Instrument Type AC Power Source Digital Watch Power Meter Hygrothermograph Thermal anemometer Light Measuring	Based on user leasurements: — test voltage in V an lystem, — information and document ing: 230V, 50Hz, Total Harmon Range Used Or 1~280VAC; 1~550Hz; 1000VA Full range 0~600V; 0~20A 15~35°C/ 15~90% er 0~20m/s, -20~70°C 1; 1~300cd/m² Information: Battery[ies] not user replaces	manual d frequency in ation on the in mic Distortion Make and M Chroma;615 CASIO; HS- YOKOGAW. TESTO; 608 TESTO; 425 KONICA MIII	strumentation, set-up and circuits <2 % lodel 104; SN:615040001117 70W; SN:208Q08R A; WT310E; SN:C3SJ16035E 3-H1; SN:1034895602 5; SN:02591883	n/a
z)	Test parameters for methe electricity supply sused for electrical test used for electrical test Instrument Type AC Power Source Digital Watch Power Meter Hygrothermograph Thermal anemometer Light Measuring	Dow to enable the power management Based on user Reasurements: — test voltage in V an ystem, — information and document ing: 230V, 50Hz, Total Harmon Range Used Or 1~280VAC; 1~550Hz; 1000VA Full range 0~600V; 0~20A 15~35°C/ 15~90% or 0~20m/s, -20~70°C 1; 1~300cd/m²	manual d frequency in ation on the in mic Distortion Make and M Chroma;615 CASIO; HS- YOKOGAW. TESTO; 608 TESTO; 425 KONICA MIII	strumentation, set-up and circuits <2 % dodel 604; SN:615040001117 70W; SN:208Q08R A; WT310E; SN:C3SJ16035E 8-H1; SN:1034895602 6; SN:02591883 NOLTQ:LS-110	n/a
.dditic	Test parameters for methe electricity supply sused for electrical test used for electrical test Instrument Type AC Power Source Digital Watch Power Meter Hygrothermograph Thermal anemometer Light Measuring	Based on user leasurements: — test voltage in V an lystem, — information and document ing: 230V, 50Hz, Total Harmon Range Used Or 1~280VAC; 1~550Hz; 1000VA Full range 0~600V; 0~20A 15~35°C/ 15~90% er 0~20m/s, -20~70°C 1; 1~300cd/m² Information: Battery[ies] not user replaced The battery[ies] in this product can	manual d frequency in ation on the in mic Distortion Make and M Chroma;615 CASIO; HS- YOKOGAW. TESTO; 608 TESTO; 425 KONICA MIII	strumentation, set-up and circuits <2 % dodel 604; SN:615040001117 70W; SN:208Q08R A; WT310E; SN:C3SJ16035E 8-H1; SN:1034895602 6; SN:02591883 NOLTQ:LS-110	n/a
Additic	Test parameters for methe electricity supply sused for electrical test used for electrical test Instrument Type AC Power Source Digital Watch Power Meter Hygrothermograph Thermal anemometer Light Measuring	Based on user leasurements: — test voltage in V an lystem, — information and document ing: 230V, 50Hz, Total Harmon Range Used Or 1~280VAC; 1~550Hz; 1000VA Full range 0~600V; 0~20A 15~35°C/ 15~90% er 0~20m/s, -20~70°C 1; 1~300cd/m² Information: Battery[ies] not user replaced The battery[ies] in this product can	manual d frequency in ation on the in mic Distortion Make and M Chroma;615 CASIO; HS- YOKOGAW. TESTO; 608 TESTO; 425 KONICA MIII	strumentation, set-up and circuits <2 % dodel 604; SN:615040001117 70W; SN:208Q08R A; WT310E; SN:C3SJ16035E 8-H1; SN:1034895602 6; SN:02591883 NOLTQ:LS-110	
Addition nternal	Test parameters for methe electricity supply sused for electrical test linstrument Type AC Power Source Digital Watch Power Meter Hygrothermograph Thermal anemomete Light Measuring Donal Notebook Battery	Based on user leasurements: — test voltage in V an lystem, — information and document ing: 230V, 50Hz, Total Harmon Range Used Or 1~280VAC; 1~550Hz; 1000VA Full range 0~600V; 0~20A 15~35°C/ 15~90% er 0~20m/s, -20~70°C 1; 1~300cd/m² Information: Battery[ies] not user replaced The battery[ies] in this product can	manual d frequency in ation on the in mic Distortion Make and M Chroma;615 CASIO; HS- YOKOGAW. TESTO; 608 TESTO; 425 KONICA MIII	strumentation, set-up and circuits <2 % dodel 604; SN:615040001117 70W; SN:208Q08R A; WT310E; SN:C3SJ16035E 8-H1; SN:1034895602 6; SN:02591883 NOLTQ:LS-110	
Addition nternal	Test parameters for methe electricity supply sused for electrical test last last last last last last last la	Based on user leasurements: — test voltage in V an lystem, — information and document ing: 230V, 50Hz, Total Harmon Range Used Or 1~280VAC; 1~550Hz; 1000VA Full range 0~600V; 0~20A 15~35°C/ 15~90% er 0~20m/s, -20~70°C 1; 1~300cd/m² Information: Battery[ies] not user replaced The battery[ies] in this product can	manual d frequency in ation on the in mic Distortion Make and M Chroma;615 CASIO; HS- YOKOGAW. TESTO; 608 TESTO; 425 KONICA MIII	strumentation, set-up and circuits <2 % dodel 604; SN:615040001117 70W; SN:208Q08R A; WT310E; SN:C3SJ16035E 8-H1; SN:1034895602 6; SN:02591883 NOLTQ:LS-110	

1)
The battery[ies] in this product cannot be easily replaced by users themselves.

Акумулаторната[ите] батерия[и] в този продукт не може да се замени[ят] лесно от самите потребители.

Las baterias de este producto no pueden ser sustituidas fácilmente por los propios usuarios. Výměnu baterie/baterií v tomto výrobku by neměli provádět sami uživatelé.

Brugeren kan ikke uden videre udskifte batteriet/batterierne i dette produkt.

Der Akku/die Akkus dieses Produkts kann/können nicht ohne weiteres vom Benutzer selbst ausgetauscht werden.

Kasutajad ei saa selle toote akut/akusid ise hõlpsasti asendada.

Η μπαταρία[-ες] στο προϊόν αυτό δεν μπορούν να αντικατασταθούν εύκολα από τους ίδιους τους χρήστες

La/les batterie(s présente(s) dans ce produit ne peuvent être facilement remplacée(s) par les utilisateurs eux-mêmes. Korisnik ne može lako zamijeniti Bateriju sam u ovom proizvodu.

La batteria/le batterie in questo prodotto non può/possono essere facilmente sostituita/e dall'utente. Lietotāji paši nevar nomainīt šā ražojuma akumulatoru(-us). Šio gaminio baterijos [baterijų] pats vartotojas negali lengvai pakeisti.

A termék akkumulátorát/akkumulátorait a felhasználó nem tudja egyedül egyszerűen kicserélni. Il-batterija/batteriji f'dan il-prodott ma tistax/jistgħux tiġi/jiġu sostitwita/i mill-utenti stess. Batteriet [ene] i dette produktet kan ikke lett erstattes av brukerne selv.

De batterij(en) in dit product is (zijn) door de gebruiker niet gemakkelijk vervangbaar.
Użytkownik nie może sam w łatwy sposób wymienić baterii w tym produkcie.
A ou as baterias deste produto não podem ser facilmente substituídas pelos próprios utilizadores.

Bateria (bateriile) din acest produs nu poate (pot) fi uşor înlocuită (înlocuite) de utilizatorii înşişi. Batériu(-ie) v tomto výrobku nemôže vymieňať používateľ. Baterij/baterije v tem izdelku uporabniki sami ne morejo zlahka zamenjati.

Tämän tuotteen akku [akut] ei[vät] ole helposti käyttäjän vaihdettavissa.

Det är inte enkelt för kunden att själv byta ut batteriet/batterierna. Bu üründeki batarya(lar) kullanıcılar tarafından kolaylıkla değiştirilemez.