

Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	ThinkPad	Logo		
Company name *	Lenovo			
Contact information *	Lenovo Global Environmental Affairs Alvin L Carter 1009 Think Place Building 2 / 5F1 Morrisville, North Carolina 27560 alcarter@lenovo.com			
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment.html			
Additional information	The latest version of this document can be found at http://www.lenovo.com/social responsibility/us/en/datasheets_notebooks.html			

	The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.					
Type of product *	Notebook					
Commercial name *	ThinkPad E570/E570c					
Model number *	20H5, 20H6, 20H7					
Issue date *	2016-07-07					
Intended market *	🔀 Global 📃 Europe 📃 Asia, Pacific & Japan 📃 Americas 📃 Other					
Additional information						

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Quality Control		
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).	bl 🔀	

Model number *	20H5, 20H6, 20H7		
Issue date *	2016-07-072016-07-07	Logo	Lenovo

Product	Product environmental attributes - Legal requirements			
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)			
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.	\boxtimes		
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),	\square		
	hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).	\boxtimes		
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).	\boxtimes		
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)			\square
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference).			\boxtimes
P1.9*	Comment: Legal reference has no maximum concentration values. Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5			
F 1.9	microgram/cm ² /week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:1998.			
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact):	\square		
	http://www.lenovo.com/social_responsibility/us/en/materials.html			
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)			
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)	\boxtimes		
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medical or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).	\square		
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference)			
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).	\square		
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	\boxtimes		
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).			
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).			\bowtie
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).			\square
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and hexavalent chromium by weight of these together.			
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).			
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montrea Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.			

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Item *=rr P6 Tre P6.1* Info P7 Des P7.1* Par P7.2* Plas P7.3* Plas P7.4* Plas P7.6* Lab P7.7* Upg P7.8* Upg P7.10 Ser P7.11* Pro Mat P7.12 P7.13 Elect P7.14 All o P7.15 All o P7.16 Flar P7.17 Alt. P7.18 Alt. Che ISO	vironn mandate eatmen ormatio sign sassem rts that astic para astic para asti	can be done e.g. with processor, memo can be done using commonly available are available after end of production for vailable after end of production for: 5 ye d substance requirements ver/housing material type:	ling each item may be found lable (see legal reference). separable e coating. asily separable materials. to ISO 11469 referring ISO 10 ays that can be removed with es not apply to safety/regulato rry, cards or drives tools or: 5 years ears ype: PC+ABS+15%Talc is are PVC free. s are PVC free chlorine and bromine. 25g are halogen free. As def ings are marked according IS	under P14.	Yes	
Item *=rr P6 Tre P6.1* Info P7 Des P7.1* Par P7.2* Plas P7.3* Plas P7.4* Plas P7.6* Lab P7.7* Upg P7.8* Upg P7.10 Ser P7.11* Pro Mat P7.12 P7.13 Elect P7.14 All o P7.15 All o P7.16 Flar P7.17 Alt. P7.18 Alt. Che ISO	mandate atmen prmatio sign asser rts that astic para- bels are poles	ry to fill in. Additional information regard information for recyclers/treatment facilities is avail by, recycling ave to be treated separately are easily erials in covers/housing have no surface is >100g consist of one material or of easily s are free from metal inlays or have inla easily separable. (This requirement does etime can be done e.g. with processor, memory can be done e.g. with processor, memory can be done e.g. with processor, memory can be done using commonly available are available after end of production for vailable after end of production for: 5 yee d substance requirements rer/housing material type: e: PC+ABS Material ty able insulation materials of power cable able insulation materials of signal cable using plastic parts >25g are free from of circuit boards (without components) >2 ded plastic parts >25g in covers / housi	ling each item may be found lable (see legal reference). separable e coating. asily separable materials. to ISO 11469 referring ISO 10 ays that can be removed with es not apply to safety/regulato rry, cards or drives tools or: 5 years ears ype: PC+ABS+15%Talc is are PVC free. s are PVC free chlorine and bromine. 25g are halogen free. As def ings are marked according IS	under P14.	Require Yes	
Item *=rr P6 Tree P6.1* Info P7 Dess P7.1* Par P7.2* Plas P7.3* Plas P7.4* Plas P7.6* Lab P7.7* Upg P7.8* Upg P7.10 Ser P7.11* Pro Mat P7.12 P7.13 Elect P7.14 All o P7.15 All o P7.16 Flar P7.17 Alt Chee TBE P7.16 Flar D7.17 Alt Chee ISO P7.18 Alt Chee ISO	mandate atmen prmatio sign asser rts that astic para- bels are poles	ry to fill in. Additional information regard information for recyclers/treatment facilities is avail by, recycling ave to be treated separately are easily erials in covers/housing have no surface is >100g consist of one material or of easily s are free from metal inlays or have inla easily separable. (This requirement does etime can be done e.g. with processor, memory can be done e.g. with processor, memory can be done e.g. with processor, memory can be done using commonly available are available after end of production for vailable after end of production for: 5 yee d substance requirements rer/housing material type: e: PC+ABS Material ty able insulation materials of power cable able insulation materials of signal cable using plastic parts >25g are free from of circuit boards (without components) >2 ded plastic parts >25g in covers / housi	ling each item may be found lable (see legal reference). separable e coating. asily separable materials. to ISO 11469 referring ISO 10 ays that can be removed with es not apply to safety/regulato rry, cards or drives tools or: 5 years ears ype: PC+ABS+15%Talc is are PVC free. s are PVC free chlorine and bromine. 25g are halogen free. As def ings are marked according IS	under P14.	Yes Image: Constraint of the second state	
P6 Tree P6.1* Info P7 Des Dis. Dis. P7.1* Par P7.2* Plas P7.3* Plas P7.5 Plas P7.6* Lab P7.6* Lab P7.7* Upg P7.8* Upg P7.10 Ser P7.12 Elect P7.13 Elect P7.14 All of P7.15 All of P7.16 Flar P7.17 Alt. Chec TBE P7.16 Flar P7.17 Alt. Chec ISO P7.18 Alt. Chec ISO	eatmen ormatio sign asser rts that astic para- astic para- bels are oduct li grading grading grading grading grading grading duct co terial a oduct co terial ty cover/r printed te B2) me reta rking: >	information for recyclers/treatment facilities is avail oly, recycling ave to be treated separately are easily erials in covers/housing have no surface is >100g consist of one material or of eas is >25g have material codes according t is are free from metal inlays or have inla easily separable. (This requirement doe etime can be done e.g. with processor, memo can be done e.g. with processor, memo can be done e.g. with processor, memo can be done using commonly available are available after end of production for: 5 ye d substance requirements ver/housing material type: e: PC+ABS Material ty able insulation materials of power cable able insulation materials of signal cable rusing plastic parts >25g are free from of circuit boards (without components) >2 ded plastic parts >25g in covers / housi	lable (see legal reference). separable e coating. asily separable materials. to ISO 11469 referring ISO 10 ays that can be removed with as not apply to safety/regulate ry, cards or drives tools or: 5 years ears ype: PC+ABS+15%Talc s are PVC free. s are PVC free chlorine and bromine. 25g are halogen free. As def ings are marked according IS	043. commonly available too ory labels). Material type: ined in IEC61249-2-21.		
P6.1* Info P7 Dess Dis. Dis. P7.1* Par P7.2* Plas P7.3* Plas P7.4* Plas P7.5 Plas P7.6* Lab P7.6* Lab P7.7* Upg P7.8* Upg P7.10 Ser P7.12 Elect P7.13 Elect P7.14 All o P7.15 All n P7.16 Flar P7.17 Alt. Chec TBE P7.17 Alt. Chec ISO P7.18 Alt. Chec ISO	ormatio sign assem rts that astic para- astic para- bels are oduct II grading grading grading grading grading are par rvice is terial a oduct co terial ty cover/r printed te B2) me reta rking: >	for recyclers/treatment facilities is avail ave to be treated separately are easily ave to be treated separately are easily arials in covers/housing have no surface s >100g consist of one material or of easily s >25g have material codes according to s are free from metal inlays or have inlate easily separable. (This requirement doer the done e.g. with processor, memory can be done using commonly available are available after end of production for: 5 yer d substance requirements ver/housing material type: e: <i>PC+ABS</i> Material ty able insulation materials of power cable able insulation materials of signal cable rusing plastic parts >25g are free from of circuit boards (without components) >2 ded plastic parts >25g in covers / housing ded plastic parts >25g in covers / housing ded plastic parts >25g in covers / housing available insulation materials of signal cable substance parts >25g in covers / housing ded plastic parts >	separable e coating. asily separable materials. to ISO 11469 referring ISO 10 ays that can be removed with as not apply to safety/regulate rry, cards or drives tools or: 5 years ears ype: PC+ABS+15%Talc s are PVC free. s are PVC free chlorine and bromine. 25g are halogen free. As def ings are marked according IS	commonly available too ory labels). Material type: ined in IEC61249-2-21.		
P7 Dess Dis. Dis. P7.1* Par P7.2* Plas P7.3* Plas P7.4* Plas P7.5 Plas P7.6* Lab P7.6* Lab P7.7* Upg P7.9. Spa P7.10 Ser P7.11* Pro Mat P7.12 P7.13 Elect P7.14 All o P7.15 All o P7.16 Flar P7.17 Alt. Chec TBE P7.16 Flar Not TBE P7.18 Alt. Chec ISO P7.18 Alt. Chec ISO	sign sassem rts that astic para astic para bels are boduct II grading grading grading grading grading are par rvice is terial a boduct co terial ty cover/r printed te B2) me reta rking: >	by, recycling ave to be treated separately are easily erials in covers/housing have no surface is >100g consist of one material or of eas is >25g have material codes according to is are free from metal inlays or have inla easily separable. (This requirement doe etime can be done e.g. with processor, memo can be done using commonly available are available after end of production for: 5 ye d substance requirements ver/housing material type: e: <i>PC+ABS</i> Material ty able insulation materials of signal cable insuing plastic parts >25g are free from o circuit boards (without components) >2 ded plastic parts >25g in covers / housi	separable e coating. asily separable materials. to ISO 11469 referring ISO 10 ays that can be removed with as not apply to safety/regulate rry, cards or drives tools or: 5 years ears ype: PC+ABS+15%Talc s are PVC free. s are PVC free chlorine and bromine. 25g are halogen free. As def ings are marked according IS	commonly available too ory labels). Material type: ined in IEC61249-2-21.		
P7.1* Par P7.2* Plas P7.3* Plas P7.3* Plas P7.4* Plas P7.5 Plas P7.6* Lab P7.6* Lab P7.7* Upg P7.9. Spa P7.10 Ser P7.11* Pro Mat P7.12 P7.13 Elect P7.14 All o P7.15 All o P7.16 Flar P7.17 Alt. Chee TBE P7.18 Alt. Chee ISO P7.18 Alt. Co 1. C Co 2. C	rts that astic ma astic para astic para bels are boduct li grading grading grading grading grading are par rvice is aterial a boduct co terial ty cover/r printed te B2) me reta rking: >	ave to be treated separately are easily erials in covers/housing have no surface s >100g consist of one material or of eas s >25g have material codes according to s are free from metal inlays or have inla easily separable. (This requirement doe etime can be done e.g. with processor, memo can be done e.g. with processor, memo can be done e.g. with processor, memo can be done using commonly available are available after end of production for vailable after end of production for: 5 ye d substance requirements rer/housing material type: e: PC+ABS Material ty able insulation materials of signal cable insulation materials of signal cable circuit boards (without components) >2 ded plastic parts >25g in covers / housi	e coating. asily separable materials. to ISO 11469 referring ISO 10 ays that can be removed with as not apply to safety/regulate rry, cards or drives tools or: 5 years ears ype: PC+ABS+15%Talc s are PVC free. s are PVC free chlorine and bromine. 25g are halogen free. As def ings are marked according IS	commonly available too ory labels). Material type: ined in IEC61249-2-21.		
P7.2* Plas P7.3* Plas P7.3* Plas P7.4* Plas P7.5 Plas P7.6* Lab P7.6* Lab P7.7* Upg P7.8* Upg P7.9. Spa P7.10 Ser P7.11* Pro Mat P7.12 P7.13 Elect P7.14 All or P7.15 All or P7.16 Flar P7.17 Alt. Chec ISO P7.18 Alt. Chec ISO	astic ma astic para astic para bels are bols are bols are bolder li grading grading grading grading are par rvice is terial a boluct co terial ty cover/r printed te B2) me reta rking: >	erials in covers/housing have no surface s >100g consist of one material or of ea s >25g have material codes according to s are free from metal inlays or have inla easily separable. (This requirement doe etime can be done e.g. with processor, memo can be done e.g. with processor, memo can be done e.g. with processor, memo can be done using commonly available are available after end of production for vailable after end of production for: 5 ye d substance requirements rer/housing material type: e: PC+ABS Material ty able insulation materials of signal cable rusing plastic parts >25g are free from of circuit boards (without components) >2 ded plastic parts >25g in covers / housi	e coating. asily separable materials. to ISO 11469 referring ISO 10 ays that can be removed with as not apply to safety/regulate rry, cards or drives tools or: 5 years ears ype: PC+ABS+15%Talc s are PVC free. s are PVC free chlorine and bromine. 25g are halogen free. As def ings are marked according IS	commonly available too ory labels). Material type: ined in IEC61249-2-21.		
P7.3* Plas P7.4* Plas P7.5 Plas P7.6* Lab P7.6* Lab P7.6* Lab P7.6* Lab P7.7* Upg P7.8* Upg P7.9. Spa P7.10 Ser P7.11* Pro Mat P7.12 P7.13 Elec P7.14 All o P7.15 All p P7.16 Flar P7.17 Alt. Che ISO P7.18 Alt. Flar con CO 1. C	stic paratic p	s >100g consist of one material or of ea s >25g have material codes according t s are free from metal inlays or have inla easily separable. (This requirement doe etime can be done e.g. with processor, memo can be done e.g. with processor, memo can be done using commonly available are available after end of production for vailable after end of production for: 5 ye d substance requirements rer/housing material type: e: <i>PC+ABS</i> Material ty able insulation materials of signal cable using plastic parts >25g are free from of circuit boards (without components) >2 ded plastic parts >25g in covers / housi	asily separable materials. to ISO 11469 referring ISO 10 ays that can be removed with as not apply to safety/regulate rry, cards or drives tools br: 5 years ears ype: <i>PC+ABS+15%Talc</i> is are PVC free. s are PVC free chlorine and bromine. 25g are halogen free. As def ings are marked according IS	commonly available too ory labels). Material type: ined in IEC61249-2-21.		
P7.4* Plas P7.5 Plas P7.6* Lab P7.6* Lab P7.6* Lab P7.6* Lab P7.6* Upg P7.7* Upg P7.8* Upg P7.9. Spa P7.10 Ser P7.11* Pro Mat P7.12 P7.13 Elec P7.14 All o P7.15 All p P7.16 Flar P7.17 Alt. Che ISO P7.18 Alt. Flar con CO 1. C Question Co	astic para astic para pels are poduct li grading grading grading are par rvice is terial a poduct co terial ty ectrical of cover/r printed te B2) me reta rking: >	s >25g have material codes according to sare free from metal inlays or have inla easily separable. (This requirement doe eatime can be done e.g. with processor, memo can be done using commonly available are available after end of production for vailable after end of production for: 5 ye d substance requirements ver/housing material type: e: PC+ABS Material ty able insulation materials of power cable able insulation materials of signal cable using plastic parts >25g are free from of circuit boards (without components) >2 ded plastic parts >25g in covers / housi	ings are marked according IS	commonly available too ory labels). Material type: ined in IEC61249-2-21.		
P7.5 Plas P7.6* Lab P7.6* Lab P7.6* Lab P7.6* Lab P7.7* Upg P7.8* Upg P7.9. Spa P7.10 Ser Mat P7.11* P7.12 Elect P7.13 Elect P7.14 All of P7.15 All of P7.16 Flar P7.17 Alt. Che TBE Alt. Che ISO P7.18 P7.18 Alt. Co 1. C Question Question	stic part bels are bolls are particular grading grading grading grading are par rvice is terial a boduct co terial ty boduct co terial ty cotrical of cover/r printed te B2) me reta rking: >	s are free from metal inlays or have inla easily separable. (This requirement doe etime can be done e.g. with processor, memo can be done using commonly available are available after end of production for vailable after end of production for: 5 ye d substance requirements ver/housing material type: e: <i>PC+ABS</i> Material ty able insulation materials of power cable able insulation materials of signal cable rusing plastic parts >25g are free from o circuit boards (without components) >2 ded plastic parts >25g in covers / housi	Ays that can be removed with es not apply to safety/regulate ory, cards or drives tools or: 5 years ears ype: PC+ABS+15%Talc is are PVC free. s are PVC free chlorine and bromine. 25g are halogen free. As def ings are marked according IS	commonly available too ory labels). Material type: ined in IEC61249-2-21.		
P7.6* Lab P7.0 Pro P7.7* Upg P7.8* Upg P7.9. Spa P7.10 Ser P7.11* Pro P7.12 Elect P7.13 Elect P7.14 All of P7.15 All p Not Not P7.16 Flar P7.17 Alt. Che TBE Alt. Che ISO P7.18 P7.18 Alt. Co 1. C 2. C P7.18	bels are poluct li grading grading are par rvice is iterial a oduct coi terial ty ectrical of cover/r printed te B2) me reta rking: >	easily separable. (This requirement doe etime can be done e.g. with processor, memo can be done using commonly available are available after end of production for vailable after end of production for: 5 yr d substance requirements ver/housing material type: e: PC+ABS Material ty able insulation materials of power cable able insulation materials of signal cable rusing plastic parts >25g are free from of circuit boards (without components) >2 ded plastic parts >25g in covers / housi	ype: PC+ABS+15%Talc s are PVC free chlorine and bromine. 25g are marked according IS	Material type:	. (See	
Pro P7.7* Upg P7.8* Upg P7.9. Spa P7.10 Ser P7.11* Pro Mat P7.12 P7.13 Elect P7.14 All of P7.15 All p P7.16 Flar P7.17 Alt. Chee TBE Alt. Chee ISO P7.18 P7.18 Alt. Con Co 1. C Co 2. C C	are par rvice is aterial a oduct co terial ty ectrical cover/r printed te B2) me reta rking: >	etime can be done e.g. with processor, memory can be done using commonly available are available after end of production for are available after end of production for: vailable after end of production for: yet d substance requirements rer/housing material type: e: PC+ABS Material type: able insulation materials of power cable able insulation materials of signal cable rusing plastic parts >25g are free from of circuit boards (without components) >2 ded plastic parts >25g in covers / housing	ry, cards or drives tools br: 5 years ears ype: PC+ABS+15%Talc s are PVC free. s are PVC free chlorine and bromine. 25g are halogen free. As def ings are marked according IS	Material type: ined in IEC61249-2-21.	. (See	
P7.7* Upg P7.8* Upg P7.9. Spa P7.10 Ser P7.11* Pro Mat P7.12 P7.13 Elect P7.14 All or P7.15 All or P7.16 Flar P7.17 Alt. Chee ISO P7.18 Alt. Flar Coor Coor 2. Cor	grading grading are par rvice is terial a oduct co terial ty ectrical cover/r printed te B2) me reta rking: 2	can be done e.g. with processor, memo- can be done using commonly available are available after end of production for vailable after end of production for: 5 ye d substance requirements rer/housing material type: e: <i>PC+ABS</i> Material ty able insulation materials of power cable able insulation materials of signal cable rusing plastic parts >25g are free from of circuit boards (without components) >2 ded plastic parts >25g in covers / housi	tools tools or: 5 years ears ype: PC+ABS+15%Talc s are PVC free. s are PVC free chlorine and bromine. 25g are halogen free. As def ings are marked according IS	ined in IEC61249-2-21.	. (See	
P7.8* Upg P7.9. Spa P7.10 Ser Mat Mat P7.11* Pro Mat Pro P7.12 Elect P7.13 Elect P7.14 All of P7.15 All of P7.16 Flar P7.17 Alt. Chee ISO P7.18 Alt. Flar Con Con Co Q.CO 2. CO	grading are par rvice is terial a oduct co terial ty ectrical (ectrical (cover/r printed te B2) me reta rking: 2	can be done using commonly available are available after end of production for vailable after end of production for: 5 ye d substance requirements rer/housing material type: e: <i>PC+ABS</i> Material ty able insulation materials of power cable able insulation materials of signal cable rusing plastic parts >25g are free from of circuit boards (without components) >2 ded plastic parts >25g in covers / housi	tools tools or: 5 years ears ype: PC+ABS+15%Talc s are PVC free. s are PVC free chlorine and bromine. 25g are halogen free. As def ings are marked according IS	ined in IEC61249-2-21.	. (See	
P7.9. Spa P7.10 Ser P7.11* Pro Mat P7.12 P7.12 Elec P7.13 Elec P7.14 All of P7.15 All of P7.16 Flar P7.17 Alt. Che ISO P7.18 Alt. Flar Con Co 1. C	are par rvice is tterial a oduct co terial ty ectrical o cover/r printed te B2) me reta rking: 2	are available after end of production for vailable after end of production for: 5 ye d substance requirements rer/housing material type: e: <i>PC+ABS</i> Material ty able insulation materials of power cable able insulation materials of signal cable using plastic parts >25g are free from of circuit boards (without components) >2 ded plastic parts >25g in covers / housi	or: 5 years ears ype: PC+ABS+15%Talc is are PVC free. s are PVC free chlorine and bromine. 25g are halogen free. As def ings are marked according IS	ined in IEC61249-2-21.	. (See	
P7.10 Ser P7.11* Pro Mat P7.12 Elec P7.13 Elec P7.14 All of P7.15 All of P7.16 Flar P7.17 Alt. Che ISO P7.18 Alt. Flar Con CO 1. C	rvice is terial a oduct cc terial ty ectrical of cover/r printed te B2) me reta rking: >	vailable after end of production for: 5 ye d substance requirements ver/housing material type: e: <i>PC+ABS</i> Material ty able insulation materials of power cable able insulation materials of signal cable rusing plastic parts >25g are free from of circuit boards (without components) >2 ded plastic parts >25g in covers / housi	ears ype: PC+ABS+15%Talc s are PVC free. s are PVC free chlorine and bromine. 25g are halogen free. As def ings are marked according IS	ined in IEC61249-2-21.	. (See	
Mat P7.11* Pro Mat P7.12 Elea P7.13 Elea P7.14 All o P7.15 All o P7.16 Flar P7.17 Alt. Che TBE Alt. Che SO P7.18 Alt. Flar Con Con Con Con	terial a oduct co terial ty ectrical of cover/h printed te B2) me reta irking: 2	d substance requirements rer/housing material type: e: PC+ABS Material type: able insulation materials of power cable able insulation materials of signal cable rusing plastic parts >25g are free from c circuit boards (without components) >2 ded plastic parts >25g in covers / housi	ype: PC+ABS+15%Talc s are PVC free. s are PVC free chlorine and bromine. 25g are halogen free. As def ings are marked according IS	ined in IEC61249-2-21.	. (See	
P7.11* Promote P7.12 Elect P7.13 Elect P7.14 All of P7.15 All of P7.16 Flar P7.17 Alt. Che TBE Alt. Che ISO Flar Con Con Con Con Con Con	oduct co terial ty ectrical cover/h printed te B2) me reta irking: >	rer/housing material type: e: <i>PC+ABS</i> Material type able insulation materials of power cable able insulation materials of signal cable rusing plastic parts >25g are free from c circuit boards (without components) >2 ded plastic parts >25g in covers / housi	s are PVC free. s are PVC free chlorine and bromine. 25g are halogen free. As def ings are marked according IS	ined in IEC61249-2-21.	. (See	
P7.12 Elec P7.13 Elec P7.14 All c P7.15 All Not P7.16 Flar Mar P7.17 Alt. Che TBE Alt. Che ISO P7.18 Alt. Flar con Co 1. C 2. C	ectrical of ectrical of ectrical of cover/h printed te B2) me reta arking: >	e: PC+ABS Material ty able insulation materials of power cable able insulation materials of signal cable rusing plastic parts >25g are free from of circuit boards (without components) >2 ded plastic parts >25g in covers / housi	s are PVC free. s are PVC free chlorine and bromine. 25g are halogen free. As def ings are marked according IS	ined in IEC61249-2-21.	. (See	
P7.12 Elect P7.13 Elect P7.14 All of P7.15 All of P7.16 Flar Mar P7.17 Alt. Che TBE Alt. Che ISO P7.18 Alt. Flar Con Con Con Co 2. Co	ectrical ectrical cover/r printed te B2) me reta rking: >	able insulation materials of power cable able insulation materials of signal cable using plastic parts >25g are free from o circuit boards (without components) >2 ded plastic parts >25g in covers / housi	s are PVC free. s are PVC free chlorine and bromine. 25g are halogen free. As def ings are marked according IS	ined in IEC61249-2-21.	. (See	
P7.13 Elect P7.14 All c P7.15 All n Not P7.16 Flar Mar Not P7.17 Alt. Che TBE Che ISO P7.18 Alt. Flar con Flar Che P7.18 Alt. Flar Co 1. C	ectrical cover/h printed te B2) me reta irking: >	able insulation materials of signal cable iusing plastic parts >25g are free from c circuit boards (without components) >2 ded plastic parts >25g in covers / housi	s are PVC free chlorine and bromine. 25g are halogen free. As def ings are marked according IS		. (See	
P7.14 All of P7.15 All Not P7.16 Flar Mar P7.17 Alt. Che TBE Alt. Che ISO P7.18 Alt. Flar con Co 1. C 2. C	cover/h printed te B2) me reta irking: >	circuit boards (without components) >2 ded plastic parts >25g in covers / housi	chlorine and bromine. 25g are halogen free. As def ings are marked according IS		. (See	
P7.15 All (Not P7.16 Flar P7.17 Alt. Che TBE Alt. Che ISO P7.18 Alt. Flar con Co 1. C 2. C	printed te B2) ime reta irking: >	circuit boards (without components) >2 ded plastic parts >25g in covers / housi	25g are halogen free. As def ings are marked according IS		. (See 🛛	
P7.16 Flar Mar P7.17 Alt. Che TBE Alt. Che ISO P7.18 Alt. Flar con Co 1. C 2. C	ime reta irking: > . 1			SO 1043-4:		
P7.17 Alt. Che TBE Alt. Che ISO P7.18 Alt. Flar con Co 1. C 2. C	. 1		40)			
Che ISO P7.18 Alt. Flar con Co 1. Co 2. C		becifications of flame retardants in print ditive), TBBPA (reactive), Othe	ed circuit boards >25g (withc			
Flar con Co 1. C 2. C	emical D 1043-	pecifications of flame retardants in print : <i>FR(40)</i>	ed circuit boards (without co	mponents) >25g accord	ling 🔀	
1. C 2. C	ime re	rded plastic parts >25g contain the	e following flame retardant	substances/preparatio	ons in 🔀	
3. C Alt.	Chemic Chemic Chemic	t: No legal limits exist, this is a n name: <i>Phosphorus compounds</i> , CA name: , CAS #: name: , CAS #:				
Che FR(emical (40)	pecifications of flame retardants in plas				
R40	0, R46,	s >25g are free from flame retardant su R48, R50, R51, R53, R60, R61 and any	combination of these (See N		5, 🔀	
		stic parts' weight >25g, recycled materia				
P7.22 Ligh	ht sour	stic parts' weight >25g, biobased materi es are free from mercury s used specify: Number of lamps:	and max. mercury content	per lamp: mg		
			· · · · · · · · · · · · · · · · · · ·			
P8.1* Bat	tteries					
P8.2 Batt	tteries	mical composition: <i>Lithium Ion / Lithiu</i>	ım Manganese Dioxide	· · · · · ·		

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	20H5, 20H6, 20H7		
Issue date *	2016-07-072015-07-07	Logo	Lenovo

Product environmental a	ttributes - Market	requirements (o	continued)	Requirement		
Item				Yes No	n.a.	
P9 Energy consump			umptions are re-	aartadi Saa D11		
	e following power leve		-		r —	
Energy mode *Power level at 100 V ACPower level at 115 V ACPower level at 230 V		Power level at 230 V AC	t Reference / Standard for energy modes and test method *			
Peak (On-max)	90 W	90 W	90 W	Full load		
Category I1						
Short Idle State - WOL Enabled	7.22 W	7.27 W	7.21 W	Use for ENERGY STAR V6 registration (P _{idie})		
Long Idle State - WOL Enabled	5.41 W	5.32 W	5.31 W	Use for ENERGY STAR V6 registration (P _{idle})		
Sleep (S3) - WOL Enabled 0.81 W 0.80 W 0.83 W Use for ENER			Use for ENERGY STAR V6 registration(P _{sleep})			
Off (S5) - WOL Enabled 0.40 W 0.40 W 0.42 W Use for ENERGY STAR V6 registr			Use for ENERGY STAR V6 registration(Poti)			
ETEC * Annual Energy Consumption	27.03 kWh/year	27.09 kWh/year	27.11 kWh/year	$E_{TEC} = (8760/1000) \times (P_{off} \times 0.25 + P_{sleep} \times 0.35 + P_{long_ldle} \times 0.10 + P_{short_ldle} \times 0.30)$		
Category I2	- I	1			1	
Short Idle State - WOL Enab	led 6.58 W	7.04 W	6.65 W	Use for ENERGY STAR V6 registration (P _{idle})		
Long Idle State - WOL Enabl		4.79 W	5.01 W	Use for ENERGY STAR V6 registration (P _{idle})	⊢	
Sleep (S3) - WOL Enabled	0.76 W	0.77 W	0.82 W	Use for ENERGY STAR V6 registration(P _{sleen})		
Off (S5) - WOL Enabled 0.70 W Off (S5) - WOL Enabled 0.42 W		0.42 W	0.47 W	Use for ENERGY STAR V6 registration(P _{off})		
EPS No-load		-				
	0.07 W	0.08 W	0.12 W			
PTEC * Typical Energy Consumption	2.98 W	3.11 W	3.04 W			
TEC * Typical Energy Consumption	0.48 kWh/week	0.50 kWh/week	0.49 kWh/week			
ETEC * Annual Energy Consumption	24.93 kWh/year	25.98 kWh/year	25.41 kWh/year	$E_{TEC} = (8760/1000) \times (P_{off} \times 0.25 + P_{sleep} \times 0.35 + P_{long_{idle}} \times 0.10 + P_{short_{idle}} \times 0.30)$		
	Pert: Off Mode(S	5) - WOL Enabled:	P _{eleon} : Sleep Mode	(S3) - WOL Enabled; P _{idle} : Idle State - WOL Enabled		
Display resolution* : 2.0736			Sieep			
Print Speed * : In	nages per minute				\boxtimes	
Default time to enter energy sa	•	<u> </u>				
	the energy save funct		th the product			
P9.3* The product meet	s the energy requirem version: Version 6.1	ents of the followi	•	gram/s:		
Others specify:		110	and category.		H	
P10 Emissions						
	- Declared according t	to ISO 9296	Declared			
P10.1 Mode	Mode description	cription		Declared A-weighted sound pressure level L_{pAm} (dB)		
			sound power level L_{WAd} (
				or Desk side (only if product is not operator attended)		
Idle	* HDD:Idle		* 2.9	20	니닏	
Operation	* HDD: Operating		* 3.3	25	IЦ	
Other mode	ODD operating		4.7	36		
	ng to: 🔀 ISO7779 🗌 Other	(only if not cove		with L _{pAm} measurement distance m)		
P10.2 The product meets	s the acoustic noise re	equirements of the	following volunt	ary program/s:	\boxtimes	

Issue dat	e* 2016-07-072016-07-07	Logo	Lenovo	
Product	environmental attributes - Market requirements (continued)		Require	ment me
Item			Yes	No n.a
	Chemical emissions from printing products			
P10.3*	Test performed according to ECMA-328 (ISO/IEC 28360) standard 🗌, other	r specify:		
P10.4	Typical emission rate (print phase) is (mg/h):			X
	Dust Ozone Styrene Benzene TV	/OC		
P10.5	Chemical emission requirements of the following voluntary program/s	are met for :		
	Dust Ozone Styrene Benzene	TVOC		
	Electromagnetic emissions			
P10.6	Computer display meets the requirement for low frequency electromagnetic fi	fields of the following volu	intary 🔀	
	program/s: JEITA-ITR (2pin adapter only)/MPR-II (3pin adapter only)			
P11	Consumable materials for printing products			
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if r			
P11.2*	Paper containing post-consumer recycled fibers can be used, provided th EN12281.	hat it meets the require	nents of	
P11.3*	2-sided (duplex) printing/copying is an integrated product function.			
P12	Ergonomics for computing products			
P12.1*	The display meets the ergonomic requirements of ISO 9241-307 for visual display	splay technologies.		
P12.2*	The physical input device meets the requirements of ISO 9995 and ISO 9241	1-410.	\square	
P13	Packaging and documentation			
P13.1*		nt (kg): 0.426		
	· · · · · ·	nt (kg): 0.216		
	Product packaging material type(s): Others (Plastic Bag) weight (kg): 0.025	,		
P13.2*	Product plastic packaging is free from PVC.		\square	
P13.3*	Specify media for user and product documentation (tick box):			
	Electronic 🔀, Paper 🔀, Other 🗌			
P13.4*	For paper user and product documentation, please specify contained percent	tage of post-consumer re	cycled	
	fiber: 70% (only for Japan)			
P14	Additional information (See Note B4)			
	NOTE: Supplier makes no representations, guarantees, assurances or warra information contained in this document. All information provided by supplier in knowledge available at the time of completion, and supplier shall have no obl provided here is approximate and provided for informational purposes only. S information.	n this document is provid ligation to update such in See a Lenovo Account Re	ed based on supp formation. The in	plier's formation
P9	See Energy Star Qualified Notebooks & Tablet Computers for the latest	information:		

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19

Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	ThinkPad Edge E570/570c	Logo
Model Number	20H5, 20H6, 20H7	Lenovo
Issue Date	2016-07-07	
Additional information		

P7.1.1	Product environmental attributes					
(d)	year of manufacture:	2016				
(e)	E TEC value (kWh) per ErP Lot 3 Category and capability adjustments applied when all di disabled and if the system is tested with switchable graphics mode with UMA driving the dis					
	Category (according to ErP Lot 3): A Etec: 19.5					
f)	E TEC value (kWh) per ErP Lot 3 Category and capability adjustments applied when all dis enabled:	screte graphics cards (dGfx) are				
	Category (according to ErP Lot 3): C Etec: 16.97					
(g)	idle state power demand (Watts);	A:6.18 / B:5.26				
(h)	sleep mode power demand (Watts);	A:0.77 / B:0.76				
(i)	sleep mode with WOL enabled power demand (Watts) (where enabled);	A:0.78 / B:0.77				
j)	off mode power demand (Watts); A:0.49 / B:0.47					
k)	off mode with WOL enabled power demand (Watts) (where enabled);	A:0.49 / B:0.47				
(I)	internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if approximately the term of term o	oplicable):				
	10% 20% 50% 100% Average					
(m)	external power supply efficiency (if applicable):					
	10% 20% 50% 100% Average ;					
	or level: V/					
(0)	the minimum number of loading cycles that the batteries can withstand (applies only to note	book computers): 500 cycles				
(p-1)	the measurement methodology used to determine information mentioned in points (I) – internal PSU efficiency:					
(p-2)	the measurement methodology used to determine information mentioned in points (m) – external PSU efficiency: EPA "Test Method for Calculating the Energy Efficiency of Single-Voltage External AC-DC and AC-AC Power Supplies" dated August 11, 2004					
(p-3)	the measurement methodology used to determine information mentioned in points (o batteries:	b) – loadingcycles				
	IEC 61960 measurement methodology					
p-4)	the measurement methodology used to determine information mentioned in maximum, idle,	sleep, off mode				

	lafined in Daint DO 1	in the D	reduct IT Fee Declaration			
power as defined in Point P9.1 in the Product IT Eco Declaration:						
IEC 62623 / IEC EN50564:2011 measurement methodology						
(q) sequence	sequence of steps for achieving a stable condition with respect to power demand::					
IEC 62623 / IEC EN50564:2011 measurement methodology						
(r) description of how sleep and/or off mode was selected or programmed:						
By selecting sleep and/or off mode thru Windows operating system						
(s) sequence off mode:	sequence of events required to reach the mode where the equipment automatically changes to sleep and/or off mode:					
refer to power management, 20mins automatically reaches sleep mode						
(t) the duration	on of idle state con	dition h	afore the computer automatically reaches clean mode, or another			
(t) the duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes): 30						
(u) the length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes): NA						
(v) the length of time before the display sleep mode is set to activate after user inactivity (in minutes): 10						
(w) information on the energy-saving potential of power management functionality:						
refer to user manual						
(x) user information on how to enable the power management functionality:						
refer to user manual						
(z) test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the						
electricity supply system, - information and documentation on the instrumentation, set-up and circuits used						
for electrical testing:						
230V, 50GHz-<0.5%-ENERGY STAR Test Method for Computers, Rev. Aug-2010						
Addition Notebook B	attery Information:					
Yes	No	n/a	This notebook computer is operated by battery/ies that can be accessed and a non-professional user.	replaced by		
(Battery not user replaceable)	(Battery user replaceable)		The battery[ies] in this product can be easily replaced	by users		
			themselves			
	\boxtimes					
	•					

Additional information						