



Annex B2 - Product environmental attributes Computers and computer monitors

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lenovo	Logo	
Company name *	Lenovo		
Contact information * e-mail address	Lenovo Global Environmental Affairs Alvin L Carter alcarter@lenovo.com		Lenovo
Internet site *	https://www.lenovo.com/us/en/sustainability-resources/		
Additional information	The latest version of this document can be found at: http://www.lenovo.com/ecodeclaration		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.					
Type of product *	Notebook Computer				
Commercial name *	Lenovo 300w Yoga Gen 4				
Model number *	82VM,82VN				
Issue date *	2023-03-13				
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other				
Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products

Model number *	82VM,82VN	Logo	1
Issue date *	2023-03-13		Lenovo

P1.1* Products do comply with current European RoHS Directive. (See legal reference and NOTE B1) P1.2* Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value. P1.3* Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value. P1.3* Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochiorofluorocarbons (HCFC), Halons, carbontetrachioride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values. P1.4* Products do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated terphenyl (PCT) in preparations (see legal reference). P1.5* Products do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference). P1.6* Parts with direct and prolonged skin contact do not release nickle in concentrations above 0,5 µg/cm²/week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:2011-5. P1.7* REACH Article 33 information about substances in articles is available at (add URL or mail contact): https://www.lenovo.com/us/en/Lenovo-REACH-SVHC-Disclosure P2.1* If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal symbol. Information on proper disposal is provided in user manual. (See legal reference) P2.2* Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal reference) P2.3* Batteries and accumulators are readily removable. (See legal reference) P2.4* Documentation includes the number of cycles the (secondary) battery can withstand. (See legal reference) P3.5* When internal batteries of a notebook computer cannot be "accessed and replaced by a nonprofessional user", the related text is present and legible on	quirement	met
 P1.1* Products do comply with current European RoHS Directive. (See legal reference and NOTE B1) P1.2* Products do not contain Asbestos (see legal reference).	Yes No	n.a.
P1.2* Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value. P1.3* Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorocarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values. P1.4* Products do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated terphenyl (PCT) in preparations (see legal reference). P1.5* Products do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference). P1.6* Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm²/week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:2011-5. P1.7* REACH Article 33 information about substances in articles is available at (add URL or mail contact): https://www.lenovo.com/us/en/Lenovo-REACH-SVHC-Disclosure P2.1* If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal symbol. Information on proper disposal is provided in user manual. (See legal reference) P2.2* Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal reference) P2.3* Batteries and accumulators are readily removable. (See legal reference) P2.4* Documentation includes the number of cycles the (secondary) battery can withstand. (See legal reference) P2.5* When internal batteries of a notebook computer cannot be "accessed and replaced by a nonprofessional user", the related text is present and legible on the external packaging (see legal reference). The product see E-marked to show conformance with applicable legal replaced by a nonprofessional user", the related text is present and legible on the external packaging (s		
P1.3* Products do not contain Ozone Depleting Substances: Chlorifluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorocarbons (HGFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values. P1.4* Products do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated terphenyl (PCT) in preparations (see legal reference). Products do not contain more than; 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference). P1.6* Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm²/week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:2011-5. REACH Article 33 information about substances in articles is available at (add URL or mail contact): https://www.lenovo.com/us/en/Lenovo-REACH-SVHC-Disclosure P2.1* If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal symbol. Information on proper disposal is provided in user manual. (See legal reference) P2.2* Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal reference) P2.3* Batteries and accumulators are readily removable. (See legal reference) P2.4* Documentation includes the number of cycles the (secondary) battery can withstand. (See legal reference) P2.4* Documentation includes the number of cycles the (secondary) battery can withstand. (See legal reference) P2.5* When internal batteries of a notebook computer cannot be *accessed and replaced by a nonprofessional user", the related text is present and legible on the external packaging (see legal reference). The product s CE-marked to show conformance with applicable legal requirements (see legal reference). P6.5.1* The product complies with the applicable Eco design requirements for ene		
hydropromofluorocarbons (HBFC), hydrochlorofluorocarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values. P1.4* Products do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated terphenyl (PCT) in preparations (see legal reference). Products do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference). P1.6* Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm²/week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:2011-5. REACH Article 33 information about substances in articles is available at (add URL or mail contact): https://www.lenovo.com/us/en/Lenovo-REACH-SVHC-Disclosure P2.8* Batteries P2.1* If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal symbol. Information on proper disposal is provided in user manual. (See legal reference) P2.2* Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal reference) P2.4* Documentation includes the number of cycles the (secondary) battery can withstand. (See legal reference) P2.5* When internal batteries of a notebook computer cannot be "accessed and replaced by a nonprofessional user", the related text is present and legible on the external packaging (see legal reference) P3.1* The product is CE-marked to show conformance with applicable legal requirements (see legal reference). The Declaration of Conformity can be requested at (add link or e-mail address): https://www.lenovo.com/us/en/compliance/eu/cof for UK P3.2* The product complies with the applicable Eco design requirements for energy-related products, (see legal reference). P65. Product packaging P65. Product packaging and packaging components do no		
terphenyl (PCT) in preparations (see legal reference). P1.5* Products do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference). Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm²/week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:2011-5. REACH Article 33 information about substances in articles is available at (add URL or mail contact): https://www.lenovo.com/us/en/Lenovo-REACH-SVHC_Disclosure P2. Batteries P2.1* If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal symbol. Information on proper disposal is provided in user manual. (See legal reference) P2.2.* Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal reference) P2.3* Batteries and accumulators are readily removable. (See legal reference) P2.4* Documentation includes the number of cycles the (secondary) battery can withstand. (See legal reference) P2.5* When internal batteries of a notebook computer cannot be "accessed and replaced by a nonprofessional user", the related text is present and legible on the external packaging (see legal reference) P3.1* The product is CE-marked to show conformance with applicable legal requirements (see legal reference). The Declaration of Conformity can be requested at (add link or e-mail address): https://www.lenovo.com/us/en/compliance/eu-doc for EU; https://www.lenovo.com/us/en/compliance/eu-doc for UK P3.2* The product complies with the applicable Eco design requirements for energy-related products, (see legal reference). Required information is; given in item P15 or added to this document, available at (add URL): http://www.lenovo.com/ecodeclaration P5.2* Product packaging P5.1* Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium and hexaval		
chain containing at least 48% per mass of chlorine in the SCCP (see legal reference). P1.6* Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm²/week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:2011-5. P1.7* REACH Article 33 information about substances in articles is available at (add URL or mail contact): https://www.lenovo.com/us/en/Lenovo-REACH-SVHC-Disclosure P2. Batteries P2.1* If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal symbol. Information on proper disposal is provided in user manual. (See legal reference) P2.2* Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal reference) P2.3* Batteries and accumulators are readily removable. (See legal reference) P2.4* Documentation includes the number of cycles the (secondary) battery can withstand. (See legal reference) P2.5* When internal batteries of a notebook computer cannot be "accessed and replaced by a nonprofessional user", the related text is present and legible on the external packaging (see legal reference) P3.1* The product is CE-marked to show conformance with applicable legal requirements (see legal reference). The Declaration of Conformity can be requested at (add link or e-mail address): https://www.lenovo.com/us/en/compliance/eu-doc for EU; https://www.lenovo.com/us/en/compliance/eu-doc for UK P3.2* The product complies with the applicable Eco design requirements for energy-related products, (see legal reference). Required information is; it is available at (add URL): http://www.lenovo.com/ecodeclaration P5.4* Product packaging P5.1* Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium and hexavalent chromium by weight of these together. P5.2* The packaging are marked with abbreviations and numbers indicating the nature of the material(s) used (see legal reference).		
(see legal reference). Comment: Max limit in legal reference when tested according to EN1811:2011-5. P1.7* REACH Article 33 information about substances in articles is available at (add URL or mail contact):		
P1.7* REACH Article 33 information about substances in articles is available at (add URL or mail contact):		
P2.1* If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal symbol. Information on proper disposal is provided in user manual. (See legal reference) P2.2* Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal reference) P2.3* Batteries and accumulators are readily removable. (See legal reference) P2.4* Documentation includes the number of cycles the (secondary) battery can withstand. (See legal reference) P2.5* When internal batteries of a notebook computer cannot be "accessed and replaced by a nonprofessional user", the related text is present and legible on the external packaging (see legal reference) P3. Conformity verification & Eco design (ErP) P3.1* The product is CE-marked to show conformance with applicable legal requirements (see legal reference). The Declaration of Conformity can be requested at (add link or e-mail address): https://www.lenovo.com/us/en/compliance/ut-doc for EU; https://www.lenovo.com/us/en/compliance/ut-doc for UK P3.2* The product complies with the applicable Eco design requirements for energy-related products, (see legal reference). Required information is; given in item P15 or added to this document, available at (add URL): http://www.lenovo.com/ecodeclaration P4. Product packaging P5.1* Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium and hexavalent chromium by weight of these together. P5.2* The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s) used (see legal reference).		
symbol. Information on proper disposal is provided in user manual. (See legal reference) P2.2* Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal reference) P2.3* Batteries and accumulators are readily removable. (See legal reference) P2.4* Documentation includes the number of cycles the (secondary) battery can withstand. (See legal reference) P2.5* When internal batteries of a notebook computer cannot be "accessed and replaced by a nonprofessional user", the related text is present and legible on the external packaging (see legal reference) P3.1* The product is CE-marked to show conformance with applicable legal requirements (see legal reference). The Declaration of Conformity can be requested at (add link or e-mail address): https://www.lenovo.com/us/en/compliance/eu-doc for EU; https://www.lenovo.com/us/en/compliance/uk-doc for UK P3.2* The product complies with the applicable Eco design requirements for energy-related products, (see legal reference). Required information is; given in item P15 or added to this document, available at (add URL): http://www.lenovo.com/ecodeclaration P5 Product packaging P5.1* Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium and hexavalent chromium by weight of these together. P5.2* The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s) used (see legal reference).		
P2.3* Batteries and accumulators are readily removable. (See legal reference) P2.4* Documentation includes the number of cycles the (secondary) battery can withstand. (See legal reference) P2.5* When internal batteries of a notebook computer cannot be "accessed and replaced by a nonprofessional user", the related text is present and legible on the external packaging (see legal reference) P3 Conformity verification & Eco design (ErP) P3.1* The product is CE-marked to show conformance with applicable legal requirements (see legal reference). The Declaration of Conformity can be requested at (add link or e-mail address): https://www.lenovo.com/us/en/compliance/eu-doc for EU; https://www.lenovo.com/us/en/compliance/uk-doc for UK P3.2* The product complies with the applicable Eco design requirements for energy-related products, (see legal reference). Required information is;		
P2.4* Documentation includes the number of cycles the (secondary) battery can withstand. (See legal reference) P2.5* When internal batteries of a notebook computer cannot be "accessed and replaced by a nonprofessional user", the related text is present and legible on the external packaging (see legal reference) P3		
P2.5* When internal batteries of a notebook computer cannot be "accessed and replaced by a nonprofessional user", the related text is present and legible on the external packaging (see legal reference) P3. Conformity verification & Eco design (ErP) P3.1* The product is CE-marked to show conformance with applicable legal requirements (see legal reference). The Declaration of Conformity can be requested at (add link or e-mail address): https://www.lenovo.com/us/en/compliance/eu-doc for EU; https://www.lenovo.com/us/en/compliance/uk-doc for UK P3.2* The product complies with the applicable Eco design requirements for energy-related products, (see legal reference). Required information is; given in item P15 or added to this document, available at (add URL): http://www.lenovo.com/ecodeclaration P5. Product packaging P5.1* Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium and hexavalent chromium by weight of these together. P5.2* The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s) used (see legal reference).		
P3 Conformity verification & Eco design (ErP) P3.1* The product is CE-marked to show conformance with applicable legal requirements (see legal reference). The Declaration of Conformity can be requested at (add link or e-mail address): https://www.lenovo.com/us/en/compliance/eu-doc for EU; https://www.lenovo.com/us/en/compliance/uk-doc for UK P3.2* The product complies with the applicable Eco design requirements for energy-related products, (see legal reference). Required information is;		
P3.1* The product is CE-marked to show conformance with applicable legal requirements (see legal reference). The Declaration of Conformity can be requested at (add link or e-mail address): https://www.lenovo.com/us/en/compliance/eu-doc for EU; https://www.lenovo.com/us/en/compliance/uk-doc for UK P3.2* The product complies with the applicable Eco design requirements for energy-related products, (see legal reference). Required information is;		
The Declaration of Conformity can be requested at (add link or e-mail address): https://www.lenovo.com/us/en/compliance/eu-doc for EU; https://www.lenovo.com/us/en/compliance/uk-doc for UK P3.2* The product complies with the applicable Eco design requirements for energy-related products, (see legal reference). Required information is;		
P3.2* The product complies with the applicable Eco design requirements for energy-related products, (see legal reference). Required information is; given in item P15 or added to this document, available at (add URL): http://www.lenovo.com/ecodeclaration P5		
Required information is; given in item P15 or added to this document, available at (add URL): http://www.lenovo.com/ecodeclaration P5 Product packaging P5.1* Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium and hexavalent chromium by weight of these together. P5.2* The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s) used (see legal reference).		
P5.1* Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium and hexavalent chromium by weight of these together. P5.2* The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s) used (see legal reference).		
hexavalent chromium by weight of these together. P5.2* The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s) used (see legal reference).		
P5.2* The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s) used (see legal reference).		
P5.3* The product packaging material is free from ozone depleting substances as specified in the Montreal Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.		
P6 Treatment information		
P6.1* Information for recyclers/treatment facilities is available (https://lenovo.com/recycling).	\square	

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number *	82VM,82VN	Logo	1
Issue date *	2023-03-13		Lenovo.

Environmental conscious design membadatory foli lin. Additional information regarding each item may be found under P14.	Product	environmental attributes - Market requirements (See General NOTE GN below)	_		
P7.1° Parts that have to be treated separately are easily separable P7.2° Plastic materials in covers/housing have no surface coating. P7.3° Plastic parts > 100 g consist of one material or of easily separable materials. P7.4° Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P7.5° Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P7.5° Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6° Labels are easily separable, (This requirement does not apply to safety/regulatory labels). P7.6° Upgrading can be done e.g. with processor, memory, cards or drives P7.8° Upgrading can be done using commonly available tools P7.8° Upgrading can be done using commonly available tools P7.8° Spare parts are available after end of production for: 5 years P7.10° Service is available after end of production for: 5 years P7.11° Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: PC/ABS Material type: Material type: Material type: P7.11° Insulation materials of external electrical cables are PVC free. P7.13° Insulation materials of external electrical cables are PVC free. P7.14° External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15° Printed circuit boards, PCBS (without components) are low halogen: all PCBs > 25 g (without components): P7.17° P					
Disassembly, recycling			Yes	No	n.a.
P7.1º Parts that have to be treated separately are easily separable	Ρ/				
P7.3* Plastic parts > 100 g consist of one material or of easily separable materials. P7.4* Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done e.g. with processor, memory, cards or drives P7.9* Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: PC/ABS P7.12 Insulation materials of internal electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0.1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyviryl chloride or 0.3% weight (3000 ppm) bromine and 0.3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g \times are low halogen as defined in IEC 61249-2-21. P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according to ISO 1043-4: Marking: FR(40) P7.17 Alt. 1; Chemical specifications of flame retardants in printed circuit boards (without components): TBBPA (additive) . TBBPA (reactive) . (See NOTE B3), Other; chemical name: DOPO, CAS #: 35948-25-5 Alt. 2; Chemical specifications of flame retardants in plastic parts > 25 g accor	P7.1*		\boxtimes		
P7.4* Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.9* Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.10* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: Material and substance requirements Material type: P7.11 Insulation materials of external electrical cables are PVC free. P7.12 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low Alt. 1; Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: DOPO, CAS #: 35948-	P7.2*	· · · · · · · · · · · · · · · · · · ·		\boxtimes	
P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels). Product lifetime P7.7 Upgrading can be done e.g. with processor, memory, cards or drives P7.8 Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11 Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: PC/ABS Material and substance requirements P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-221. P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according to ISO 1043-4: Marking: FR(40) Alt. 1: Chemical specifications of flame retardants in printed circuit boards (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: DOPO, CAS #: 35948-25-5 Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: 1	P7.3*	Plastic parts > 100 g consist of one material or of easily separable materials.	\boxtimes		
P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). Product lifetime P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: PC/ABS Material type: Material type: Material type: Material type: Insulation materials of external electrical cables are PVC free. P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low lalogen as defined in IEC 61249-2-2-1. P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according to ISO 1043-4: Marking: FR(40) P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: DOPO, CAS #: 35948-25-5 Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: " Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: " 1. Chemical name: CAS #: " 3. Chemical name: CAS #: " 3. Chemical name: CAS #: " 4. Chemical name: CAS #: " 3. Chemical name: CAS #: " 4. Chemical pareit parts > 25 g, flame retardant subs	P7.4*	Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.	\boxtimes		
Pr.17 Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: PC/ABS Material type: Material type: P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyviny chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g \times are low halogen as defined in IEC 61249-2-21. P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according to ISO 1043-4: Marking: FR(40) P7.17 Alt. 1; Chemical specifications of flame retardants in printed circuit boards (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: DOPO, CAS #: 35948-25-5 Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: Alt. 1; Theme retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: CAS #: 2. Chemical name: CAS #: 3. Chemical name: CAS #: 3. Chemical name: CAS #: 3. Chemical name: CAS #: 4. Chemical name: CAS #: 3. Chemical name: CAS #: 3. Chemical name: CAS #: 4. Chemical name: CAS #: 3. Chemical name: CAS #: 4. Chemical	P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.	\boxtimes		
P7.7° Upgrading can be done e.g. with processor, memory, cards or drives	P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	\boxtimes		
P7.8' Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.11' Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: Material type: Material type: PC/ABS Material type: Material type: Material type: Material type: PC/ABS Material type: Material type: Material type: Material type: P7.11 Insulation materials of internal electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according to ISO 1043-4: Marking: FR(40) P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other, chemical name: DOPO, CAS #: 35948-25-5 Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: 3. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4. L2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard		Product lifetime			
P7.9 Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years	P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	\boxtimes		
P7.10 Service is available after end of production for: 5 years	_	10 0 ,	\boxtimes		
Material and substance requirements P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: PC/ABS	P7.9	Spare parts are available after end of production for: 5 years			
P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: PC/ABS Material type: Material type: PF.12 Insulation materials of external electrical cables are PVC free.	P7.10	Service is available after end of production for: 5 years			
Material type: PC/ABS Material type: Material type: P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according to ISO 1043-4: Marking: FR(40) P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: DOPO, CAS #: 35948- 25-5 Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements:					
P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according to ISO 1043-4: Marking: FR(40) P7.17 Alt. 1; Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: DOPO, CAS #: 35948-25-5 Alt. 2; Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1; Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2; Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements:	P7.11*				
P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyviny chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according to ISO 1043-4: Marking: FR(40) P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: DOPO, CAS #: 35948-25-5 Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements:					
P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according to ISO 1043-4: Marking: FR(40) P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: DOPO, CAS #: 35948-25-5 Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements:				$\underline{\underline{X}}$	
weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according to ISO 1043-4: Marking: FR(40) P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: DOPO, CAS #: 35948-25-5 Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements:					
P7.15 Printed circuit boards, PCBs (without components) are low halogen: all □ PCBs > 25 g ☑ are low □ □ halogen as defined in IEC 61249-2-21. P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according to ISO 1043-4: ☑ □ Marking: FR(40) P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): □ TBBPA (additive) □, TBBPA (reactive) □ (See NOTE B3), Other; chemical name: DOPO, CAS #: 35948- □ □ according ISO 1043-4: P7.18 Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g □ □ □ according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: □ Chemical name: , CAS #: □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □	P7.14		\boxtimes		
P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according to ISO 1043-4: Marking: FR(40) P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: DOPO, CAS #: 35948-25-5 Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements:					
P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according to ISO 1043-4: Marking: FR(40) P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other; chemical name: DOPO, CAS #: 35948- 25-5 Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements:	P7.15	Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low	\boxtimes		
Marking: FR(40) P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other; chemical name: DOPO, CAS #: 35948- 25-5 Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements:	D7 16				
TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other; chemical name: DOPO, CAS #: 35948		Marking: FR(40)		Ш	
25-5 Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements:	P7.17				
Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g P7.18		, , , ,	- 🖂	Ш	
according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements:		20-0			
P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements:					
1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements:	P7.18				
2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements:					
3. Chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements:					
Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements:					
P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements:			\square		
assigned the following Risk phrases; and Hazard statements:	D7 10				\dashv
	F 1.18				

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

Model number *	82VM,82VN	Logo	1
Issue date *	2023-03-13		Lenovo

Product environmental attributes - Market requirements (continued)					Requir	eme	nt met	
Item						Yes	No	n.a.
	Material and subs	tance requirements	(continued)					
P7.20*	Postconsumer recy	cled plastic material o	content is used in the p	roduct (See NOTE B6) :			
	a) Of total plastic	parts' weight > 25 g,			ontent (calculated as a			
	percentage of total plastic by weight) is 10.58%. or							
P7.21*	b) The weight of recycled material is 52.8 g. P7.21* Biobased plastic material content is used in the product (See NOTE B7):							
If YES; at least one of the two alternatives below shall be answered;								
a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic by weight) is								
	or b) The weight of	the biobased plastic r	material is g.					
P7.22*	Light sources are f	ree from mercury, i.e.	less than 0,1 mg/lamp		or lown; ma			
P7.23*		specify: Number of lar	nps: and maxim e total mercury content	num mercury content p		\square		\square
P8	Batteries	arr integral display, tri	c total mercury content	t iii tiic iiitegiated disp	ay. v.v mg			
P8.1*		omposition: Lithium i	on					
P9		· .	<u> </u>					
P9.1		tion (See NOTE B8)	ls or energy consumpti	ons are reported:				
_	•				In ((0) 1 1	•		
Energy mo	ode *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference/Standard modes and test meth		y	Ш
Peak (On-	-Max)	65 W	65 W	65 W	Full Load			
Device Ca								
Enabled (3.792 W	3.240 W	3.732 W	ENERGY STAR Con			
Long Idle Enabled (State – WOL P _{long_idle})	1.344 W	1.416 W	1.512 W	ENERGY STAR Con	nputers	V8.0	
Sleep (S3 (P _{Sleep})) – WOL Disabled	0.408 W	0.540 W	0.432 W	ENERGY STAR Con	nputers	V8.0	
Off Mode Disabled	(S5) – WOL (P _{off})	0.384 W	0.384 W	0.408 W	ENERGY STAR Con	nputers	V8.0	
PTEC * Typical En	ergy Consumption	W	W	W				
ETEC * Annual En	ETEC * Annual Energy Consumption 11.34 kWh/year 10.69 kWh/year 11.43 kWh/year $E_{TEC} = (8760/1000) \times P_{Sleep} \times 0.05 + P_{long_ld} \times 0.35$							
External Power Supply Efficiency Level (International Efficiency Marking Protocol) *: VI International Efficiency								
Protocol (IEMP) for External Power Supplies								
Display resolution * : 1.049 megapixels 1366*768								
Default tim	ne to enter energy sa				ENERGY STAR Con	nputers	V8.0	
P9.2*			on is provided with the	product.		\boxtimes		
P9.3	Energy efficiency of	lass (monitors only):						

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available;

see http://www.ecma-international.org/publications/standards/Ecma-370.htm.

Model number *	82VM,82VN	Logo	1
Issue date *	2023-03-13		Lenovo

Product	environmental	attributes - Market requirements (continued)	equire	ment	met	
Item		,	Yes	No	n.a.	
P10	Emissions					
	Noise emission	n – Declared according to ISO 9296 (See NOTE B9)				
P10.1	Mode		er level,			
İ	Idle	* Idle Mode * 1.7			\neg	
	Operation	* Operating (CPU) * 1.7				
	Other Mode	Declared A-weighted sound pressure level (dB) NA (operator position desktop – idle)				
	Other mode Declared A-weighted sound pressure level (dB) L _{pAm} NA (operator position desktop – operating-HDD/SSD) NA (operator position desktop – operating-CPU)					
	Measured acco	rding to: SO 7779 ECMA-74 Other (only if not covered by ECMA-74)				
	Electromagnet	/				
P10.4	Computer displa	ay meets the requirement for low frequency electromagnetic fields of the following voluntary PR-II(3 pin AC adapter only)				
P12		or computing products				
P12.1*	The display me	ets the ergonomic requirements of ISO 9241-307 for visual display technologies.	\boxtimes			
P12.2*	The physical in	put device meets the requirements of ISO 9995 and ISO 9241-410.	X	Ħ	Ħ	
P13	Packaging and	d documentation				
P13.1*	* Product packaging material type(s): Cardboard Product packaging material type(s): Cardboard Product packaging material type(s): EPE Product packaging material type(s): EPE Product packaging material type(s): EPE weight (kg): 0.0213 weight (kg): 0.0213					
P13.2*	Product packaging material type(s): LDPE weight (kg): 0.0136 Product plastic primary packaging is free from PVC.					
P13.3*	For product primary corrugated fiberboard packaging, specify the contained percentage of minimum post- consumer recovered fiber content: 80 %					
P13.4*						
P13.5		mplete this item if paper documentation used) ct documentation on paper media is chlorine-free: pecify:				
	Totally chlorine-	free	\boxtimes			
	Elemental chlorine-free					
	Processed chlo		Ш			
P14	Voluntary prog					
P14.1	The product me	eets the requirements of the following voluntary program(s):				
	ENERGY STAF Eco-label: <i>EPE</i>					
	Eco-label: TCO	Criteria version: 9.0 Date: 2023/04/20 Product category: Notebook				
P15	Additional info	ormation (See NOTE B10)				
P9	Energy consul	mption of computer products; description of the tested product configuration:				

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm.

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive)* * Specific exemptions apply for certain products and applications.	P1.1, P3.1
Regulation (EC) 1907/2006 (REACH Regulation), annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2006/66/EC (Battery and accumulators Directive), as amended.* * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2014/35/EU (Low Voltage Directive)	P3.1
Directive 2014/30/EU (EMC Directive)	P3.1
Directive 2014/53/EU (RE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Commission Regulation (EC) No 278/2009 of 6 April 2009 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for no-load condition electric power demand and average active efficiency of external power supplies	P3.1, P3.2, P9.1
COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers	P2.4, P2.5, P3.1, P3.2, P7.23, P9.1
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1
Implementing Regulation (EU) 2019/290 establishing the format for registration and reporting of producers of electrical and electronic equipment to the register.	
Commission Implementing Regulation 2017/699 establishing a common methodology for the calculation of the weight of electrical and electronic equipment (EEE) placed on the national market in each Member State and a common methodology for the calculation of the quantity of waste electrical and electronic equipment (WEEE) generated by weight in each Member State.	

Lenovo ErP Lot26 Information Sheet - Network Equipment -

As required by_

- Commission Regulation (EC) No 1275/2008 of 17 December 2008 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for standby and off-mode electric power consumption of electrical and electronic household equipment (ErP Lot 6)
- Commission Regulation (EU) No 801/2013 of 22 August 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for (ErP Lot 26).

Products scope of this sheet:

Notebook/Tablet Computer < 6 W Idle

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	Lenovo 300w Yoga Gen 4	Logo
Model Number	82VM,82VN	
Product Type	Notebook Computer with Idle Power < 6 W	Lenovo
Issue Date	2023-03-13	
Additional information		

	Product environmental attributes	
	year of manufacture:	2023
1	Network Standby Classification	LoNA Equipment
	Off Mode Power (Watts)	0.39 Watts
	Standby Mode	Watts
	Description of how to enable Network Standby Mode	Network Standby Mode is enabled at Shipment
	Description of how to manually enter Network Standby Mode	Press the Power Button once Click on the Power Button and choose Sleep
	Default Delay time to Network Standby Mode	5.0 minutes
	Reactivation Function from Network Standby Mode	Open Notebook, Press Keyboard or power button, activate USB

Network Port	Wired	Wireless	USB-A	USB-C	HDMI	BlueTooth	Other:		
	Ethernet	Ethernet							
Present in Product									
Activated at									
Shipment									
Active in Network Standby Mode									
Location of	N/A	N/A	Left and Righ	Left	Left	N/A	N/A		
Network Port	N/A	N/A	Left and ragin	Len	Len	N/A	N/A		
Network Port Maximum	GB/s	0.15 GB/s	GB/s	GB/s	GB/s	GB/s	GB/s		
Performance	GB/S	0.13 GB/S	GB/S	GB/S	GB/S	GB/S	GB/S		
Network Protocol		Wi-Fi 6; 802.11ax	USB 3.2 Gen 1	USB 3.2 Gen 2		BT5.2			
Network Standby	Watts	0.52Watts	Watts	Watts	Watts	Watts	Watts		
Mode Power Network									
Standby									
Power – All	0.52 Watts								
Active									
Active									
Connections Additional Informa									
Connections	onnecting to ar					User Manual			
Additional Informa Instructions on c	onnecting to ar			ss networks is inc 24.8 degree Celsi		User Manual			
Additional Informa Instructions on c	onnecting to an or measurements rature,	S,				User Manual			
Connections Additional Informa Instructions on c Test parameters for ambient temper	onnecting to an or measurements rature,	s, in Hz,		24.8 degree Celsi		User Manual			
Connections Additional Informa Instructions on c Test parameters for ambient temperatus voltage in V	onnecting to an or measurements rature, and frequency distortion of the documentation	in Hz, e electricity sup	ply system,	24.8 degree Celsi 230 V / 50 Hz	ius				
Connections Additional Informa Instructions on content temperature ambient temperature total harmonic conformation and	onnecting to are or measurements rature, rand frequency distortion of the documentation its used for elec-	in Hz, electricity sup n on the instructrical testing	ply system,	24.8 degree Celsi 230 V / 50 Hz <2%	ius				
Connections Additional Informa Instructions on a contract parameters for ambient temperature test voltage in Voltage in Voltage in Formation and set-up and circumset-up and ci	onnecting to are or measurements or measurements or and frequency distortion of the documentation its used for electroply efficiency (if Output Voltage	in Hz, e electricity sup n on the instruictrical testing f applicable)*: Output Current	ply system, mentation, Output Power	24.8 degree Celsi 230 V / 50 Hz <2% Power Meter: YO Average Active Efficiency	KOGAWA-W7	ad No L	ver		
Connections Additional Informa Instructions on Connections Test parameters for ambient temperates voltage in	onnecting to are or measurements rature, rand frequency distortion of the documentation its used for electory pply efficiency (if Output Voltage 20 V	in Hz, e electricity sup n on the instructrical testing f applicable)*: Output Current 2.25 A	ply system, mentation, Output Power 45 W	24.8 degree Celsi 230 V / 50 Hz <2% Power Meter: YO Average Active Efficiency 89%	KOGAWA-W7	7310 ad No L cy Po 0.02	ver 5 W		
Connections Additional Informa Instructions on Connections Test parameters for ambient temper test voltage in Voltage i	onnecting to are or measurements rature, rand frequency distortion of the documentation its used for elemonits used for elemonits used pply efficiency (if Output Voltage 20 V 20 V	in Hz, electricity sup n on the instructrical testing f applicable)*: Output Current 2.25 A 2.25 A	ply system, mentation, Output Power 45 W 45 W	24.8 degree Celsi 230 V / 50 Hz <2% Power Meter: YO Average Active Efficiency 89% 88%	**************************************	7310 ad No L cy Po 0.02 0.03	ver 5 W 3 W		
Connections Additional Informa Instructions on Connections Test parameters for ambient temperature test voltage in Volt	onnecting to are presented in the properties of	in Hz, e electricity sup n on the instructrical testing f applicable)*: Output Current 2.25 A 2.25 A 2.25 A	ply system, mentation, Output Power 45 W 45 W 45 W 45 W	24.8 degree Celsi 230 V / 50 Hz <2% Power Meter: YO Average Active Efficiency 89% 88% 89% 89%	## 10% Lo Efficien	ad No L cy Pov 0.02 0.00 0.01	ver 5 W 3 W 1 W 2 W		
Connections Additional Informal Instructions on a contraction of a contra	onnecting to are presented in the properties of	in Hz, electricity sup n on the instructrical testing fapplicable)*: Output Current 2.25 A 2.25 A 2.25 A 3.25 A	ply system, mentation, Output Power 45 W 45 W 45 W 45 W 65 W	24.8 degree Celsi 230 V / 50 Hz <2% Power Meter: YO Average Active Efficiency 89% 88% 89% 89% 90%	## 10% Lo Efficien	7310 ad No L cy Pov 0.02 0.03 0.01 0.01	Net		
Connections Additional Informa Instructions on a Instruction on a Ins	onnecting to are presented in the properties of	in Hz, e electricity sup n on the instructrical testing f applicable)*: Output Current 2.25 A 2.25 A 2.25 A 3.25 A 3.25 A	ply system, mentation, Output Power 45 W 45 W 45 W 45 W 65 W 65 W	24.8 degree Celsi 230 V / 50 Hz <2% Power Meter: YO Average Active Efficiency 89% 88% 89% 89% 89% 89%	### 10% Lo Efficien ### 89% ###	ad No L cy Pov 0.02 0.03 0.01 0.02 0.02	ver 5 W 3 W 1 W 2 W 5 W 3 W		
Connections Additional Informal Instructions on a contraction of a contra	onnecting to are presented in the properties of	in Hz, electricity sup n on the instructrical testing fapplicable)*: Output Current 2.25 A 2.25 A 2.25 A 3.25 A	ply system, mentation, Output Power 45 W 45 W 45 W 45 W 65 W	24.8 degree Celsi 230 V / 50 Hz <2% Power Meter: YO Average Active Efficiency 89% 88% 89% 89% 90%	## 10% Lo Efficien	ad No L cy Pov 0.02 0.03 0.07 0.02 0.00 0.00 0.00	ver 5 W 3 W 1 W 2 W 5 W 3 W		
Test parameters for ambient temper test voltage in Votal harmonic of information and set-up and circulateral power summer of the control of t	onnecting to are presented by the second of	in Hz, e electricity sup n on the instructrical testing f applicable)*: Output Current 2.25 A 2.25 A 2.25 A 3.25 A 3.25 A 3.25 A	Output Power 45 W 45 W 45 W 65 W 65 W	24.8 degree Celsi 230 V / 50 Hz <2% Power Meter: YO Average Active Efficiency 89% 88% 89% 90% 89% 89%	## 10% Lo Efficien ## 89% ## 89% ## 90%	ad No L cy Pov 0.02 0.03 0.07 0.02 0.00 0.00 0.00	ver 5 W 3 W 1 W 2 W 5 W 3 W 8 W		
Connections Additional Informa Instructions on Connections Test parameters for ambient temper test voltage in Voltage i	onnecting to are presented in the property of	in Hz, e electricity sup n on the instructrical testing f applicable)*: Output Current 2.25 A 2.25 A 2.25 A 3.25 A 3.25 A 3.25 A 3.25 A	Output Power 45 W 45 W 45 W 65 W 65 W 65 W	24.8 degree Celsi 230 V / 50 Hz <2% Power Meter: YO Average Active Efficiency 89% 88% 89% 89% 89% 89% 89% 89% 89% 89%	## 10% Lo Efficien 89% 87% 89% 88% 90% 89% 90% 84%	ad No L cy Pov 0.02 0.03 0.01 0.02 0.03 0.09 0.09	ver 5 W 3 W 1 W 2 W 5 W 3 W 8 W		