

ECMA/TC38-TG3/2015/026 (Rev. 1 – 15 April 2015)

### Annex B2 - Product environmental attributes Notebooks and Tablets

The declaration may be published only when all rows and/or fields marked with \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lenovo	Logo
Company name *	Lenovo	
Contact information *	Lenovo Global Environmental Affairs	
e-mail address	Alvin L Carter	Lenovo
	alcarter@lenovo.com	
Internet site *	https://www.lenovo.com/us/en/sustainability-resources/	
Additional information	The latest version of this document can be found at:	
	http://www.lenovo.com/ecodeclaration	

	based on product specification or test results based obtained from sample testing), that the product nts given in this declaration.
Type of product *	Portable Computer Tablet
Commercial name *	Lenovo Tab Extreme
Model number *	ZACE,ZACF
Issue date *	2022.1.29
Intended market *	🔀 Global 🔲 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other
Additional information	

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

#### About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products

Model n	umber *	ZACF	Long		
lssue da	ate *	2023.1.29	Lend		R
	t environ	mental attributes - Legal requirements	Require		
Item			Yes	No	n.a.
P1		bus substances and preparations			
P1.1*		s do comply with current European RoHS Directive. (See legal reference and NOTE B1)	$\square$		
P1.2*		s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value.	$\boxtimes$		
P1.3*	hydrobr trichloro	s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), pmofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- ethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum ration values.			
P1.4*	Product	s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated /l (PCT) in preparations (see legal reference).	$\boxtimes$		
P1.5*	Product	s do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in intaining at least 48% per mass of chlorine in the SCCP (see legal reference).	the 🔀		
P1.6*	Parts wi (see leg	th direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm²/we al reference). nt: Max limit in legal reference when tested according to EN1811:2011-5.	ek 🔀		
P1.7*	REACH	Article 33 information about substances in articles is available at (add URL or mail contact): <a href="http://www.lenovo.com/us/en/Lenovo-REACH-SVHC-Disclosure">www.lenovo.com/us/en/Lenovo-REACH-SVHC-Disclosure</a>	$\square$		
P2	Batterie	S			
P2.1*		oduct contains a battery or an accumulator, the battery/accumulator is labeled with the disposal Information on proper disposal is provided in user manual. (See legal reference)	$\boxtimes$		
P2.2*	Batterie referenc	s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See leg	gal 🔀		
P2.3*	Batterie	s and accumulators are readily removable. (See legal reference)	$\square$		
P3	Confor	nity verification & Eco design (ErP)			
P3.1*	The pro The Dec https://	duct is CE-marked to show conformance with applicable legal requirements (see legal reference) claration of Conformity can be requested at (add link or e-mail address): <a href="http://www.lenovo.com/us/en/compliance/eu-doc">www.lenovo.com/us/en/compliance/eu-doc</a> for EU; <a href="http://www.lenovo.com/us/en/compliance/uk-doc">www.lenovo.com/us/en/compliance/eu-doc</a> for EU;	). 🔀		
P3.2*	The pro	duct complies with the Eco design requirements for energy-related products, al reference).	$\square$		
	· ·	d information is; $\boxtimes$ given in item P15 or added to this document, $\boxtimes$ available at (add URL):			
	https://	www.lenovo.com/us/en/compliance/eco-declaration			
P5		t packaging			
P5.1*	hexaval	ng and packaging components do not contain more than 0,01% lead, mercury, cadmium ent chromium by weight of these together.			
P5.2*	used (se	kaging materials are marked with abbreviations and numbers indicating the nature of the materia ee legal reference).			
P5.3*	(see leg	duct packaging material is free from ozone depleting substances as specified in the Montreal Proto al reference). nt: Legal reference has no maximum concentration values.	ocol 🔀		
P6		Int information			
P6.1*		ion for recyclers/treatment facilities is available (see legal reference).	$\square$		

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model nu	ımber *	ZACF	Logo	Lon		
Issue dat	te *	2023.1.29		Len	ovo	тн
Product	environ	mental attributes - Market requirements (See General NOTE GN	below)			
		onmental conscious design		Require		
Item		tory to fill in. Additional information regarding each item may be found under P14.		Yes	No	n.a.
<b>P7</b> P7.1*		Disassembly, recycling at have to be treated separately are easily separable				
						<u> </u>
P7.2*		naterials in covers/housing have no surface coating.		<u> </u>		
P7.3*		arts > 100 g consist of one material or of easily separable materials.		<u> </u>	<u> </u>	
P7.4*		arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.				
P7.5		arts are free from metal inlays or have inlays that can be removed with commonly a	available tools.			
P7.6*		re easily separable. (This requirement does not apply to safety/regulatory labels).		$\square$		
		lifetime				
P7.7*		ng can be done e.g. with processor, memory, cards or drives				
P7.8*		ng can be done using commonly available tools			$\boxtimes$	
P7.9	Spare pa	arts are available after end of production for: <b>1</b> years				
P7.10	Service i	s available after end of production for: <b>1</b> years				
		and substance requirements				
P7.11*		cover/housing material type (e.g. plastics, metal, aluminum):				
P7.12		type: AL Material type: PC+20%GF Materia n materials of external electrical cables are PVC free.	al type: SUS304			
P7.12		n materials of external electrical cables are PVC free.				
P7.13					<u> </u>	
P7.14	weight ( polyvinyl	plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) b 1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in an 25% post-consumer recycled content.	e retardants, and	- L		
P7.15		sircuit boards, PCBs (without components) are low halogen: all ⊠ PCBs > 25 g ad in IEC 61249-2-21. (See 1NOTE B2)	are low haloge	n 🛛		
P7.16	Marking:					$\boxtimes$
P7.17		nemical specifications of flame retardants in printed circuit boards > 25 g (without co			_	_
	TBBF	PA (additive), TBBPA (reactive) (See NOTE B3), Other: DOPO, CAS #: 3594	8-25-5	$\bowtie$		
		nemical specifications of flame retardants in printed circuit boards (without compone g ISO 1043-4:	ents) > 25 g			$\square$
P7.18	Alt. 1: Fl	ame retarded plastic parts > 25 g contain the following flame retardant substance	s/preparations in	า		
	concentr	ations above 0,1%:				$\boxtimes$
		ical name: , CAS #: (See NOTE B4)				
		ical name: , CAS #: " ical name: , CAS #: "				
			o 4			
D7.40		nemical specifications of flame retardants in plastic parts > 25 g according ISO 104		<u> </u>	<u> </u>	
P7.19	assigned	parts > 25 g, flame retardant substances/preparations above 0,1% are used which the following Risk phrases; and Hazard statements:				
P7.20*		rce(s) for these classifications is/are found at (add URL(s)): , (See sumer recycled plastic material content is used in the product (See Note B6):	note B5)			
F1.20	Posicons	sumer recycleu plastic material content is used in the product (See Note Bo):		$\square$		
	a) Of t a pe or	at least one of the two alternatives below shall be answered; total plastic parts' weight > 25 g, the postconsumer recycled plastic material conten ercentage of total plastic by weight) is <b>35%</b> .	t (calculated as			

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model number *	ZACF	Logo	Lenovo
Issue date *	2023.1.29		LEHOVO
Product environ	nental attributes - Market requirements (continued)	· · ·	Requirement met

Item

Requirement met Yes No

n.a.

	Material and subs	stance requirements	(continued)		
P7.21*	Biobased plastic n	naterial content is used	d in the product (See NO	DTE B7):	
	a) Of total plasti total plastic b	c parts' weight > 25 g,	es below shall be answe the biobased plastic ma		ed as a percentage of
	or b) The weight of	f the biobased plastic r	material is a.		
P7.22*	Light sources are	free from mercury, i.e.	less than 0,1 mg/lamp.		
	,	specify: Number of lar	mps: and maximi	um mercury content pe	
P8	Batteries	omposition: Li jar D-	human		
P8.1*		composition: Li-ion Po	lymer		
P9.1		tion (See NOTE B8)	ls or energy consumption	na ara rapartad:	
Energy mod		Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference/Standard for energy modes and test method *
Peak (On-r	nax)	68 W	68 W	68 W	Full load
Category	<u>/2</u>				
Short Idle Enabled	State - WOL	3.7320 W	3.7428 W	3.8868 W	ENERGY STAR Computers V8.0 (P <sub>idle</sub> )
Long Idle S Enabled	State - WOL	0.3684 W	0.3672 W	0.4008 W	ENERGY STAR Computers V8.0 (P <sub>idle</sub> )
Sleep (S3)	- WOL Disabled	0.3684 W	0.3672 W	0.4008 W	ENERGY STAR Computers V8.0
Off (S5) - V	VOL Disabled	0.3024 W	0.3048 W	0.3420 W	ENERGY STAR Computers V8.0
EPS No-loa (External power s	ad upply / charger plugged in the connected from the product.)	0.039 W	0.042 W	0.075 W	
ETEC *	ergy Consumption	11.92 W	11.95 W	12.54 W	E <sub>TEC</sub> = (8760/1000) x (P <sub>off</sub> x 0.25 + P <sub>sleep</sub> x 0.35 + P <sub>long_Idle</sub> x 0.10+ P <sub>short Idle</sub> x 0.30)
		Poff: Off Mode(S5) - W	OL Enabled; P <sub>sleep</sub> : Sleep	Mode(S3) - WOL Enable	d; P <sub>idle</sub> : Idle State - WOL Enabled
External Po	ower Supply Efficier	ncy Level (Internationa	I Efficiency Marking Pro	tocol) * : <b>VI</b>	
Display res	olution * : <b>5.628</b> me	egapixels			
Default time	e to enter energy sa	ave mode: 0.5 minutes			
P9.2*	Information about	the energy save functi	on is provided with the	product.	
P9.3	Energy efficiency	class (monitors only):			
P10	Emissions				
D10.1		<b>v</b>	ISO 9296 (See NOTE		A weighted actual power level ( (D)
P10.1	Mode N Idle *	Mode description		<ul> <li>Statistical upper limit</li> </ul>	A-weighted sound power level, <i>L</i> <sub>WA,c</sub> (B)
	Operation *			*	X
		Declared A-weighted soun	d pressure level (dB) L <sub>pAm</sub>	(operator per	ition desktop – idle)
	I		d pressure level (dB) L <sub>p</sub> Am	(operator pos	iition desktop – operating)
	Measured accordi	ng to: ISO 7779 _ Other	ECMA-74 (only if not covered by	ECMA-74)	
	•				

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

Model nu	umber *	ZACF			Logo	Long		
Issue da	te *	2023.1.29				Leno		
Product	t environ	mental attribu	tes - Market requirements (	(continued)		Require	ment m	et
Item						Yes	No n	.a.
		magnetic emiss						
P10.4	program	n(s):	the requirement for low frequen	cy electromagnetic fiel	ds of the following volunt	ary		
P12	Ergono	mics for compu	iting products					
P12.1*	The disp	play meets the e	rgonomic requirements of ISO 92	241-307 for visual disp	lay technologies.	$\square$		
P12.2*	The phy	sical input devic	e meets the requirements of ISC	9995 and ISO 9241-4	-10.	$\boxtimes$		
P13		ing and docum						
P13.1*	Product	packaging mate	rial type(s): <b>Cardboard</b> weigh rial type(s): <b>paper(manual)</b> weigh rial type(s): <b>Molded Pulp</b> weigh	ght (kg): 0.056				
P13.2*	Product	plastic primary p	backaging is free from PVC.			$\boxtimes$		
P13.3*		duct primary co er recovered fibe	rrugated fiberboard packaging, er content: %	specify the contained	percentage of minimun	n post-		
P13.4*		media for user a tronic, 🔀Paper,	nd product documentation (tick l	cox):				
P13.5	Ùser an		nis item if paper documentation un nentation on paper media is chlo					
	Totally	chlorine-free				$\square$		
		tal chlorine-free						
		ed chlorine-free				H		
P14	Volunta	ry programs						
P14.1			equirements of the following volu	untary program(s):				
	Eco-lab		Criteria version: <b>8.0</b> Criteria version:	Date: <b>2020-4</b> Date:	Product category: 2 Product category:			
DIE	Eco-lab		Criteria version:	Date:	Product category:			
P15 P9			(See NOTE B10)	anu deseriation of th	a too to al musel unit a suffic			
<u>ry</u>	NOTE: the info supplie informa	Supplier makes rmation contail r's knowledge a ttion. The inform	f specific configuration may v no representations, guarante ned in this document. All infor available at the time of comple nation provided here is approz re for more information.	es, assurances or wa mation provided by s tion, and supplier sha	rranties whether expre upplier in this docume all have no obligation t	ss or implied, i nt is provided o update such	based of	n
P9	See En	ergy Star Qualit	fied Notebooks & Tablet Comp gov/index.cfm?fuseaction=fin	uters for the latest in d_a_product.showPr	formation: oductGroup&pgw_cod	e=CO		

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

## Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1
Regulation (EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC ( Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1

# Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

#### Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	Lenovo Tab Extreme	Logo
Model Number	ZACE,ZACF	Lenovo
Issue Date	2023.1.29	Lenovo
Additional information		

	Product environmental attributes				
(d)	Year of manufacture:				2023
(e)	Etec value (kWh) per ErP Lot 3 Catego disabled and if the system is tested with				cards (dGfx) are
(f)	Etec value (kWh) per ErP Lot 3 Categor enable	y and capability adjust	ments applied when a	all discrete graphics	cards (dGfx) are
		Category A (according to ErP Lot 3)	Category B (according to ErP Lot 3)	Category C (according to ErP Lot 3)	Category D (according to ErP Lot 3)
	Memory over base [GB]	12			
ents sting	Additional internal storage	No (Yes / No)	(Yes / No)	(Yes / No)	(Yes / No)
capability adjustments applied during testing	Discrete television tuner	No (Yes / No)	(Yes / No)	(Yes / No)	(Yes / No)
ability a lied du	Discrete Audio Card	No (Yes / No)	(Yes / No)	(Yes / No)	(Yes / No)
cap	Discrete graphics Card(s) [number / #]	No #: (Yes / No)	#: (Yes / No)	#: (Yes / No)	#: (Yes / No)
	Category of discrete graphics Card(s)	Νο			
sults	Etec Value (kWh) - dGfx disabled all discrete graphics cards (dGfx) are disabled/ UMA is active for switchable graphics/ product has no graphics cards (dGfx)	11.07			
Test results	Etec Value (kWh) - dGfx enabled all discrete graphics cards (dGfx) are enabled				
(g)	Idle state power demand (Watts);		L	ł	3.2472
(h)	Sleep mode power demand (Watts);				0.6060
(i)	Sleep mode with WOL enabled power de	emand (Watts) (where	enabled);		
(j)	Off mode power demand (Watts);				0.3816
(k)	Off mode with WOL enabled power dem	and (Watts) (where en	abled);		
(I)	Internal power supply efficiency at 10 %,	20 %, 50 % and 100 %	% of rated output pow	er (if applicable):	
	10% 20% 50%	100% Avera	age		
(m)	External power supply efficiency (if appli	cable)*:			
	Average active efficiency: 83.2% (5V 3	A 15W);89.51%(20V :	3.4A 68W);90.62%(11	IV 6.2A 68.2W)	
	*internal note: show values for all available external p	ower supplies			
(0)	Minimum number of loading cycles that t	he batteries can withs	tand (applies only to r	notebook computers):	800cls , <i>≥</i> 70% o capacity
(p-1)	Measurement methodology used to dete	rmine information mer NA	ntioned in points (I) – i	nternal PSU efficiency	:
(p-2)	Measurement methodology used to dete Measuring the Energy Consumption				

(p-4)       Measurement methodology used to determine information mentioned in maximum, idle, sleep, off mode power as defined in Point P9.1 in the Product IT Eco Declaration:         EN 62623:2013 Desktop and notebook computers - Measurement of energy         (q)       Sequence of steps for achieving a stable condition with respect to power demand:: EN 62623:2013 Desktop and notebook computers - Measurement of energy         (r)       Description of how sleep and/or off mode was selected or programmed: refer to power management, sleep mode: ACPI system level G1/S3 (suspend to RAM) state; off mod ACPI system level G2/S5 ('soft off') state         (s)       Sequence of events required to reach the mode where the equipment automatically changes to sleep and/o off mode: refer to power management, 0.5mins automatically reaches sleep mode         (t)       Duration of idle state condition before the computer automatically reaches sleep mode (in minutes):         (v)       Length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes):         (v)       Length of time before the display sleep mode is set to activate after user inactivity (in minutes):         (v)       Length of time before the display sleep mode is set to activate after user inactivity (in minutes):         (v)       Length of time before the display sleep mode is set to activate after user inactivity (in minutes):         (v)       Length of time before the display sleep mode is set to activate after user inactivity (in minutes): <t< th=""><th>gy gy state; off mode:</th><th>asurement of energy demand::</th><th>Point P9.1 in the Product IT Eco Declaration: 623:2013 Desktop and notebook computers - Me r achieving a stable condition with respect to power</th><th>power as defined in <b>EN 6</b>2</th></t<>	gy gy state; off mode:	asurement of energy demand::	Point P9.1 in the Product IT Eco Declaration: 623:2013 Desktop and notebook computers - Me r achieving a stable condition with respect to power	power as defined in <b>EN 6</b> 2
(q)       Sequence of steps for achieving a stable condition with respect to power demand::         EN 62623:2013 Desktop and notebook computers - Measurement of energy         (r)       Description of how sleep and/or off mode was selected or programmed:         refer to power management, sleep mode: ACPI system level G1/S3 (suspend to RAM) state; off mod ACPI system level G22S5 ('soft off') state         (s)       Sequence of events required to reach the mode where the equipment automatically changes to sleep and/o off mode:         refer to power management, 0.5mins automatically reaches sleep mode         (t)       Duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode, or another mode that has a lower power demand requirement than sleep mode (in minutes):         (u)       Length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes):         (w)       Information on the energy-saving potential of power management functionality: refer to user manual         (x)       User information on how to enable the power management functionality: refer to user manual         (z)       Test parameters for measurements: used for electrical testing: 230 (±1 %) V a.c., 50 Hz (±1 %), EN 62623:2013         Additional Notebook Battery Information: we placeable       Battery[ies] user replaceable The battery[ies] in this product cannot be easily replaced by users themselves. <sup>1</sup> <td< td=""><td>gy state; off mode:</td><td>demand::</td><td>r achieving a stable condition with respect to power</td><td></td></td<>	gy state; off mode:	demand::	r achieving a stable condition with respect to power	
EN 62623:2013 Desktop and notebook computers - Measurement of energy         (r)       Description of how sleep and/or off mode was selected or programmed: refer to power management, sleep mode: ACPI system level G1/S3 (suspend to RAM) state; off mod ACPI system level G2/S5 ('soft off') state         (s)       Sequence of events required to reach the mode where the equipment automatically changes to sleep and/o off mode: refer to power management, 0.5mins automatically reaches sleep mode         (t)       Duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode, or another mode that has a lower power demand requirement than sleep mode (in minutes):         (u)       Length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes):         (v)       Length of time before the display sleep mode is set to activate after user inactivity (in minutes):         (w)       Information on the energy-saving potential of power management functionality: refer to user manual         (x)       User information on how to enable the power management functionality: refer to user manual         (z)       Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: 230 (±1 %) V a.c., 50 Hz (±1 %), EN 62623:2013         Additional Notebook Battery Information:	state; off mode:			q) Sequence of steps for
(r)       Description of how sleep and/or off mode was selected or programmed:         refer to power management, sleep mode: ACPI system level G1/S3 (suspend to RAM) state; off mod ACPI system level G2/S5 ('soft off') state         (s)       Sequence of events required to reach the mode where the equipment automatically changes to sleep and/o off mode:         refer to power management, 0.5mins automatically reaches sleep mode         (t)       Duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes):         (u)       Length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes):         (v)       Length of time before the display sleep mode is set to activate after user inactivity (in minutes):         (w)       Information on the energy-saving potential of power management functionality: <i>refer to user manual</i> (x)         (x)       User information on how to enable the power management functionality: <i>refer to user manual</i> (x)         (z)       Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: 230 (±1 %) V a.c., 50 Hz (±1 %), EN 62623:2013         Additional Notebook Battery Information:       Battery[ies]	state; off mode:	asurement of energy	623:2013 Desktop and notebook computers - Me	
refer to power management, sleep mode: ACPI system level G1/S3 (suspend to RAM) state; off mode ACPI system level G2/S5 ('soft off') state         (s)       Sequence of events required to reach the mode where the equipment automatically changes to sleep and/o off mode:         refer to power management, 0.5mins automatically reaches sleep mode         (t)       Duration of idle state condition before the computer automatically reaches sleep mode (in minutes):         (u)       Length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirements for sleep mode (in minutes):         (v)       Length of time before the display sleep mode is set to activate after user inactivity (in minutes):         (w)       Information on the energy-saving potential of power management functionality: <i>refer to user manual</i> refer to user manual         (x)       User information on how to enable the power management functionality: <i>refer to user manual</i> refer to user manual         (z)       Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:230 (±1 %) V a.c., 50 Hz (±1 %), EN 62623:2013         Additional Notebook Battery Information:         Battery[ies] not user replaceable       The battery[ies] in this product cannot be easily replaceable <t< td=""><td></td><td></td><td></td><td>EN 62</td></t<>				EN 62
ACPI system level G2/S5 ('soft off') state         (s)       Sequence of events required to reach the mode where the equipment automatically changes to sleep and/o off mode:         refer to power management, 0.5mins automatically reaches sleep mode         (t)       Duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes):         (u)       Length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes):         (u)       Length of time before the display sleep mode is set to activate after user inactivity (in minutes):         (w)       Information on the energy-saving potential of power management functionality:         (x)       User information on how to enable the power management functionality:         refer to user manual       (x)         (z)       Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:230 (±1 %) V a.c., 50 Hz (±1 %), EN 62623:2013         Additional Notebook Battery Information:         The battery[ies] not user replaceable       Battery[ies] user replaceable         The battery[ies] in this product cannot be easily replaced by users themselves. <sup>1)</sup> Imermal/built-in Battery			eep and/or off mode was selected or programmed:	r) Description of how s
off mode:       refer to power management, 0.5mins automatically reaches sleep mode         (t)       Duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode, (in minutes):         (u)       Length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes):         (v)       Length of time before the display sleep mode is set to activate after user inactivity (in minutes):         (w)       Information on the energy-saving potential of power management functionality:         refer to user manual       refer to user manual         (x)       User information on how to enable the power management functionality:         refer to user manual       refer to user manual         (z)       Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: 230 (±1 %) V a.c., 50 Hz (±1 %), EN 62623:2013         Additional Notebook Battery Information:       Battery[ies] not user replaceable         The battery[ies] in this product cannot be easily replaced by users themselves. 1)       Internal/built-in Battery         External/detachable Battery	to sleep and/or			refer to power man
(t)       Duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes):         (u)       Length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes):         (u)       Length of time before the display sleep mode is set to activate after user inactivity (in minutes):         (v)       Length of time before the display sleep mode is set to activate after user inactivity (in minutes):         (v)       Length of time before the display sleep mode is set to activate after user inactivity (in minutes):         (v)       Length of time before the display sleep mode is set to activate after user inactivity (in minutes):         (v)       Length of time before the display sleep mode is set to activate after user inactivity (in minutes):         (w)       Information on the energy-saving potential of power management functionality:         (w)       refer to user manual         (x)       User information on how to enable the power management functionality:         (x)       User information on how to enable the power management functionality:         (x)       refer to user manual         (x)       User information and documentation on the instrumentation, set-up and circuits used for electrical testing: 230 (±1 %) V a.c., 50 Hz (±1 %), EN 62623:2013         Additional Notebook Battery Infor		omatically changes to sleep and/or	required to reach the mode where the equipment aut	
condition which does not exceed the applicable power demand requirements for sleep mode (in minutes):         (u)       Length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes):         (v)       Length of time before the display sleep mode is set to activate after user inactivity (in minutes):         (v)       Length of time before the display sleep mode is set to activate after user inactivity (in minutes):         (w)       Information on the energy-saving potential of power management functionality:         (x)       User information on how to enable the power management functionality:         (z)       Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:230 (±1 %) V a.c., 50 Hz (±1 %), EN 62623:2013         Additional Notebook Battery Information:       Battery[ies] not user replaceable         The battery[ies] in this product cannot be easily replaced by users themselves. 1)       Internal/built-in Battery         Sios Backup Battery       Image: Size Size Size Size Size Size Size Size	3	eaches sleep mode	r to power management, 0.5mins automatically re	refe
mode that has a lower power demand requirement than sleep mode (in minutes):         (v)       Length of time before the display sleep mode is set to activate after user inactivity (in minutes):         (w)       Information on the energy-saving potential of power management functionality:         refer to user manual         (x)       User information on how to enable the power management functionality:         refer to user manual         (x)       User information on how to enable the power management functionality:         refer to user manual         (z)       Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: 230 (±1 %) V a.c., 50 Hz (±1 %), EN 62623:2013         Additional Notebook Battery Information:         Battery[ies] not       Battery[ies] user replaceable         The battery[ies] in this product cannot be easily replaced by users themselves. <sup>1</sup> )       Internal/built-in Battery         Bios Backup Battery	(in minutes):	nts for sleep mode (in minutes):	not exceed the applicable power demand requirement	condition which does
(w)       Information on the energy-saving potential of power management functionality:         refer to user manual         (x)       User information on how to enable the power management functionality:         refer to user manual         (z)       Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:230 (±1 %) V a.c., 50 Hz (±1 %), EN 62623:2013         Additional Notebook Battery Information:         Battery[ies] not       Battery[ies] user replaceable         The battery[ies] in this product cannot be easily replaced by users themselves. <sup>1</sup> )       Internal/built-in Battery         Internal/detachable Battery       Internal/detachable Battery       Internal/detachable Battery         Bios Backup Battery       Internal       Internal	ches a power NA			
refer to user manual         (x)       User information on how to enable the power management functionality:         refer to user manual         (z)       Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: 230 (±1 %) V a.c., 50 Hz (±1 %), EN 62623:2013         Additional Notebook Battery Information:         Battery[ies] not       user replaceable         The battery[ies] in this product cannot be easily replaced by users themselves. <sup>1)</sup> Battery[ies] user replaceable         Internal/built-in Battery	nutes): 1	ser inactivity (in minutes):	re the display sleep mode is set to activate after t	v) Length of time befo
(x)       User information on how to enable the power management functionality:         refer to user manual         (z)       Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: 230 (±1 %) V a.c., 50 Hz (±1 %), EN 62623:2013         Additional Notebook Battery Information:         Battery[ies] not user replaceable       Battery[ies] user replaceable         The battery[ies] in this product cannot be easily replaced by users themselves. 1)       Internal/built-in Battery         External/detachable Battery       Image: Colspan="2">Image: Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2"Colspan="2"Colspan="2"Colspan="2"Colspan="2"Colspan="2"Colspan="2"Colspan="2"Colspan="2"Colspan="2"Colspan="2"Colspan="2"Colspan="2"Colspan="2"Colspan="2"Colspan="2"Colspan="2">Colspan="2"Colspan		iality:		W) Information on the el
refer to user manual         (z)       Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: 230 (±1 %) V a.c., 50 Hz (±1 %), EN 62623:2013         Additional Notebook Battery Information:         Battery[ies] not       user replaceable         The battery[ies] in this product cannot be easily replaced by users themselves. 1)       Battery[ies] user replaceable         Internal/built-in Battery       Image: Colspan="2">Image: Colspan="2">Image: Colspan="2">Colspan="2"Colspan="2			refer to user manual	
z)       Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: 230 (±1 %) V a.c., 50 Hz (±1 %), EN 62623:2013         Additional Notebook Battery Information:         Battery[ies] not user replaceable         The battery[ies] in this product cannot be easily replaced by users themselves. 1)         Internal/built-in Battery         External/detachable Battery         Bios Backup Battery			now to enable the power management functionality:	x) User information on
the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: 230 (±1 %) V a.c., 50 Hz (±1 %), EN 62623:2013         Additional Notebook Battery Information:         Battery[ies] not user replaceable         The battery[ies] in this product cannot be easily replaced by users themselves. 1)         Internal/built-in Battery         External/detachable Battery         Bios Backup Battery			refer to user manual	
Battery[ies] not user replaceable       Battery[ies] user replaceable         The battery[ies] in this product cannot be easily       Battery[ies] user replaceable         Internal/built-in Battery       Image: Comparison of the second		strumentation, set-up and circuits	system, — information and documentation on the ins	the electricity supply
The battery[ies] in this product cannot be easily replaced by users themselves. 1)         Internal/built-in Battery         External/detachable Battery         Bios Backup Battery				Additional Notebook Batter
replaced by users themselves. 1)         Internal/built-in Battery         External/detachable Battery         Bios Backup Battery	er replaceable   n/a	Battery[ies] user replaceable		
External/detachable Battery				
Bios Backup Battery			$\boxtimes$	nternal/built-in Battery
				External/detachable Battery
				Bios Backup Battery
Other:				Other:
Additional information				Additional information

Baterij/baterije v tem izdelku uporabniki sami ne morejo zlahka zamenjati. Tämän tuotteen akku [akut] ei[vät] ole helposti käyttäjän vaihdettavissa. Det är inte enkelt för kunden att själv byta ut batteriet/batterierna. Bu üründeki batarya(lar) kullanıcılar tarafından kolaylıkla değiştirilemez.