



Annex B2 - Product environmental attributes **Computers and computer monitors**

The declaration may be published only when all rows and/or fields marked with * are filled-in (N/A for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lenovo	Logo	
Company name *	Lenovo		_
Contact information * e-mail address	Lenovo Environmental Social and Governance environment@lenovo.com		Lenovo
Internet site *	https://www.lenovo.com/us/en/sustainability-resources/	•	
Additional information	The latest version of this document can be found at:		_
	http://www.lenovo.com/ecodeclaration		

The company declares (based on product specification or test results based obtained from sample testing), that the product						
conforms to the statemen	conforms to the statements given in this declaration.					
Type of product *	Notebook Computer					
Commercial name *	ThinkPad L15 Gen 4					
Model number *	21H3,21H4					
Issue date *	2023-04-11					
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other					
Additional information						

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 - P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products

Model number *	21H3,21H4	Logo	
Issue date *	2023-04-11		Lenovo

Product	environmental attributes - Legal requirements	equirer	nent	met
Item	•	Yes	No	N/A
P1	Hazardous substances and preparations			
P1.1*	Products comply with current European RoHS Directive. (See legal reference and NOTE B1)	\boxtimes		
P1.2*	Products do not contain Asbestos (See legal reference) Comment: Legal reference has no maximum concentration value.	\boxtimes		
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (See legal reference). Comment: Legal reference has no maximum concentration values			
P1.4*	Products do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated terphenyl (PCT) in preparations (See legal reference)	\boxtimes		
P1.5*	Products do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (See legal reference)	\boxtimes		
P1.6*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm²/week (See legal reference) Comment: Max limit in legal reference when tested according to EN1811:2011-5			
P1.7*	REACH Article 33 information about substances in articles is available at (add URL or mail contact): https://www.lenovo.com/us/en/Lenovo-REACH-SVHCDisclosure			
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal symbol. Information on proper disposal is provided in user manual. (See legal reference)	\boxtimes		
P2.2*	Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal reference)	\boxtimes		
P2.3*	Batteries and accumulators are readily removable. (See legal reference)	\boxtimes		
P2.4*	Documentation includes the number of cycles the (secondary) battery can withstand. (See legal reference)			
P2.5*	When internal batteries of a notebook computer cannot be "accessed and replaced by a nonprofessional user", the related text is present and legible on the external packaging (See legal reference)	\boxtimes		
P3	Conformity verification & Eco design (ErP)	*		
P3.1*	The product is CE-marked to show conformance with applicable legal requirements (see legal reference). The Declaration of Conformity can be requested at (add link or e-mail address): https://www.lenovo.com/us/en/compliance/eu-doc for EU https://www.lenovo.com/us/en/compliance/uk-doc for UK			
P3.2*	The product complies with the applicable Eco design requirements for energy-related products, (See legal reference)	\boxtimes		
	Required information is; Silven in item P15 or added to this document, available at (add URL): http://www.lenovo.com/ecodeclaration			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium and hexavalent chromium by weight of these together	\boxtimes		
P5.2*	The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s) used (See legal reference)	\boxtimes		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal Protocol (See legal reference) Comment: Legal reference has no maximum concentration values			
P6	Treatment information			
P6.1*	Information for recyclers/treatment facilities is available (https://lenovo.com/recycling).	\boxtimes		

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number *	21H3,21H4	Logo	1
Issue date *	2023-04-11		Lenovo

Droduc	t environmental attributes - Market requirements (See General NOTE GN below)			
Floude		Require	ment	met
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	N/A
P7	Design Disassembly, recycling	·		
P7.1*	Parts that have to be treated separately are easily separable	\boxtimes		
P7.2*	Plastic materials in covers/housing have no surface coating			
P7.3*	Plastic parts > 100 g consist of one material or of easily separable materials			
P7.4*	Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4			
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools			
P7.6*	Labels are easily separable (This requirement does not apply to safety/regulatory labels)	$\overline{\boxtimes}$		
	Product lifetime			
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	\boxtimes		
P7.8*	Upgrading can be done using commonly available tools	\boxtimes		
P7.9	Spare parts are available after end of production for: 5 years			
P7.10	Service is available after end of production for: 5 years			
	Material and substance requirements			
P7.11*	Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: PC/ABS Material type: PC Material type: PC			
P7.12	Insulation materials of external electrical cables are PVC free		\boxtimes	
P7.13	Insulation materials of internal electrical cables are PVC free	\boxtimes		
P7.14	External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content			
P7.15	Printed circuit boards, PCBs (without components) are low halogen as defined in IEC 61249-2-21. (See NOTE B2): Only PCBs > 25g ☑ or All PCBs ☑			
P7.16	Flame retarded plastic parts > 25 g in covers / housings are marked according to ISO 1043-4: Marking: FR(40)			
P7.17	Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: 168G2, CAS #: 9920850-1	- 🖂		
	<u>Alt. 2:</u> Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according to ISO 1043-4:			
P7.18	Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: "			
	3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according to ISO 1043-4: <i>FR(40)</i>	\boxtimes		
P7.19	In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5)			

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm.

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

Model number *	21H3,21H4	Logo	1
Issue date *	2023-04-11		Lenovo

Product environmental attributes - Market requirements (continued)						Requi	reme	nt met
Item						Yes	No	N/A
D= 00+	aterial and substance require				<u> </u>			
	estconsumer recycled plastic ma YES; at least one of the two alte Of total plastic parts' weight; percentage of total plastic by The weight of recycled mater	ernatives below s > 25 g, the posto weight) is 8.83 %	hall be answered onsumer recycle	d;	,			
P7.21* Bio	obased plastic material content	is used in the pro						
If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic by weight) is %. or total plastic of the biobased plastic material is g.								
b) The weight of the biobased plastic material is g P7.22* Light sources are free from mercury, i.e. less than 0,1 mg/lamp If mercury is used specify. Number of lamps: and maximum mercury content per lamp: mg								
	mercury is used specify: Number product includes an integral disp			mercury content				-
	atteries	Diay, the total me	icury content in	ine integrated dis	spiay. V.V mg			
	attery chemical composition: Lit	hium ion						
	nergy consumption (See NOT							
	or the product the following power		gy consumptions	are reported:				
Energy mode '	*	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference/Standard for modes and test method			
Peak (On-Max	()	100 W	100 W	100 W	Full Load			
Device Categ	ory 1							
	te – WOL Enabled (P _{short_idle})	5.832 W	5.772 W	5.664 W	ENERGY STAR Compo			
Long Idle Sta	te – WOL Enabled (Plong_idle)	0.816 W	0.816 W	0.828 W	ENERGY STAR Compl	uters V8	.0	
Sleep (S3) - V	VOL Disabled (P Sleep)	0.816 W	0.816 W	0.828 W	ENERGY STAR Compl	uters V8	.0	
Off Mode (S5)) – WOL Disabled (P _{off})	0.504 W	0.504 W	0.516 W	ENERGY STAR Compl	uters V8	.0	
Device Categ	ory 2							
	te – WOL Enabled (P _{short_idle})	7.620 W	7.620 W	7.800 W	ENERGY STAR Compl	uters V8	.0	
Long Idle Sta	te – WOL Enabled (Plong_idle)	1.344 W	1.308 W	1.308 W	ENERGY STAR Compl	uters V8	.0	
Sleep (S3) - V	VOL Disabled (P Sleep)	1.344 W	1.308 W	1.308 W	ENERGY STAR Compl	uters V8	.0	
Off Mode (S5)) – WOL Disabled (P _{off})	0.432 W	0.420 W	0.456 W	ENERGY STAR Compo	uters V8	.0	
Device Categoria	ory Typical Configuration							
	te – WOL Enabled (Pshort_idle)	W	W	W	ENERGY STAR Compl	uters V8	.0	
Long Idle Sta	te – WOL Enabled (Plong_idle)	W	W	W	ENERGY STAR Compl	uters V8	.0	
Sleep (S3) - V	WOL Enabled (P _{Sleep})	W	W	W	ENERGY STAR Compo	uters V8	.0	
Off Mode (S5)) – WOL Enabled (P _{off})	W	W	W	ENERGY STAR Compl	uters V8	.0	
	y Consumption	W	W	W				
ETEC * Annual Energy Consumption		17.71/ 23.52 kWh/year	17.32/ 23.34 kWh/year	17.16/ 23.81 kWh/year	Mode Weighting Full Capability			
							ng	
Display resolut	Display resolution *: 2.074 megapixels 1920*1080							
Default time to enter energy save mode: 5 minutes ENERGY STA					ENERGY STAR Compo	uters V8	.0	
	formation about the energy save	•	ided with the pro	duct				
P9.3 En	nergy efficiency class (monitors	only):						\square

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available;

see http://www.ecma-international.org/publications/standards/Ecma-370.htm.

Model number *	21H3,21H4	Logo	1
Issue date *	2023-04-11		Lenovo

Product 6	environmental	ttributes - Market requ	irements (cont	inued)	F	Require	nent	met
Item						Yes	No	N/A
P10	Emissions							
		 Declared according to IS 	O 9296 (See NOT					
P10.1	Mode	Mode description		Statistical upper	er limit A-weighted sound pow	er level,		
	Idle	* Idle Mode		* 2.6				
	Operation	* Operating (CPU)		* 3.4				
	Other Mode	Declared A-weighted sound pro	essure level (dB)	NA (operator)	position desktop – idle)			
	Other mode	Declared A-weighted sound pro	essure level (dB)		oosition desktop – operating-HL oosition desktop – operating-CF			
	Measured accor	· = -		h FOMA 74)				
	Flooring money and		nly if not covered	by ECMA-74)			•	
D10.4	Computer displa		low fraguancy als	atromagnatia fields	of the following voluntary			
P10.4	program(s): MPI	meets the requirement for -II(3 pin AC adapter only)	low frequency ele	ctromagnetic fields	s of the following voluntary			
P12.1*		computing products	nto of ISO 0244 2	07 for vioual diapla	v tachnalogica			
		s the ergonomic requireme					<u>Ц</u>	<u>Ц</u>
P12.2*	The physical input device meets the requirements of ISO 9995 and ISO 9241-410				\boxtimes			
P13	Packaging and	locumentation						
P13.1*	Product packagi Product packagi	g material type(s): Carboa g material type(s): Carboa g material type(s): Paper g material type(s): Paper		: 0.0539 : 0.161				
P13.2*	Product plastic p	imary packaging is free fro	m PVC			\boxtimes		П
P13.3*		ary corrugated fiberboard pared fiber content: 60 %	ackaging, specify	the contained perce	entage of minimum post-			
P13.4*	Specify media for	user and product documer aper , Other	ntation (tick box):					
P13.5		plete this item if paper doct documentation on paper medify:		ee:				
	Totally chlorine-	ee				\boxtimes		
	Elemental chlori	e-free				Ħ		
	Processed chlor	ne-free						
P14	Voluntary prog	ams						
P14.1	The product med	ts the requirements of the f	ollowing voluntary	program(s):				
	ENERGY STAR			Date: 2023-02-02		_		
	Eco-label: EPE	2018	II. IEEE 1000.1-	Date: 2023-04-17	Product category: Notebook			
	Eco-label: TCO	Criteria versio	n: 9.0	Date: 2023-04-30	Product category: Notebook	r		
P15	Additional info	nation (See NOTE B10)						
P9	Energy consun	otion of computer produc	ts; description o	f the tested produ	ıct configuration:			
P7.7	In further expla	ation of Upgradability (P	7.7/P7.8), the foll	owing component	ts can be upgraded:			
P7.8	Processor	Not	Upgradeable					
	Memory		radeable using c	ommon tools				
	Cards		Jpgradeable					
	Drives/Storage		radeable using co		antica whather are a first	mnlind :		line:
	the information	makes no representation contained in this docume	s, guarantees, as int All informatic	surances or Warr in provided by sur	anties whether express or in oplier in this document is pi	ripiiea, l rovided l	egard	iing Lor
					have no obligation to upda		Jaseu	on
					r informational purposes on		Lend	ovo

NOTE B9 A Guidance document on Acoustic Noise is available;

 $see \ \underline{http://www.ecma-international.org/publications/standards/Ecma-370.htm}.$

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive)* * Specific exemptions apply for certain products and applications.	P1.1, P3.1
Regulation (EC) 1907/2006 (REACH Regulation), annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2006/66/EC (Battery and accumulators Directive), as amended.* * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2.3, P8.1
Directive 2014/35/EU (Low Voltage Directive)	P3.1
Directive 2014/30/EU (EMC Directive)	P3.1
Directive 2014/53/EU (RE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Commission Regulation (EC) No 278/2009 of 6 April 2009 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for no-load condition electric power demand and average active efficiency of external power supplies	P3.1, P3.2, P9.1
COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers	P2.4, P2.5, P3.1, P3.2, P7.23, P9.1
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1
Implementing Regulation (EU) 2019/290 establishing the format for registration and reporting of producers of electrical and electronic equipment to the register.	
Commission Implementing Regulation 2017/699 establishing a common methodology for the calculation of the weight of electrical and electronic equipment (EEE) placed on the national market in each Member State and a common methodology for the calculation of the quantity of waste electrical and electronic equipment (WEEE) generated by weight in each Member State.	

Lenovo ErP Lot26 Information Sheet - Network Equipment -

As required by_

- Commission Regulation (EC) No 1275/2008 of 17 December 2008 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for standby and off-mode electric power consumption of electrical and electronic household equipment (ErP Lot 6)
- Commission Regulation (EU) No 801/2013 of 22 August 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for (ErP Lot 26).

Products scope of this sheet:

Notebook/Tablet Computer < 6 W Idle

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	ThinkPad L15 Gen 4	Logo
Model Number	21H3,21H4	_
Product Type	Notebook Computer with Idle Power < 6 W	Lenovo.
Issue Date	2023-04-011	
Additional information		

roduct environmental attributes	
year of manufacture:	2023
Network Standby Classification	LoNA Equipment
Off Mode Power (Watts)	0.49 Watts
Standby Mode	Watts ⊠Mode Not Applicable
	minutes Default Delay Time
Description of how to enable Network Standby Mode	Network Standby Mode is enabled at Shipment
Description of how to manually enter Network Standby Mode	1) Press the Power Button once; 2) Click on the Power Button and choose Sleep
Default Delay time to Network Standby Mode	10 minutes
Reactivation Function from Network Standby Mode	Open Notebook, Press Keyboard or power button, activate USB
	year of manufacture: Network Standby Classification Off Mode Power (Watts) Standby Mode Description of how to enable Network Standby Mode Description of how to manually enter Network Standby Mode Default Delay time to Network Standby Mode

5)	Network Port	Wired Ethernet	Wireless Ethernet	USB-A	USB-C	HDMI	BlueTooth	Other: Smart-card slot
	Present in Product							
	Activated at Shipment							
	Active in Network Standby Mode							
	Location of Network Port	Left	N/A	Left	Left	Left	N/A	Left
	Network Port Maximum Performance	1.0 GB/s	0.1 GB/s	GB/	GB/s	GB/s	GB/s	GB/s
	Network Protocol	802.3	Wi-Fi 6; 802.11ax	USB 3. Gen 1	2 Thunderb olt™ 4		BT5.2	4G
	Network Standby Mode Power	1.3 Watts	1.34 Watts	Watts	Watts	Watts	Watts	Watts
	Network Standby Power – All Connections				1.3 Watts			
·)	Instructions on acti		ctivating wirele	ess network(s	s) is included in t	he User Manua	1	
)	Test parameters for r	measurements,	ctivating wirele		,		1	
)	Test parameters for r	measurements,			24.8 degrees Cels			
1	Test parameters for r	measurements, re d frequency in F	łz	1	,			
1	Test parameters for r ambient temperatur test voltage in V an	measurements, re d frequency in F	łz	1	24.8 degrees Cels 230 V / 50 Hz			Calibration
	Test parameters for rambient temperature test voltage in V and total harmonic disto	measurements, re d frequency in F ortion of the elec	lz tricity supply sys	stem 2	24.8 degrees Cels 230 V / 50 Hz 2.00% Equipment AC Source	Make/Mode	el Last (Calibration
)	Test parameters for r ambient temperatur test voltage in V an	measurements, re d frequency in F ortion of the elec	Iz tricity supply sys the instrumentati	stem 2	24.8 degrees Cels 230 V / 50 Hz 2.00% Equipment AC Source Power Analyzer	sius	el Last (Calibration
)	Test parameters for rambient temperature test voltage in V and total harmonic distortion and documents to the test voltage in V and total harmonic distortion and documents to the test voltage in V and total harmonic distortion and documents to the test voltage in V and test voltage in	measurements, re d frequency in F ortion of the elec	Iz tricity supply sys the instrumentati	stem 2	24.8 degrees Cels 230 V / 50 Hz 2.00% Equipment AC Source Power Analyzer Timer Thermometer	Make/Mode	el Last (Calibration
	Test parameters for rambient temperature test voltage in V and total harmonic distormation and docup and circuits used	measurements, re d frequency in Fortion of the electron	tricity supply sys	stem 2	24.8 degrees Cels 230 V / 50 Hz 2.00% Equipment AC Source Power Analyzer Timer	Make/Mode	el Last (Calibration
	Test parameters for rambient temperature test voltage in V and total harmonic distortion and documents to the test voltage in V and total harmonic distortion and documents to the test voltage in V and total harmonic distortion and documents to the test voltage in V and test voltage in	measurements, re d frequency in Fortion of the electron	tricity supply sys	stem 2	24.8 degrees Cels 230 V / 50 Hz 2.00% Equipment AC Source Power Analyzer Timer Thermometer Hygrometer	Make/Mode YOKOGAV WT210	el Last (Date	Calibration
	Test parameters for rambient temperature test voltage in V and total harmonic distormation and docup and circuits used. External power supplements.	measurements, re d frequency in F ortion of the electron cumentation on the difference of the formula of the electrical telegraphs. It is a summary of the electrical telegraphs. It is a summary of the electrical telegraphs. It is a summary of the electrical telegraphs. It is a summary of the ele	tricity supply system instrumentations pplicable)*: Output Current	ion, set-	24.8 degrees Cels 230 V / 50 Hz 2.00% Equipment AC Source Power Analyzer Timer Thermometer Hygrometer Average Active Efficiency	Make/Mode YOKOGAV WT210	VA- No Loa	nd r
	Test parameters for rambient temperature test voltage in V and total harmonic distormation and docup and circuits used External power suppopulse. Model Delta	measurements, re d frequency in F ortion of the electrical telectrical telectr	tricity supply system instrumentations policable)*: Output Current 5 A	output Power 100 W	24.8 degrees Cels 230 V / 50 Hz 2.00% Equipment AC Source Power Analyzer Timer Thermometer Hygrometer Average Active Efficiency 90%	Make/Mode YOKOGAV WT210 10% Loac	VA- No Loa Powe 0.03 V	nd r
)	Test parameters for rambient temperature test voltage in V and total harmonic distormation and docup and circuits used External power suppose. Model Delta Chicony	measurements, re d frequency in F ortion of the electrical telectrical telectr	tricity supply system instrumentations the instrumentation of the in	Output Power 100 W 100 W	24.8 degrees Cels 230 V / 50 Hz 2.00% Equipment AC Source Power Analyzer Timer Thermometer Hygrometer Average Active Efficiency 90% 89%	Make/Mode YOKOGAV WT210 10% Loac	VA- No Loa Powe 0.03 W	nd r
	Test parameters for rambient temperature test voltage in V and total harmonic distormation and docup and circuits used External power supplements to the control of the co	measurements, re d frequency in F prior of the electrical telectrical telectri	tricity supply system the instrumentations the instrumentation of the instrumentation of the instrumentation of the instrument of the inst	Output Power 100 W 100 W 100 W	24.8 degrees Cels 230 V / 50 Hz 2.00% Equipment AC Source Power Analyzer Timer Thermometer Hygrometer Average Active Efficiency 90% 89% 89%	Make/Mode YOKOGAV WT210 10% Loac	No Loady Power 0.03 W 0 W	nd r
	Test parameters for rambient temperature test voltage in V and total harmonic distormation and docup and circuits used External power suppose. Model Delta Chicony	measurements, re d frequency in F ortion of the electrical telectrical telectr	tricity supply system instrumentations the instrumentation of the in	Output Power 100 W 100 W	24.8 degrees Cels 230 V / 50 Hz 2.00% Equipment AC Source Power Analyzer Timer Thermometer Hygrometer Average Active Efficiency 90% 89%	Make/Mode YOKOGAV WT210 10% Loac	No Loa Power 0.03 V 0 W 0.11 V	nd r
	Test parameters for rambient temperature test voltage in V and total harmonic distormation and docup and circuits used External power supplements to the control of the co	measurements, re d frequency in Fortion of the electrical telectrical telectri	tricity supply system the instrumentations the instrumentation of the instrumentation of the instrumentation of the instrument of the inst	Output Power 100 W 100 W 100 W 100 W	24.8 degrees Cels 230 V / 50 Hz 2.00% Equipment AC Source Power Analyzer Timer Thermometer Hygrometer Average Active Efficiency 90% 89% 89%	Make/Mode YOKOGAV WT210 10% Loac	No Loa Power 0.03 V 0 W 0.11 V	id r V
	Test parameters for rambient temperature test voltage in V and total harmonic distormation and docup and circuits used External power supplemental	measurements, re d frequency in F ortion of the electrical te cumentation on the dectrical te dy efficiency (if a Output Voltage 20 V 20 V 20 V V 750Hz	tricity supply system instrumentations the instrumentations pplicable)*: Output Current 5 A 5 A 5 A A determine inform	Output Power 100 W 100 W 100 W W	24.8 degrees Cels 23.0 V / 50 Hz 2.00% Equipment AC Source Power Analyzer Timer Thermometer Hygrometer Average Active Efficiency 90% 89% 89% 90%	Make/Mode YOKOGAV WT210 10% Loac Efficiency	No Loa Power 0.03 V 0 W 0.11 V	id r V